
tangentsky Documentation

Release 0.6.13

Josh Bialkowski

May 13, 2021

Contents

1	Installation	3
1.1	Install with pip	3
1.2	Install from source	4
1.3	IDE Integrations	4
1.4	Pre-commit	4
1.5	Docker Images	5
2	Configuration	7
3	cmake-annotate	15
4	cmake-format	17
4.1	Features	17
4.2	Usage	20
4.3	Example	24
4.4	Formatting Algorithm	28
4.5	Case Studies	32
5	cmake-lint	43
5.1	Usage	43
5.2	Inline Directives	47
5.3	Example	47
5.4	Linters Checks List	53
5.5	Lint Code Reference	54
5.6	Linters notes	63
6	ctest-to	65
6.1	Usage	65
6.2	Example	65
7	Various configuration options and parameters	67
7.1	Options affecting listfile parsing	67
7.2	Options affecting formatting.	70
7.3	Options affecting comment reflow and formatting.	87
7.4	Options affecting the linter	93
7.5	Options affecting file encoding	102
7.6	Miscellaneous configurations options.	104

8	Implementing Custom Parsers	107
8.1	Using the simple specification	107
8.2	Generating simple specifications	108
9	CMake Parse Tree	111
9.1	Tokenizer	111
9.2	Parser: Syntax Tree	113
9.3	Formatter: Layout Tree	116
9.4	Example file	118
10	Parser Algorithm	119
11	Automatic Parsers	121
11.1	Expect Objects	121
11.2	Case studies	122
11.3	Conclusion	124
12	Contributing to cmake-format	125
12.1	General Rules	125
12.2	Build Systems	125
12.3	Sidcar Tests	125
12.4	Debugging	126
12.5	Pull Requests	127
12.6	Copyright Assignment	128
12.7	Un-Assigned contributions	128
13	Release Process	129
13.1	Update master	129
13.2	Cut a Release	129
14	Release Notes	131
14.1	v0.6 series	131
14.2	v0.5 series	134
14.3	v0.4 series	136
15	Changelog	137
15.1	v0.6 series	137
15.2	v0.5 series	143
15.3	v0.4 series	146
15.4	v0.3 series	149
15.5	v0.2 series	150
16	cmake_format package	153
16.1	Module contents	153
16.2	Submodules	153
16.3	cmake_format.configuration module	153
16.4	cmake_format.common module	156
16.5	cmake_format.lexer module	157
16.6	cmake_format.markup module	157
16.7	cmake_format.parse module	157
16.8	cmake_format.parse.funs module	158
17	Indices and tables	159
	Python Module Index	161

The `cmakelang` project provides Quality Assurance (QA) and other language tools for `cmake`:

- `cmake-annotate` can generate pretty HTML from your listfiles
- `cmake-format` can format your listfiles nicely so that they don't look like crap.
- `cmake-lint` can check your listfiles for problems
- `ctest-to` can parse a `ctest` output tree and translate it into a more structured format (either JSON or XML).

CHAPTER 1

Installation

All of the tools are included as part of the `cmakelang` python distribution package.

Note: Until version 0.6.13 the software was distributed under the `cmake-format` python package. As the project grew to include multiple tools beyond the formatter, the name was changed to something more appropriate. The `cmake-format` package will be maintained for the foreseeable future as an empty package depending on `cmakelang` to ease users transition.

1.1 Install with pip

The easiest way to install `cmakelang` is from pypi.org using `pip`. For example:

```
pip install cmakelang
```

If you're on a linux-type system (such as ubuntu) the above command might not work if it would install into a system-wide location. If that's what you really want you might need to use `sudo`, e.g.:

```
sudo pip install cmakelang
```

In general though I wouldn't really recommend doing that though since things can get pretty messy between your system python distributions and your `pip` managed directories. Alternatively you can install it for your user with:

```
pip install --user cmakelang
```

which I would probably recommend for most users.

Note: If you wish to use a configuration file in YAML format you'll want to install with the optional `YAML` feature, e.g.:

```
pip install cmakelang[YAML]
```

or manually install `pyyaml`. Likewise, if you'd like to use the HTML annotator you may install with the optional `html-gen` feature, e.g.:

```
pip install cmakelang[html-gen]
```

or you may install `jinja2` manually.

1.2 Install from source

You can also install from source with `pip`. You can download a release package from [github](#) or [pypi](#) and then install it directly with `pip`. For example:

```
pip install v0.6.13.tar.gz
```

Note that the release packages on `github` are automatically generated from `git` tags which are the same commit used to generate the corresponding version package on `pypi.org`. So whether you install a particular version from `github` or `pypi` shouldn't matter.

`Pip` can also install directly from `github`. For example:

```
pip install git+https://github.com/cheshirekow/cmake_format.git
```

If you wish to test a pre-release or dev package from a branch called `foobar` you can install it with:

```
pip install "git+https://github.com/cheshirekow/cmake_format.git@foobar"
```

1.3 IDE Integrations

For the formatter specifically:

- There is an official [vscode extension](#)
- Someone also created a [sublime plugin](#)

Note that for both plugins `cmake-format` itself must be installed separately.

1.4 Pre-commit

If you are a user of the [pre-commit](#) project you can easily add the formatter, `cmake-format`, to your hooks with the following addition to your `.pre-commit-hooks.yaml` file.

```
repos:
- repo: https://github.com/cheshirekow/cmake-format-precommit
  rev: v0.6.13
  hooks:
  - id: cmake-format
```

1.5 Docker Images

There is an official docker image at [dockerhub](#). You can pull the latest with, e.g.:

```
docker pull cheshirekow/cmake-format
```


CHAPTER 2

Configuration

The different tools utilize a common parsing core and so share a common configuration system and in fact can share the same configuration file(s).

The tools accept configuration files in yaml, json, or python format.

Note: In order to read your configuration files in YAML format, the tools require the `pyyaml` python package to be installed. This dependency is not enforced by default during installation since this is an optional feature. It can be enabled by installing with a command like `pip install cmake-lang[YAML]`. Or you can install `pyyaml` manually.

You may specify a path to one or more configuration files with the `--config-file` (`--config-files`) command line option. Otherwise, the tools will search the ancestry of each source file looking for a configuration file to use. If no configuration file is found it will use sensible defaults.

Automatically detected configuration files may have any name that matches `\.?cmake-format(.yaml|.json|.py)`.

If you'd like to create a new configuration file, `cmake-format` can help by dumping out the default configuration in your preferred format. You can run `cmake-format --dump-config [python|json|yaml]` to print the default configuration to `stdout` and use that as a starting point.

Warning: `cmake-format` will detect and load an automatic configuration file, even when executing `--dump-config`. This is so that you can debug the *active* configuration from a certain location in your tree. If you have a corrupt / un-parsable configuration file in an automatic location `--dump-config` may fail. You can always `cd` to a clean location (`/` or `/tmp`) and execute `--dump-config` to get a default configuration.

Here is an example python-style configuration file with the default options and help-text. Some detailed explanation and examples can be found at [Various configuration options and parameters](#).

```
# -----  
# Options affecting listfile parsing
```

(continues on next page)

(continued from previous page)

```

# -----
with section("parse"):

    # Specify structure for custom cmake functions
    additional_commands = { 'cc_binary': { 'flags': ['ADD_RUNTARGET'],
        'kwargs': { 'DEPS': '*',
            'INC': { 'kwargs': { 'INTERFACE': '*',
                'PRIVATE': '*',
                'PUBLIC': '*' },
            'pargs': 0 },
            'LIBDIRS': { 'kwargs': { 'INTERFACE': '*',
                'PRIVATE': '*',
                'PUBLIC': '*' },
            'pargs': '*' },
            'PKGDEPS': '*',
            'PROPERTIES': { 'kwargs': { 'EXPORT_NAME': 1,
                'OUTPUT_NAME': 1 } },
            'SRCS': '*' },
        'pargs': '1+' },
    'cc_library': { 'flags': ['STATIC', 'SHARED'],
        'kwargs': { 'DEPS': { 'kwargs': { 'INTERFACE': '*',
            'PRIVATE': '*',
            'PUBLIC': '*' },
            'pargs': '*' },
            'INC': { 'kwargs': { 'INTERFACE': '*',
                'PRIVATE': '*',
                'PUBLIC': '*' },
            'pargs': 0 },
            'LIBDIRS': { 'kwargs': { 'INTERFACE': '*',
                'PRIVATE': '*',
                'PUBLIC': '*' },
            'pargs': '*' },
            'PKGDEPS': '*',
            'PROPERTIES': { 'kwargs': { 'ARCHIVE_OUTPUT_NAME': 1,
                'EXPORT_NAME': 1,
                'INTERFACE_INCLUDE_
↪DIRECTORIES': 1,
                'LIBRARY_OUTPUT_NAME': 1,
                'OUTPUT_NAME': 1,
                'SOVERSION': 1,
                'SUFFIX': 1,
                'VERSION': 1 } },
            'SRCS': '*' },
        'pargs': '1+' },
    'cc_test': { 'kwargs': { 'ARGV': '*',
        'DEPS': '*',
        'LABELS': '*',
        'PKGDEPS': '*',
        'SRCS': '*',
        'TEST_DEPS': '*',
        'WORKING_DIRECTORY': '*' },
        'pargs': 1 },
    'check_call': { 'flags': [ 'OUTPUT_QUIET',
        'ERROR_QUIET',
        'OUTPUT_STRIP_TRAILING_WHITESPACE',
        'ERROR_STRIP_TRAILING_WHITESPACE' ],
        'kwargs': { 'COMMAND': '*' },

```

(continues on next page)

(continued from previous page)

```

        'ENCODING': '1',
        'ERROR_FILE': '1',
        'ERROR_VARIABLE': '1',
        'INPUT_FILE': '1',
        'OUTPUT_FILE': '1',
        'OUTPUT_VARIABLE': '1',
        'RESULTS_VARIABLE': '1',
        'RESULT_VARIABLE': '1',
        'TIMEOUT': '1',
        'WORKING_DIRECTORY': '1'}},
'check_pyoneline': { 'kwargs': {'ERROR_VARIABLE': 1, 'OUTPUT_VARIABLE': 1},
                    'pargs': '+'},
'create_debian_binary_packages': { 'kwargs': {'DEPS': '*', 'OUTPUTS': '*'},
                                   'pargs': [3, '+']},
'create_debian_depsrepo': {'pargs': [3, '+']},
'create_debian_packages': { 'kwargs': {'DEPS': '*', 'OUTPUTS': '*'},
                            'pargs': [ { 'flags': ['FORCE_PBUILDER'],
                                         'nargs': '+'}]},
'debhelp': {'pargs': ['1+'], 'spelling': 'DEBHELP'},
'exportvars': { 'kwargs': {'VARS': '+'},
               'pargs': '1+',
               'spelling': 'EXPORTVARS'},
'format_and_lint': { 'kwargs': { 'CC': '*',
                                 'CMAKE': '*',
                                 'JS': '*',
                                 'PY': '*',
                                 'SHELL': '*'}},
'get_debs': {'pargs': [3, '*']},
'gresource': {'kwargs': {'DEPENDS': '+', 'SRCDIR': 1}, 'pargs': 2},
'gtk_doc_add_module': { 'kwargs': { 'FIXREFOPTS': '*',
                                     'IGNOREHEADERS': '*',
                                     'LIBRARIES': '*',
                                     'LIBRARY_DIRS': '*',
                                     'SOURCE': '*',
                                     'SUFFIXES': '*',
                                     'XML': 1},
                  'pargs': 1},
'importvars': { 'kwargs': {'VARS': '+'},
               'pargs': '1+',
               'spelling': 'IMPORTVARS'},
'join': {'kwargs': {'GLUE': 1}, 'pargs': [1, '+']},
'pkg_find': {'kwargs': {'PKG': '*'}},
'stage_files': { 'kwargs': { 'FILES': '*',
                             'LIST': 1,
                             'SOURCEDIR': 1,
                             'STAGE': 1}},
'tangent_addtest': { 'kwargs': { 'COMMAND': '+',
                                 'CONFIGURATIONS': '+',
                                 'DEPENDS': '+',
                                 'LABELS': '+',
                                 'NAME': 1,
                                 'WORKING_DIRECTORY': 1}},
'tangent_extract_svg': {'kwargs': {'EXPORT': 1, 'OUTPUT': 1, 'SRC': 1}},
'tangent_fetchobj': {'kwargs': {'OUTDIR': 1}, 'pargs': 2},
'tangent_rmark_render': { 'kwargs': { 'DEPENDS': 1,
                                       'FORMAT': 1,
                                       'OUTPUT': 1,

```

(continues on next page)

(continued from previous page)

```

        'PAGENO': 1,
        'UUID': 1},
        'pargs': 1},
    'tangent_unzip': { 'kwargs': {'OUTPUT': '1+', 'WORKING_DIRECTORY': 1},
        'pargs': '1+'},
    'travis_decrypt': {'kwargs': {}, 'pargs': [3]}}

# Override configurations per-command where available
override_spec = {}

# Specify variable tags.
vartags = []

# Specify property tags.
proptags = []

# -----
# Options affecting formatting.
# -----
with section("format"):

    # Disable formatting entirely, making cmake-format a no-op
    disable = False

    # How wide to allow formatted cmake files
    line_width = 80

    # How many spaces to tab for indent
    tab_size = 2

    # If true, lines are indented using tab characters (utf-8 0x09) instead of
    # <tab_size> space characters (utf-8 0x20). In cases where the layout would
    # require a fractional tab character, the behavior of the fractional
    # indentation is governed by <fractional_tab_policy>
    use_tabchars = False

    # If <use_tabchars> is True, then the value of this variable indicates how
    # fractional indentions are handled during whitespace replacement. If set to
    # 'use-space', fractional indentation is left as spaces (utf-8 0x20). If set
    # to 'round-up' fractional indentation is replaced with a single tab character
    # (utf-8 0x09) effectively shifting the column to the next tabstop
    fractional_tab_policy = 'use-space'

    # If an argument group contains more than this many sub-groups (parg or kwarg
    # groups) then force it to a vertical layout.
    max_subgroups_hwrap = 2

    # If a positional argument group contains more than this many arguments, then
    # force it to a vertical layout.
    max_pargs_hwrap = 6

    # If a cmdline positional group consumes more than this many lines without
    # nesting, then invalidate the layout (and nest)
    max_rows_cmdline = 2

    # If true, separate flow control names from their parentheses with a space
    separate_ctrl_name_with_space = False

```

(continues on next page)

(continued from previous page)

```
# If true, separate function names from parentheses with a space
separate_fn_name_with_space = False

# If a statement is wrapped to more than one line, than dangle the closing
# parenthesis on its own line.
dangle_parens = False

# If the trailing parenthesis must be 'dangled' on its own line, then align it
# to this reference: `prefix`: the start of the statement, `prefix-indent`:
# the start of the statement, plus one indentation level, `child`: align to
# the column of the arguments
dangle_align = 'prefix'

# If the statement spelling length (including space and parenthesis) is
# smaller than this amount, then force reject nested layouts.
min_prefix_chars = 4

# If the statement spelling length (including space and parenthesis) is larger
# than the tab width by more than this amount, then force reject un-nested
# layouts.
max_prefix_chars = 10

# If a candidate layout is wrapped horizontally but it exceeds this many
# lines, then reject the layout.
max_lines_hwrap = 2

# What style line endings to use in the output.
line_ending = 'unix'

# Format command names consistently as 'lower' or 'upper' case
command_case = 'canonical'

# Format keywords consistently as 'lower' or 'upper' case
keyword_case = 'unchanged'

# A list of command names which should always be wrapped
always_wrap = []

# If true, the argument lists which are known to be sortable will be sorted
# lexicographically
enable_sort = True

# If true, the parsers may infer whether or not an argument list is sortable
# (without annotation).
autosort = False

# By default, if cmake-format cannot successfully fit everything into the
# desired linewidth it will apply the last, most aggressive attempt that it
# made. If this flag is True, however, cmake-format will print error, exit
# with non-zero status code, and write-out nothing
require_valid_layout = False

# A dictionary mapping layout nodes to a list of wrap decisions. See the
# documentation for more information.
layout_passes = {}
```

(continues on next page)

(continued from previous page)

```

# -----
# Options affecting comment reflow and formatting.
# -----
with section("markup"):

    # What character to use for bulleted lists
    bullet_char = '*'

    # What character to use as punctuation after numerals in an enumerated list
    enum_char = '.'

    # If comment markup is enabled, don't reflow the first comment block in each
    # listfile. Use this to preserve formatting of your copyright/license
    # statements.
    first_comment_is_literal = False

    # If comment markup is enabled, don't reflow any comment block which matches
    # this (regex) pattern. Default is `None` (disabled).
    literal_comment_pattern = None

    # Regular expression to match preformat fences in comments default=
    # ``r'^\s*([\~]{3}[\~]*) (.*)$'``
    fence_pattern = '^\\s*([\\~]{3}[\\~]*) (.*)$'

    # Regular expression to match rulers in comments default=
    # ``r'^\s*[^\\w\\s]{3}.*[\\w\\s]{3}$'``
    ruler_pattern = '^\\s*[^\\w\\s]{3}.*[\\w\\s]{3}$'

    # If a comment line matches starts with this pattern then it is explicitly a
    # trailing comment for the preceeding argument. Default is '#<'
    explicit_trailing_pattern = '#<'

    # If a comment line starts with at least this many consecutive hash
    # characters, then don't lstrip() them off. This allows for lazy hash rulers
    # where the first hash char is not separated by space
    hashruler_min_length = 10

    # If true, then insert a space between the first hash char and remaining hash
    # chars in a hash ruler, and normalize its length to fill the column
    canonicalize_hashrulers = True

    # enable comment markup parsing and reflow
    enable_markup = True

# -----
# Options affecting the linter
# -----
with section("lint"):

    # a list of lint codes to disable
    disabled_codes = ['C0113']

    # regular expression pattern describing valid function names
    function_pattern = '[0-9a-z_]+'

    # regular expression pattern describing valid macro names
    macro_pattern = '[0-9A-Z_]+'
```

(continues on next page)

(continued from previous page)

```

# regular expression pattern describing valid names for variables with global
# (cache) scope
global_var_pattern = '[A-Z][0-9A-Z_]+'

# regular expression pattern describing valid names for variables with global
# scope (but internal semantic)
internal_var_pattern = '_[A-Z][0-9A-Z_]+'

# regular expression pattern describing valid names for variables with local
# scope
local_var_pattern = '[a-z][a-z0-9_]+'

# regular expression pattern describing valid names for privatedirectory
# variables
private_var_pattern = '_[0-9a-z_]+'

# regular expression pattern describing valid names for public directory
# variables
public_var_pattern = '[A-Z][0-9A-Z_]+'

# regular expression pattern describing valid names for function/macro
# arguments and loop variables.
argument_var_pattern = '[a-z][a-z0-9_]+'

# regular expression pattern describing valid names for keywords used in
# functions or macros
keyword_pattern = '[A-Z][0-9A-Z_]+'

# In the heuristic for C0201, how many conditionals to match within a loop in
# before considering the loop a parser.
max_conditionals_custom_parser = 2

# Require at least this many newlines between statements
min_statement_spacing = 1

# Require no more than this many newlines between statements
max_statement_spacing = 2
max_returns = 6
max_branches = 12
max_arguments = 5
max_localvars = 15
max_statements = 50

# -----
# Options affecting file encoding
# -----
with section("encode"):

    # If true, emit the unicode byte-order mark (BOM) at the start of the file
    emit_byteorder_mark = False

    # Specify the encoding of the input file. Defaults to utf-8
    input_encoding = 'utf-8'

    # Specify the encoding of the output file. Defaults to utf-8. Note that cmake
    # only claims to support utf-8 so be careful when using anything else

```

(continues on next page)

(continued from previous page)

```
output_encoding = 'utf-8'

# -----
# Miscellaneous configurations options.
# -----
with section("misc"):

    # A dictionary containing any per-command configuration overrides. Currently
    # only `command_case` is supported.
    per_command = {}
```

CHAPTER 3

cmake-annotate

The `cmake-annotate` frontend program which can create semantic HTML documents from parsed listfiles. This enables, in particular, semantic highlighting for your code documentation.

```
usage:
cmake-annotate [-h]
                [--format {page,stub}]
                [-o OUTFILE_PATH]
                [-c CONFIG_FILE]
                infilepath [infilepath ...]

Parse cmake listfiles and re-emit them with semantic annotations in HTML.

Some options regarding parsing are configurable by providing a configuration
file. The configuration file format is the same as that used by cmake-format,
and the same file can be used for both programs.

cmake-format can spit out the default configuration for you as starting point
for customization. Run with --dump-config [yaml|json|python].

positional arguments:
  infilepaths

optional arguments:
  -h, --help            show this help message and exit
  -v, --version         show program's version number and exit
  -f {page,stub,iframe}, --format {page,stub,iframe}
                        whether to output a standalone `page` complete with
                        <html></html> tags, or just the annotated content
  -o OUTFILE_PATH, --outfile-path OUTFILE_PATH
                        Where to write the formatted file. Default is stdout.
  -c CONFIG_FILE, --config-file CONFIG_FILE
                        path to configuration file
```

`--format stub` will output just the marked-up listfile content. The markup is done as `<span>` elements with different css classes for each parse-tree node or lexer token. The content is not encapsulated in any root element (such

as a `<div>`). `--format page` will embed that content into a full page with a root `<html>` and an embedded stylesheet.

The example listfile in the README, for example, can be rendered as:

`cmake-format` can format your listfiles nicely so that they don't look like crap.

4.1 Features

4.1.1 Markup

`cmake-format` is for the exceptionally lazy. It will even format your comments for you. It will reflow your comment text to within the configured line width. It also understands a very limited markup format for a couple of common bits.

rulers: A ruler is a line which starts with and ends with three or more non-alphanum or space characters:

```
# ---- This is a Ruler ----  
# cmake-format will know to keep the ruler separated from the  
# paragraphs around it. So it wont try to reflow this text as  
# a single paragraph.  
# ---- This is also a Ruler ---
```

list: A list is started on the first encountered list item, which starts with a bullet character (*) followed by a space followed by some text. Subsequent lines will be included in the list item until the next list item is encountered (the bullet must be at the same indentation level). The list must be surrounded by a pair of empty lines. Nested lists will be formatted in nested text:

```
# here are some lists:  
#  
# * item 1  
# * item 2  
#  
#   * subitem 1  
#   * subitem 2  
#  
# * second list item 1  
# * second list item 2
```

enumerations: An enumeration is similar to a list but the bullet character is some integers followed by a period. New enumeration items are detected as long as either the first digit or the punctuation lines up in the same column as the previous item. `cmake-format` will renumber your items and align their labels for you:

```
# This is an enumeration
#
# 1. item
# 2. item
# 3. item
```

fences: If you have any text which you do not want to be formatted you can guard it with a pair of fences. Fences are three or more tilde characters:

```
# ~~~
# This comment is fenced
#   and will not be formatted
# ~~~
```

Note that comment fences guard reflow of *comment text*, and not `cmake` code. If you wish to prevent formatting of `cmake`, code, see below. In addition to fenced-literals, there are three other ways to preserve comment text from markup and/or reflow processing:

- The `--first-comment-is-literal` configuration option will exactly preserve the first comment in the file. This is intended to preserve copyright or other formatted header comments.
- The `--literal-comment-pattern` configuration option allows for a more generic way to identify comments which should be preserved literally. This configuration takes a regular expression pattern.
- The `--enable-markup` configuration option globally enables comment markup processing. It defaults to `true` so set it to `false` if you wish to globally disable comment markup processing. Note that trailing whitespace is still chomped from comments.

4.1.2 Disable Formatting Locally

You can locally disable and enable code formatting by using the special comments `# cmake-format: off` and `# cmake-format: on`.

4.1.3 Sort Argument Lists

Starting with version *0.5.0*, `cmake-format` can sort your argument lists for you. If the configuration includes `autosort=True` (the default), it will replace:

```
add_library(foobar STATIC EXCLUDE_FROM_ALL
    sourcefile_06.cc
    sourcefile_03.cc
    sourcefile_02.cc
    sourcefile_04.cc
    sourcefile_07.cc
    sourcefile_01.cc
    sourcefile_05.cc)
```

with:

```
add_library(foobar STATIC EXCLUDE_FROM_ALL
    sourcefile_01.cc
```

(continues on next page)

(continued from previous page)

```

sourcefile_02.cc
sourcefile_03.cc
sourcefile_04.cc
sourcefile_05.cc
sourcefile_06.cc
sourcefile_07.cc)

```

This is implemented for any argument lists which the parser knows are inherently sortable. This includes the following cmake commands:

- `add_library`
- `add_executable`

For most other cmake commands, you can use an annotation comment to hint to `cmake-format` that the argument list is sortable. For instance:

```

set(SOURCES
    # cmake-format: sortable
    bar.cc
    baz.cc
    foo.cc)

```

Annotations can be given in a line-comment or a bracket comment. There is a long-form and a short-form for each. The acceptable formats are:

Line Comment	long	# cmake-format: <tag>
Line Comment	short	# cmf: <tag>
Bracket Comment	long	# [[cmake-format: <tag>]]
Bracket Comment	short	# [[cmf: <tag>]]

In order to annotate a positional argument list as sortable, the acceptable tags are: `sortable` or `sort`. For the commands listed above where the positional argument lists are inherently sortable, you can locally disable sorting by annotating them with `unsortable` or `unsort`. For example:

```

add_library(foofoo STATIC
    # cmake-format: unsort
    sourcefile_03.cc
    sourcefile_01.cc
    sourcefile_02.cc)

```

Note that this is only needed if your configuration has enabled `autosort`, and you can globally disable sorting by making setting this configuration to `False`.

4.1.4 Custom Commands

Due to the fact that cmake is a macro language, *cmake-format* is, by necessity, a *semantic* source code formatter. In general it tries to make smart formatting decisions based on the meaning of arguments in an otherwise unstructured list of arguments in a cmake statement. *cmake-format* can intelligently format your custom commands, but you will need to tell it how to interpret your arguments.

Currently, you can do this by adding your command specifications to the `additional_commands` configuration variables, e.g.:

```
# Additional FLAGS and KWARGS for custom commands
additional_commands = {
    "foo": {
        "pargs": 2,
        "flags": ["BAR", "BAZ"],
        "kwargs": {
            "HEADERS": '*',
            "SOURCES": '*',
            "DEPENDS": '*',
        }
    }
}
```

The format is a nested dictionary mapping statement names (dictionary keys) to [argument specifications](#). For the example specification above, the custom command would look something like this:

```
foo(hello world
    HEADERS a.h b.h c.h d.h
    SOURCES a.cc b.cc c.cc d.cc
    DEPENDS flub buzz bizz
    BAR BAZ)
```

4.2 Usage

Basic usage for `cmake-format` is:

```
usage:
cmake-format [-h]
              [--dump-config {yaml,json,python} | -i | -o OUTFILE_PATH]
              [-c CONFIG_FILE]
              infilepath [infilepath ...]

Parse cmake listfiles and format them nicely.

Formatting is configurable by providing a configuration file. The configuration
file can be in json, yaml, or python format. If no configuration file is
specified on the command line, cmake-format will attempt to find a suitable
configuration for each ``inputpath`` by checking recursively checking it's
parent directory up to the root of the filesystem. It will return the first
file it finds with a filename that matches '\.?cmake-format(.yaml|.json|.py)'.

cmake-format can spit out the default configuration for you as starting point
for customization. Run with ``--dump-config [yaml|json|python]``.

positional arguments:
  infilepathpaths

optional arguments:
  -h, --help            show this help message and exit
  -v, --version          show program's version number and exit
  -l {error,warning,info,debug}, --log-level {error,warning,info,debug}
                        If specified, print the default configuration to
                        stdout and exit
  --dump-config [{yaml,json,python}]
                        If specified, print the default configuration to
                        stdout and exit
  --dump {lex,parse,parsedb,layout,markup}
```

(continues on next page)

(continued from previous page)

```

--no-help          When used with --dump-config, will omit helptext
                   comments in the output
--no-default       When used with --dump-config, will omit any unmodified
                   configuration value.
-i, --in-place
--check           Exit with status code 0 if formatting would not change
                   file contents, or status code 1 if it would
-o OUTFILE_PATH, --outfile-path OUTFILE_PATH
                   Where to write the formatted file. Default is stdout.
-c CONFIG_FILES [CONFIG_FILES ...], --config-files CONFIG_FILES [CONFIG_FILES ...]
                   path to configuration file(s)

```

Nearly all *Configuration* options are also available as command line options:

```

Options affecting listfile parsing:
--vartags [VARTAGS [VARTAGS ...]]
                   Specify variable tags.
--proptags [PROPTAGS [PROPTAGS ...]]
                   Specify property tags.

Options affecting formatting.:
--disable [DISABLE] Disable formatting entirely, making cmake-format a no-
                   op
--line-width LINE_WIDTH
                   How wide to allow formatted cmake files
--tab-size TAB_SIZE How many spaces to tab for indent
--use-tabchars [USE_TABCHARS]
                   If true, lines are indented using tab characters
                   (utf-8 0x09) instead of <tab_size> space characters
                   (utf-8 0x20). In cases where the layout would require
                   a fractional tab character, the behavior of the
                   fractional indentation is governed by
                   <fractional_tab_policy>
--fractional-tab-policy {use-space,round-up}
                   If <use_tabchars> is True, then the value of this
                   variable indicates how fractional indentions are
                   handled during whitespace replacement. If set to 'use-
                   space', fractional indentation is left as spaces
                   (utf-8 0x20). If set to 'round-up' fractional
                   indentation is replaced with a single tab character
                   (utf-8 0x09) effectively shifting the column to the
                   next tabstop
--max-subgroups-hwrap MAX_SUBGROUPS_HWRAP
                   If an argument group contains more than this many sub-
                   groups (parg or kwarg groups) then force it to a
                   vertical layout.
--max-pargs-hwrap MAX_PARGS_HWRAP
                   If a positional argument group contains more than this
                   many arguments, then force it to a vertical layout.
--max-rows-cmdline MAX_ROWS_CMDLINE
                   If a cmdline positional group consumes more than this
                   many lines without nesting, then invalidate the layout
                   (and nest)
--separate-ctrl-name-with-space [SEPARATE_CTRL_NAME_WITH_SPACE]
                   If true, separate flow control names from their
                   parentheses with a space

```

(continues on next page)

(continued from previous page)

```

--separate-fn-name-with-space [SEPARATE_FN_NAME_WITH_SPACE]
    If true, separate function names from parentheses with
    a space
--dangle-parens [DANGLE_PARENS]
    If a statement is wrapped to more than one line, than
    dangle the closing parenthesis on its own line.
--dangle-align {prefix,prefix-indent,child,off}
    If the trailing parenthesis must be 'dangled' on its
    on line, then align it to this reference: `prefix`:
    the start of the statement, `prefix-indent`: the start
    of the statement, plus one indentation level, `child`:
    align to the column of the arguments
--min-prefix-chars MIN_PREFIX_CHARS
    If the statement spelling length (including space and
    parenthesis) is smaller than this amount, then force
    reject nested layouts.
--max-prefix-chars MAX_PREFIX_CHARS
    If the statement spelling length (including space and
    parenthesis) is larger than the tab width by more than
    this amount, then force reject un-nested layouts.
--max-lines-hwrap MAX_LINES_HWRAP
    If a candidate layout is wrapped horizontally but it
    exceeds this many lines, then reject the layout.
--line-ending {windows,unix,auto}
    What style line endings to use in the output.
--command-case {lower,upper,canonical,unchanged}
    Format command names consistently as 'lower' or
    'upper' case
--keyword-case {lower,upper,unchanged}
    Format keywords consistently as 'lower' or 'upper'
    case
--always-wrap [ALWAYS_WRAP [ALWAYS_WRAP ...]]
    A list of command names which should always be wrapped
--enable-sort [ENABLE_SORT]
    If true, the argument lists which are known to be
    sortable will be sorted lexicographicall
--autosort [AUTOSORT]
    If true, the parsers may infer whether or not an
    argument list is sortable (without annotation).
--require-valid-layout [REQUIRE_VALID_LAYOUT]
    By default, if cmake-format cannot successfully fit
    everything into the desired linewidth it will apply
    the last, most aggressive attempt that it made. If this
    flag is True, however, cmake-format will print error,
    exit with non-zero status code, and write-out nothing

Options affecting comment reflow and formatting.:
--bullet-char BULLET_CHAR
    What character to use for bulleted lists
--enum-char ENUM_CHAR
    What character to use as punctuation after numerals in
    an enumerated list
--first-comment-is-literal [FIRST_COMMENT_IS_LITERAL]
    If comment markup is enabled, don't reflow the first
    comment block in each listfile. Use this to preserve
    formatting of your copyright/license statements.
--literal-comment-pattern LITERAL_COMMENT_PATTERN

```

(continues on next page)

(continued from previous page)

```

        If comment markup is enabled, don't reflow any comment
        block which matches this (regex) pattern. Default is
        `None` (disabled).
--fence-pattern FENCE_PATTERN
        Regular expression to match preformat fences in
        comments default= ``r'^\s*([~]{3}[~]*) (.*)$'``
--ruler-pattern RULER_PATTERN
        Regular expression to match rulers in comments
        default= ``r'^\s*([^\w\s]{3}.*[^\w\s]{3})$'``
--explicit-trailing-pattern EXPLICIT_TRAILING_PATTERN
        If a comment line matches starts with this pattern
        then it is explicitly a trailing comment for the
        preceeding argument. Default is '#<'
--hashruler-min-length HASHRULER_MIN_LENGTH
        If a comment line starts with at least this many
        consecutive hash characters, then don't lstrip() them
        off. This allows for lazy hash rulers where the first
        hash char is not separated by space
--canonicalize-hashrulers [CANONICALIZE_HASHRULERS]
        If true, then insert a space between the first hash
        char and remaining hash chars in a hash ruler, and
        normalize its length to fill the column
--enable-markup [ENABLE_MARKUP]
        enable comment markup parsing and reflow

```

Options affecting the linter:

```

--disabled-codes [DISABLED_CODES [DISABLED_CODES ...]]
        a list of lint codes to disable
--function-pattern FUNCTION_PATTERN
        regular expression pattern describing valid function
        names
--macro-pattern MACRO_PATTERN
        regular expression pattern describing valid macro
        names
--global-var-pattern GLOBAL_VAR_PATTERN
        regular expression pattern describing valid names for
        variables with global (cache) scope
--internal-var-pattern INTERNAL_VAR_PATTERN
        regular expression pattern describing valid names for
        variables with global scope (but internal semantic)
--local-var-pattern LOCAL_VAR_PATTERN
        regular expression pattern describing valid names for
        variables with local scope
--private-var-pattern PRIVATE_VAR_PATTERN
        regular expression pattern describing valid names for
        private directory variables
--public-var-pattern PUBLIC_VAR_PATTERN
        regular expression pattern describing valid names for
        public directory variables
--argument-var-pattern ARGUMENT_VAR_PATTERN
        regular expression pattern describing valid names for
        function/macro arguments and loop variables.
--keyword-pattern KEYWORD_PATTERN
        regular expression pattern describing valid names for
        keywords used in functions or macros
--max-conditionals-custom-parser MAX_CONDITIONALS_CUSTOM_PARSER
        In the heuristic for C0201, how many conditionals to

```

(continues on next page)

(continued from previous page)

```

        match within a loop in before considering the loop a
        parser.
--min-statement-spacing MIN_STATEMENT_SPACING
        Require at least this many newlines between statements
--max-statement-spacing MAX_STATEMENT_SPACING
        Require no more than this many newlines between
        statements
--max-returns MAX_RETURNS
--max-branches MAX_BRANCHES
--max-arguments MAX_ARGUMENTS
--max-localvars MAX_LOCALVARS
--max-statements MAX_STATEMENTS

Options affecting file encoding:
--emit-byteorder-mark [EMIT_BYTEORDER_MARK]
        If true, emit the unicode byte-order mark (BOM) at the
        start of the file
--input-encoding INPUT_ENCODING
        Specify the encoding of the input file. Defaults to
        utf-8
--output-encoding OUTPUT_ENCODING
        Specify the encoding of the output file. Defaults to
        utf-8. Note that cmake only claims to support utf-8 so
        be careful when using anything else

```

4.3 Example

Will turn this:

```

# The following multiple newlines should be collapsed into a single newline

cmake_minimum_required(VERSION 2.8.11)
project(cmakelang_test)

# This multiline-comment should be reflowed
# into a single comment
# on one line

# This comment should remain right before the command call.
# Furthermore, the command call should be formatted
# to a single line.
add_subdirectories(foo bar baz
    foo2 bar2 baz2)

# This very long command should be wrapped
set(HEADERS very_long_header_name_a.h very_long_header_name_b.h very_long_header_name_
↪c.h)

# This command should be split into one line per entry because it has a long argument_
↪list.
set(SOURCES source_a.cc source_b.cc source_d.cc source_e.cc source_f.cc source_g.cc_
↪source_h.cc)

```

(continues on next page)

(continued from previous page)

```

# The string in this command should not be split
set_target_properties(foo bar baz PROPERTIES COMPILE_FLAGS "-std=c++11 -Wall -Wextra")

# This command has a very long argument and can't be aligned with the command
# end, so it should be moved to a new line with block indent + 1.
some_long_command_name("Some very long argument that really needs to be on the next
↳line.")

# This situation is similar but the argument to a KWARG needs to be on a
# newline instead.
set(CMAKE_CXX_FLAGS "-std=c++11 -Wall -Wno-sign-compare -Wno-unused-parameter -xx")

set(HEADERS header_a.h header_b.h # This comment should
                                # be preserved, moreover it should be split
                                # across two lines.
    header_c.h header_d.h)

# This part of the comment should
# be formatted
# but...
# cmake-format: off
# This bunny should remain untouched:
# .
# | |
# ()
# c( uu}
# cmake-format: on
#     while this part should
#     be formatted again

# This is a paragraph
#
# This is a second paragraph
#
# This is a third paragraph

# This is a comment
# that should be joined but
# TODO(josh): This todo should not be joined with the previous line.
# NOTE(josh): Also this should not be joined with the todo.

if(foo)
if(sbar)
# This comment is in-scope.
add_library(foo_bar_baz foo.cc bar.cc # this is a comment for arg2
                                       # this is more comment for arg2, it should be
↳joined with the first.
    baz.cc) # This comment is part of add_library

other_command(some_long_argument some_long_argument) # this comment is very long and
↳gets split across some lines

other_command(some_long_argument some_long_argument some_long_argument) # this
↳comment is even longer and wouldn't make sense to pack at the end of the command so
↳it gets it's own lines

```

(continues on next page)

(continued from previous page)

```

endif()
endif()

# This very long command should be broken up along keyword arguments
foo(nonkwarg_a nonkwarg_b HEADERS a.h b.h c.h d.h e.h f.h SOURCES a.cc b.cc d.cc_
↳DEPENDS foo bar baz)

# This command uses a string with escaped quote chars
foo(some_arg some_arg "This is a \"string\" within a string")

# This command uses an empty string
foo(some_arg some_arg "")

# This command uses a multiline string
foo(some_arg some_arg "
    This string is on multiple lines
")

# No, I really want this to look ugly
# cmake-format: off
add_library(a b.cc
            c.cc      d.cc
                  e.cc)
# cmake-format: on

```

into this:

```

# The following multiple newlines should be collapsed into a single newline

cmake_minimum_required(VERSION 2.8.11)
project(cmakelang_test)

# This multiline-comment should be reflowed into a single comment on one line

# This comment should remain right before the command call. Furthermore, the
# command call should be formatted to a single line.
add_subdirectories(foo bar baz foo2 bar2 baz2)

# This very long command should be wrapped
set(HEADERS very_long_header_name_a.h very_long_header_name_b.h
      very_long_header_name_c.h)

# This command should be split into one line per entry because it has a long
# argument list.
set(SOURCES
    source_a.cc
    source_b.cc
    source_d.cc
    source_e.cc
    source_f.cc
    source_g.cc
    source_h.cc)

# The string in this command should not be split
set_target_properties(foo bar baz PROPERTIES COMPILE_FLAGS
      "-std=c++11 -Wall -Wextra")

```

(continues on next page)

(continued from previous page)

```

# This command has a very long argument and can't be aligned with the command
# end, so it should be moved to a new line with block indent + 1.
some_long_command_name(
    "Some very long argument that really needs to be on the next line.")

# This situation is similar but the argument to a KWARG needs to be on a newline
# instead.
set(CMAKE_CXX_FLAGS
    "-std=c++11 -Wall -Wno-sign-compare -Wno-unused-parameter -xx")

set(HEADERS
    header_a.h header_b.h # This comment should be preserved, moreover it should
                          # be split across two lines.
    header_c.h header_d.h)

# This part of the comment should be formatted but...
# cmake-format: off
# This bunny should remain untouched:
# .
# | |
# ()
# c( uu}
# cmake-format: on
# while this part should be formatted again

# This is a paragraph
#
# This is a second paragraph
#
# This is a third paragraph

# This is a comment that should be joined but
# TODO(josh): This todo should not be joined with the previous line.
# NOTE(josh): Also this should not be joined with the todo.

if(foo)
    if(sbar)
        # This comment is in-scope.
        add_library(
            foo_bar_baz
            foo.cc bar.cc # this is a comment for arg2 this is more comment for arg2,
                          # it should be joined with the first.
            baz.cc) # This comment is part of add_library

        other_command(
            some_long_argument some_long_argument) # this comment is very long and
                                                    # gets split across some lines

        other_command(
            some_long_argument some_long_argument some_long_argument) # this comment
                                                                        # is even longer
                                                                        # and wouldn't
                                                                        # make sense to
                                                                        # pack at the
                                                                        # end of the
                                                                        # command so it

```

(continues on next page)

(continued from previous page)

```

# gets it's own
# lines

endif()
endif()

# This very long command should be broken up along keyword arguments
foo(nonkwarg_a nonkwarg_b
    HEADERS a.h b.h c.h d.h e.h f.h
    SOURCES a.cc b.cc d.cc
    DEPENDS foo
    bar baz)

# This command uses a string with escaped quote chars
foo(some_arg some_arg "This is a \"string\" within a string")

# This command uses an empty string
foo(some_arg some_arg "")

# This command uses a multiline string
foo(some_arg some_arg "
    This string is on multiple lines
")

# No, I really want this to look ugly
# cmake-format: off
add_library(a b.cc
    c.cc      d.cc
             e.cc)
# cmake-format: on

```

4.4 Formatting Algorithm

The formatter works by attempting to select an appropriate position and wrap (collectively referred to as a “lay-out”) for each node in the layout tree. Positions are represented by (row, col) pairs and the wrap dictates how children of that node are positioned.

4.4.1 Wrapping

cmake-format implements three styles of wrapping. The default wrapping for all nodes is horizontal wrapping. If horizontal wrapping fails to emit an admissible layout, then a node will advance to either vertical wrapping or nested wrapping (which one depends on the type of node).

Horizontal Wrapping

Horizontal wrapping is like “word wrap”. Each child is assigned a position immediately following its predecessor, so long as that child fits in the remaining space up to the column limit. Otherwise the child is moved to the next line:

```

|                                     |<- col-limit
|           |
|       |
|           |

```


(continued from previous page)

Nesting

Nesting places children in a column which is one `tab_width` to the right of the parent node's position, and one line below. For example:

```
|<- col-limit
```

In a more deeply nested layout tree, we might see the following:

Depending on how `cmake-format` is configured, elements at different depths may be nested differently. For example:

Note that the only nodes that can nest are `STATEMENT` and `KWARGGROUP` nodes. These nodes necessarily only have one child, an `ARGGROUP` node. Therefore there really isn't a notion of "wrapping" for these nodes.

4.4.2 Formatting algorithm

For top-level nodes in the layout tree (i.e. `COMMENT`, `STATEMENT`, `BODY`, `FLOW_CONTROL`, etc...) the positioning is straight forward and these nodes are laid out in a single pass. Each child is positioned on the first line after the output cursor of it's predecessor, and at a column `config.format.tab_size` to the right of it's parent.

STATEMENTS however, are laid out over several passes until the text for that subtree is accepted. Each pass is governed by a specification mapping pass number to a wrap decision (i.e. a boolean indicating whether or not to wrap vertical or nest children)

Layout Passes

The current algorithm works in a kind of top-down refinement. When a node is laid out by calling its `reflow()` method, it is informed of its parent's current pass number (`passno`). It then iterates through its own `passno` from zero up to its parent's `passno` and terminates at the first admissible layout. Note that within the layout of the node itself, its current `passno` can only affect its `wrap` decision. However, because each of its children will advance through their own passes, the overall layout of a subtree between two different passes may change, even if the node at the subtree root didn't change its `wrap` decision between those passes.

This approach seems to work well even for *deeply nested* or *complex* statements.

Newline decision

When a node is in horizontal layout mode (`wrap=False`), there are a couple of reasons why the algorithm might choose to insert a newline between two of its children.

1. If a token would overflow the column limit, insert a newline (e.g. the usual notion of wrapping)
2. If the token is the last token before a closing parenthesis, and the token plus the parenthesis would overflow the column limit, then insert a newline.
3. If a token is preceded by a line comment, then the token cannot be placed on the same line as the comment (or it will become part of the comment) so a newline is inserted between them.
4. If a token is a line comment which is not associated with an argument (e.g. it is a “free” comment at the current scope) then it will not be placed on the same line as a preceding argument token. If it was, then subsequent parses would associate this comment with that argument. In such a case, a newline is inserted between the preceding argument and the line comment.
5. If the node is an interior node, and one of its children is internally wrapped (i.e. consumes more than two lines) then it will not be placed on the same line as another node. In such a case a newlines is inserted.
6. If the node is an interior node and a child fails to find an admissible layout at the current cursor, a newline is inserted and a new layout attempt is made for the child.

Admissible layouts

There are a couple of reasons why a layout may be deemed inadmissible:

1. If the bounding box of a node overflows the column limit
2. If a node is horizontally wrapped at the current `passno` but consumes more than `max_lines_hwrap` lines
3. If the node is horizontally wrapped at the current `passno` but the node path is marked as `always_wrap`

Comments

A (multi-line) comment on the last row does not contribute to the height for the purposes of this thresholding, but one on any other line does. Another way to say this is that comments are excluded from the size computation, but their influence on other argument is not:

```
# This content is 3 lines tall
foobarbaz_hello(
    argument_one argument_two # this comment is two lines long and it
                              # forces the next argument onto line three
    argument_three argument_four)
```

(continues on next page)

(continued from previous page)

```
# This is only 2 lines tall
foobarbaz_hello(
    argument_one argument_two argument_three
    argument_four # this comment is two lines long and wraps but it
    # has no contribution to the size of the content.
```

Dealing with comments during horizontal wrapping can be a little tricky. They definitely induce a newline at their termination, but they may also predicate a newline in front of the commented argument. See the examples in [Case Studies/Comments](#). We don't necessarily need to deal with this right now. The user can always force the issue by adding some comment strings that force a comment width, like this:

```
set(HEADERS header_a.h header_b.h header_c.h
    header_d.h # This comment is pretty long and if it's argument is close
                # to the edge of the column then the comment gets wrapped
                # very poorly -----
    header_e.h header_f.h)
```

The string of dashes ----- is long enough that the minimum width of the comment block is given by:

```
# This comment is pretty
# long and if it's
# argument is close to the
# edge of the column then
# the comment gets wrapped
# very poorly
# -----
```

Which would preclude it from being crammed into the right-most slot.

4.5 Case Studies

This is a collection of interesting cases that are illustrative of different concepts for formatting options.

4.5.1 Positional Arguments

Lots of short args, looks good all on one line:

```
add_subdirectories(foo bar baz foo2 bar2 baz2)
```

Also doesn't look too bad when wrapped horizontally:

```
add_subdirectories(
    foo bar baz foo2 bar2 baz2 foo3 bar3 baz3 foo4 bar4 baz4 foo5 bar5 baz5
    foo6 bar6 baz6 foo7 bar7 baz7 foo8 bar8 baz8 foo9 bar9 baz9)
```

Though probably matches expectations better if it is wrapped vertically, even if it does look like shit:

```
add_subdirectories(
    foo
    bar
    baz
```

(continues on next page)

(continued from previous page)

```

foo2
bar2
baz2
foo3
bar3
baz3
foo4
bar4
baz4
foo5
bar5
baz5
foo6
bar6
baz6
foo7
bar7
baz7
foo8
bar8
baz8
foo9
bar9
baz9)

```

Just a couple of long args, looks bad wrapped horizontally:

```

set (HEADERS very_long_header_name_a.h very_long_header_name_b.h
    very_long_header_name_c.h)

```

and looks better wrapped vertically, horizontally nested:

```

set (HEADERS
    very_long_header_name_a.h
    very_long_header_name_b.h
    very_long_header_name_c.h)

```

also looks pretty good packed after the first argument:

```

set (HEADERS very_long_header_name_a.h
    very_long_header_name_b.h
    very_long_header_name_c.h)

```

or possibly nested:

```

set (HEADERS
    very_long_header_name_a.h
    very_long_header_name_b.h
    very_long_header_name_c.h)

set (
    HEADERS
    very_long_header_name_a.h
    very_long_header_name_b.h
    very_long_header_name_c.h)

```

(continues on next page)

(continued from previous page)

but this starts to look a little inconsistent when other arguments are used::

```
set(  
  HEADERS PARENT_SCOPE  
  very_long_header_name_a.h  
  very_long_header_name_b.h  
  very_long_header_name_c.h)
```

Lots of medium-length args, looks good vertical, horizontally nested:

```
set(SOURCES  
  source_a.cc  
  source_b.cc  
  source_d.cc  
  source_e.cc  
  source_f.cc  
  source_g.cc)
```

Interestingly, if the PARGGROUP list is one level deeper, the distinction between what looks good is a little blurrier. With lots of short names, I think it looks good both ways:

```
# This very long command should be broken up along keyword arguments  
foo(nonkwarg_a nonkwarg_b  
  HEADERS a.h b.h c.h d.h e.h f.h  
  SOURCES a.cc b.cc d.cc  
  DEPENDS foo  
  bar baz)
```

versus:

```
# This very long command should be broken up along keyword arguments  
foo(nonkwarg_a nonkwarg_b  
  HEADERS a.h  
          b.h  
          c.h  
          d.h  
          e.h  
          f.h  
  SOURCES a.cc b.cc d.cc  
  DEPENDS foo  
  bar baz)
```

though it does seem like the same rules can be applied here if we include some configuration for both number of arguments and length of arguments.

4.5.2 Keyword Arguments

When children include both positionals and keyword arguments, it looks good with each group wrapped vertically, while grand children are wrapped horizontally:

```
set_target_properties(  
  foo bar baz  
  PROPERTIES COMPILE_FLAGS "-std=c++11 -Wall -Wextra")
```

I think it makes sense even with just a single positional, even if it is a little sparsish:

```
set_target_properties(
  foo
  PROPERTIES COMPILE_FLAGS "-std=c++11 -Wall -Wextra -Wfoobarbazoption")
```

Another option is to put the “short” positional arguments on the first line, but while this might look good in some cases I think the cost of inconsistency is high. This also introduces some readability issues in that the positional arguments are easy to overlook in this layout:

```
set_target_properties(foo
  PROPERTIES COMPILE_FLAGS "-std=c++11 -Wall -Wextra -Wfoobarbazoption")
```

Though in the case that it could all be on one line so we should do that:

```
set_target_properties(
  foo PROPERTIES COMPILE_FLAGS "-std=c++11 -Wall -Wextra")
```

And `set_target_properties` is actually kind of special because `PROPERTIES` doesn't act much like a keyword. It's more of a separator after which we parse things in pairs. This might look nicer, but I'm not sure we can really make it fit with other rules:

```
set_target_properties(
  foo PROPERTIES
  COMPILE_FLAGS "-std=c++11 -Wall -Wextra -Wfoobarbazoption"
  LINKER_FLAGS "-fpic -someotheroption")
```

Though with custom parse logic we might be able to do so. The custom parser would include `PROPERTIES` in the positional arguments and would label the first half of each pair as a `KEYWORD` node.

4.5.3 set()

`set()` is somewhat of a special case due to things like this:

```
set(args
  OUTPUT fizz.txt
  COMMAND foo --bar --baz
  DEPENDS foo.txt bar.txt baz.txt
  COMMENT "This is my rule"
  BYPRODUCTS buzz.txt)
add_custom_command(${arg})
```

I suppose it's not the worse case that we just horizontally wrap it by default in which case the user can enforce wrapping with line comments. It would be nice if they could somehow annotate it though, like with a comment `# cmf: as=add_custom_command`. That sounds complicated though. One really fancy solution would be to scan for potential kwargs, then try to match against a known command based on the registry.

Note that `set()` isn't the only command like this. There are likely to be other commands, specifically wrapper commands, that might take an unstructured argument list which becomes structured under the hood.

4.5.4 Comments

Argument comments can get a little tricky, because this looks bad:

```
set(HEADERS header_a.h header_b.h header_c.h header_d.h # This comment is
                                                    # pretty long and
                                                    # if it's argument
                                                    # is close to the
                                                    # edge of the column
                                                    # then the comment
                                                    # gets wrapped very
                                                    # poorly
header_e.h header_f.h)
```

and this looks good:

```
set(HEADERS
  header_a.h
  header_b.h
  header_c.h
  header_d.h # This comment is pretty long and if it's argument is close
              # to the edge of the column then the comment gets wrapped
              # very poorly
  header_e.h
  header_f.h)
```

but this also looks acceptable and I could imagine some organization choosing to go this route with their style configuration:

```
set(HEADERS header_a.h header_b.h header_c.h
  header_d.h # This comment is pretty long and if it's argument is close
              # to the edge of the column then the comment gets wrapped
              # very poorly
  header_e.h header_f.h)
```

So I'm not sure that the presence of a line comment should necessarily predicate a vertical wrapping. Rather, I think the choice of wrapping strategy should be independant of the presence of a comment. In the case of horizontal wrapping though, we need some kind of threshold or score to determine when a comment has gotten “too smooshed” and the whole thing should move to the next line. In the example above:

```
# option A:
set(HEADERS header_a.h header_b.h header_c.h header_d.h # This comment is
                                                    # pretty long and
                                                    # if it's argument
                                                    # is close to the
                                                    # edge of the column
                                                    # then the comment
                                                    # gets wrapped very
                                                    # poorly
header_e.h header_f.h)

# option B:
set(HEADERS header_a.h header_b.h header_c.h
  header_d.h # This comment is pretty long and if it's argument is close
              # to the edge of the column then the comment gets wrapped
              # very poorly
  header_e.h header_f.h)
```

“Option A” lays out the comment on eight lines while “option B” lays out the comment in three lines. I’m not sure what the threshold should be for choosing one over the other. Should it be based on how many lines the comment is, or how much whitespace we introduce due to it? In “Option A” we introduce seven lines of whitespace between

consecutive rows of arguments whereas in “Option B” we only add two. Should it be based on aspect ratio?

And, honestly, “Option A” isn’t all that bad. I’m not sure it would cross everyones threshold for inducing a wrap.

For this particular example I think the best looking layout is the vertical wrapping, but we don’t want the presence of a line comment to automatically induce vertical wrapping. For instance in this example, we definitely want to keep horizontal wrapping, we just want the line comment to induce an early wrap:

```
add_custom_command(
  OUTPUT ${CMAKE_CURRENT_BINARY_DIR}/foobar_doc.stamp
  COMMAND sphinx-build -M html #
    ${CMAKE_CURRENT_SOURCE_DIR} #
    ${CMAKE_CURRENT_BINARY_DIR}
  COMMAND touch ${CMAKE_CURRENT_BINARY_DIR}/foobar_doc.stamp
  DEPENDS ${foobar_docs}
  WORKING_DIRECTORY ${CMAKE_SOURCE_DIR})
```

One compromise solution is to change the behavior of the line comment depending on the nature of the PARGGROUP. The parser can tag each PARGGROUP with it’s `default_wrap` (either “horizontal” or “vertical”). Then, when a wrap is required the default wrap can be used. A wrap might be required due to:

- arguments overflow the column width
- exceed threshold in number or size of arguments
- presence of a line comment

This compromise is the reason the previous version of `cmake-format` had a distinct `HPACK` wrapping algorithm. It allowed us a configuration where all wrapping would be vertical wrapping.

A second compromise solution, which is compatible with the previous solution, is to make the wrapping tunable by an annotation comment. For instance:

```
add_custom_command(
  OUTPUT ${CMAKE_CURRENT_BINARY_DIR}/foobar_doc.stamp
  COMMAND sphinx-build -M html # cmf:hwrap
    ${CMAKE_CURRENT_SOURCE_DIR} #
    ${CMAKE_CURRENT_BINARY_DIR}
  COMMAND touch ${CMAKE_CURRENT_BINARY_DIR}/foobar_doc.stamp
  DEPENDS ${foobar_docs}
  WORKING_DIRECTORY ${CMAKE_SOURCE_DIR})
```

where the `hwrap` annotation would change the default behavior of the line comment from inducing vertical wrapping to inducing a newline within vertical wrapping. If the annotation syntax requires too many characters, we could use something like double-hash `##`, hash-h `#h``, or hash-v (``#v`) for this purpose. This could be a standard “microtag” format including the ability to set the list sortable. For example: `#v, s` would be “vertical, sortable”

Another interesting case is if we have an argument comment on a keyword argument, or a prefix group. For example:

```
set(foobarbaz # comment about foobarbaz
    value_one value_two value_three value_four value_five value_six
    value_seven value_eight)
```

Should that be formatted as above, or as:

```
set(foobarbaz # comment about foobarbaz
    value_one value_two value_three value_four value_five
    value_six value_seven value_eight)
```

If we’re already formatting `set` as:

```
set(foofoobarbaz value_one value_two value_three value_four value_five
    value_six value_seven value_eight)
```

4.5.5 Nesting

When logic get's nested, the need to nest after long command names becomes more apparent:

```
if(foo)
  if(sbar)
    # This comment is in-scope.
    add_library(
      foo_bar_baz
      foo.cc
      bar.cc # this is a comment for arg2 this is more comment for
             # arg2, it should be joined with the first.
      baz.cc) # This comment is part of add_library

    other_command(
      some_long_argument some_long_argument) # this comment is very
                                              # long and gets split
                                              # across some lines

    other_command(some_long_argument some_long_argument some_long_argument)
    # this comment is even longer and wouldn't make sense to pack at the
    # end of the command so it gets it's own lines
  endif()
endif()
```

Another good example is `add_custom_comand()`:

```
add_custom_command(
  OUTPUT ${CMAKE_CURRENT_BINARY_DIR}/foobar_doc.stamp
  COMMAND sphinx-build -M html ${CMAKE_CURRENT_SOURCE_DIR}
           ${CMAKE_CURRENT_BINARY_DIR}
  COMMAND touch ${CMAKE_CURRENT_BINARY_DIR}/foobar_doc.stamp
  DEPENDS ${foobar_docs}
  WORKING_DIRECTORY ${CMAKE_SOURCE_DIR})
```

But note the tricky bit here. I think we definitely want the `COMMAND ARGGROUP` (which is a single `PARGGROUP`) to be horizontally wrapped.

There are also some commands with second (or more) levels of keyword arguments, and it's not clear if the nesting rules are best applied top-down:

```
install(
  TARGETS foo bar baz
  ARCHIVE DESTINATION <dir>
           PERMISSIONS OWNER_READ OWNER_WRITE OWNER_EXECUTE
           CONFIGURATIONS Debug Release
           COMPONENT foo-component
           OPTIONAL EXCLUDE_FROM_ALL NAMELINK_SKIP
  LIBRARY DESTINATION <dir>
           PERMISSIONS OWNER_READ OWNER_WRITE OWNER_EXECUTE
           CONFIGURATIONS Debug Release
           COMPONENT foo-component
           OPTIONAL EXCLUDE_FROM_ALL NAMELINK_SKIP
```

(continues on next page)

(continued from previous page)

```

RUNTIME DESTINATION <dir>
      PERMISSIONS OWNER_READ OWNER_WRITE OWNER_EXECUTE
      CONFIGURATIONS Debug Release
      COMPONENT foo-component
      OPTIONAL EXCLUDE_FROM_ALL NAMELINK_SKIP)

```

Or bottom-up:

```

install(
  TARGETS foo bar baz
  ARCHIVE
    DESTINATION <dir>
    PERMISSIONS OWNER_READ OWNER_WRITE OWNER_EXECUTE
    CONFIGURATIONS Debug Release
    COMPONENT foo-component
    OPTIONAL EXCLUDE_FROM_ALL NAMELINK_SKIP
  LIBRARY
    DESTINATION <dir>
    PERMISSIONS OWNER_READ OWNER_WRITE OWNER_EXECUTE
    CONFIGURATIONS Debug Release
    COMPONENT foo-component
    OPTIONAL EXCLUDE_FROM_ALL NAMELINK_SKIP
  RUNTIME
    DESTINATION <dir>
    PERMISSIONS OWNER_READ OWNER_WRITE OWNER_EXECUTE
    CONFIGURATIONS Debug Release
    COMPONENT foo-component
    OPTIONAL EXCLUDE_FROM_ALL NAMELINK_SKIP)

```

4.5.6 Conditionals

Treating boolean operators as keyword arguments works pretty well, so long as we treat parenthetical groups as a single unit:

```

set(matchme "_DATA_\\|_CMAKE_\\|_INTRA_PRED_\\|_COMPILED_\\|_HOSTING_\\|_PERF_\\|_CODER_")
if(("${var}" MATCHES "_TEST_" AND NOT "${var}" MATCHES "${matchme}")
    OR (CONFIG_AV1_ENCODER
        AND CONFIG_ENCODE_PERF_TESTS
        AND "${var}" MATCHES "_ENCODE_PERF_TEST_")
    OR (CONFIG_AV1_DECODER
        AND CONFIG_DECODE_PERF_TESTS
        AND "${var}" MATCHES "_DECODE_PERF_TEST_")
    OR (CONFIG_AV1_ENCODER AND "${var}" MATCHES "_TEST_ENCODER_")
    OR (CONFIG_AV1_DECODER AND "${var}" MATCHES "_TEST_DECODER_"))
  list(APPEND aom_test_source_vars ${var})
endif()

```

I don't think there's any reason to add structure for the internal operators like MATCHES. In particular children of a boolean operator can be simple positional argument groups (horizontally-wrapped). We can tag the internal operator as a keyword but we don't need to create a KWARGGROUP for it.

4.5.7 Internally Wrapped Positionals

The third kwarg (AND) in this statement looks bad because it is Internally wrapped. The second option looks better:

```
set(matchme "_DATA_\|_CMAKE_\|INTRA_PRED\|_COMPILED\|_HOSTING\|_PERF_\|CODER_")
if("${var}" MATCHES "_TEST_" AND NOT "${var}" MATCHES "${matchme}")
    OR (CONFIG_AV1_ENCODER AND CONFIG_ENCODE_PERF_TESTS AND "${var}" MATCHES
                                              "_ENCODE_PERF_TEST_"
    )
    list(APPEND aom_test_source_vars ${var})
endif()

set(matchme "_DATA_\|_CMAKE_\|INTRA_PRED\|_COMPILED\|_HOSTING\|_PERF_\|CODER_")
if("${var}" MATCHES "_TEST_" AND NOT "${var}" MATCHES "${matchme}")
    OR (CONFIG_AV1_ENCODER
        AND CONFIG_ENCODE_PERF_TESTS
        AND "${var}" MATCHES "_ENCODE_PERF_TEST_")
    list(APPEND aom_test_source_vars ${var})
endif()
```

However, this short `set()` statement looks better if we don't push the internally wrapped argument to the next line:

```
set(sources # cmake-format: sortable
      bar.cc baz.cc foo.cc)
```

Perhaps the difference is that in the latter case it's going to consume two lines anyway... whereas in the former case it would only consume one line.

4.5.8 Columnized arguments

Some very long statements with a large number of keywords might look nice and organized if we columize the child argument groups. For example:

```
ExternalProject_Add(
  FOO
  PREFIX           ${FOO_PREFIX}
  TMP_DIR          ${TMP_DIR}
  STAMP_DIR        ${FOO_PREFIX}/stamp
  # Download
  DOWNLOAD_DIR     ${DOWNLOAD_DIR}
  DOWNLOAD_NAME    ${FOO_ARCHIVE_FILE_NAME}
  URL              ${STORAGE_URL}/${FOO_ARCHIVE_FILE_NAME}
  URL_MD5          ${FOO_MD5}
  # Patch
  PATCH_COMMAND    ${PATCH_COMMAND} ${PROJECT_SOURCE_DIR}/patch.diff
  # Configure
  SOURCE_DIR       ${SRC_DIR}
  CMAKE_ARGS       ${CMAKE_OPTS}
  # Build
  BUILD_IN_SOURCE  1
  BUILD_BYPRODUCTS ${CUR_COMPONENT_ARTIFACTS}
  # Logging
  LOG_CONFIGURE    1
  LOG_BUILD        1
  LOG_INSTALL      1
)
```

Note what `clang-format` does for these cases. If two consecutive keywords are more than `n` characters different in length, then break columns, which might come out something like this:

```

ExternalProject_Add(
  FOO
  PREFIX      ${FOO_PREFIX}
  TMP_DIR     ${TMP_DIR}
  STAMP_DIR   ${FOO_PREFIX}/stamp
  # Download
  DOWNLOAD_DIR ${DOWNLOAD_DIR}
  DOWNLOAD_NAME ${FOO_ARCHIVE_FILE_NAME}
  URL          ${STORAGE_URL}/${FOO_ARCHIVE_FILE_NAME}
  URL_MD5      ${FOO_MD5}
  # Patch
  PATCH_COMMAND ${PATCH_COMMAND} ${PROJECT_SOURCE_DIR}/patch.diff
  # Configure
  SOURCE_DIR   ${SRC_DIR}
  CMAKE_ARGS   ${CMAKE_OPTS}
  # Build
  BUILD_IN_SOURCE 1
  BUILD_BYPRODUCTS ${CUR_COMPONENT_ARTIFACTS}
  # Logging
  LOG_CONFIGURE 1
  LOG_BUILD     1
  LOG_INSTALL   1
)

```

As an experimental feature, we could require a tag `# cmf: columnize` to enable this formatting.

4.5.9 Algorithm Ideas and Notes

Layout Passes

Up through version 0.5.2 each node would lay itself out using pass numbers `[0, <parent-passno>]`. This worked pretty well, but actually I would like the nesting to be a little more depth dependant. For example I would like depth 0 (statement) to nest rather early, while I would like higher depths (i.e. KWARGS) to nest later, but go vertical earlier.

One alternative is to have a global `passno` and apply different rules at each pass until things fit, but the problem with this option is that two subtrees might require vastly different passes. We don't want to vertically wrap one all kwargs just because one needs to.

The `cmake-lint` program will check your listfiles for style violations, common mistakes, and anti-patterns.

5.1 Usage

Basic usage for `cmake-lint` is:

```
usage:
cmake-lint [-h]
            [--dump-config {yaml,json,python} | -o OUTFILE_PATH]
            [-c CONFIG_FILE]
            infilepath [infilepath ...]

Check cmake listfile for lint

positional arguments:
  infilepath

optional arguments:
  -h, --help                show this help message and exit
  -v, --version              show program's version number and exit
  -l {error,warning,info,debug}, --log-level {error,warning,info,debug}
  --dump-config [{yaml,json,python}]
                           If specified, print the default configuration to
                           stdout and exit
  -o OUTFILE_PATH, --outfile-path OUTFILE_PATH
                           Write errors to this file. Default is stdout.
  --no-help                  When used with --dump-config, will omit helptext
                           comments in the output
  --no-default               When used with --dump-config, will omit any unmodified
                           configuration value.
  --suppress-decorations     Suppress the file title decoration and summary
```

(continues on next page)

(continued from previous page)

```

        statistics
-c CONFIG_FILES [CONFIG_FILES ...], --config-files CONFIG_FILES [CONFIG_FILES ...]
    path to configuration file(s)

```

Nearly all *Configuration* options are also available as command line options:

```

Options affecting listfile parsing:
--vartags [VARTAGS [VARTAGS ...]]
    Specify variable tags.
--proptags [PROPTAGS [PROPTAGS ...]]
    Specify property tags.

Options affecting formatting.:
--disable [DISABLE]    Disable formatting entirely, making cmake-format a no-
                        op
--line-width LINE_WIDTH
                        How wide to allow formatted cmake files
--tab-size TAB_SIZE    How many spaces to tab for indent
--use-tabchars [USE_TABCHARS]
                        If true, lines are indented using tab characters
                        (utf-8 0x09) instead of <tab_size> space characters
                        (utf-8 0x20). In cases where the layout would require
                        a fractional tab character, the behavior of the
                        fractional indentation is governed by
                        <fractional_tab_policy>
--fractional-tab-policy {use-space,round-up}
                        If <use_tabchars> is True, then the value of this
                        variable indicates how fractional indentions are
                        handled during whitespace replacement. If set to 'use-
                        space', fractional indentation is left as spaces
                        (utf-8 0x20). If set to 'round-up' fractional
                        indentation is replaced with a single tab character
                        (utf-8 0x09) effectively shifting the column to the
                        next tabstop
--max-subgroups-hwrap MAX_SUBGROUPS_HWRAP
                        If an argument group contains more than this many sub-
                        groups (parg or kwarg groups) then force it to a
                        vertical layout.
--max-pargs-hwrap MAX_PARGS_HWRAP
                        If a positional argument group contains more than this
                        many arguments, then force it to a vertical layout.
--max-rows-cmdline MAX_ROWS_CMDLINE
                        If a cmdline positional group consumes more than this
                        many lines without nesting, then invalidate the layout
                        (and nest)
--separate-ctrl-name-with-space [SEPARATE_CTRL_NAME_WITH_SPACE]
                        If true, separate flow control names from their
                        parentheses with a space
--separate-fn-name-with-space [SEPARATE_FN_NAME_WITH_SPACE]
                        If true, separate function names from parentheses with
                        a space
--dangle-parens [DANGLE_PARENS]
                        If a statement is wrapped to more than one line, than
                        dangle the closing parenthesis on its own line.
--dangle-align {prefix,prefix-indent,child,off}
                        If the trailing parenthesis must be 'dangled' on its

```

(continues on next page)

(continued from previous page)

```

on line, then align it to this reference: `prefix`:
the start of the statement, `prefix-indent`: the start
of the statement, plus one indentation level, `child`:
align to the column of the arguments
--min-prefix-chars MIN_PREFIX_CHARS
    If the statement spelling length (including space and
    parenthesis) is smaller than this amount, then force
    reject nested layouts.
--max-prefix-chars MAX_PREFIX_CHARS
    If the statement spelling length (including space and
    parenthesis) is larger than the tab width by more than
    this amount, then force reject un-nested layouts.
--max-lines-hwrap MAX_LINES_HWRAP
    If a candidate layout is wrapped horizontally but it
    exceeds this many lines, then reject the layout.
--line-ending {windows,unix,auto}
    What style line endings to use in the output.
--command-case {lower,upper,canonical,unchanged}
    Format command names consistently as 'lower' or
    'upper' case
--keyword-case {lower,upper,unchanged}
    Format keywords consistently as 'lower' or 'upper'
    case
--always-wrap [ALWAYS_WRAP [ALWAYS_WRAP ...]]
    A list of command names which should always be wrapped
--enable-sort [ENABLE_SORT]
    If true, the argument lists which are known to be
    sortable will be sorted lexicographically
--autosort [AUTOSORT]
    If true, the parsers may infer whether or not an
    argument list is sortable (without annotation).
--require-valid-layout [REQUIRE_VALID_LAYOUT]
    By default, if cmake-format cannot successfully fit
    everything into the desired linewidth it will apply
    the last, most aggressive attempt that it made. If this
    flag is True, however, cmake-format will print error,
    exit with non-zero status code, and write-out nothing

Options affecting comment reflow and formatting.:
--bullet-char BULLET_CHAR
    What character to use for bulleted lists
--enum-char ENUM_CHAR
    What character to use as punctuation after numerals in
    an enumerated list
--first-comment-is-literal [FIRST_COMMENT_IS_LITERAL]
    If comment markup is enabled, don't reflow the first
    comment block in each listfile. Use this to preserve
    formatting of your copyright/license statements.
--literal-comment-pattern LITERAL_COMMENT_PATTERN
    If comment markup is enabled, don't reflow any comment
    block which matches this (regex) pattern. Default is
    `None` (disabled).
--fence-pattern FENCE_PATTERN
    Regular expression to match preformat fences in
    comments default= ``r'^\s*([~]{3}[~]*) (.*)$``
--ruler-pattern RULER_PATTERN
    Regular expression to match rulers in comments

```

(continues on next page)

(continued from previous page)

```

        default= ``r'^\s*{3}.*{3}$'``
--explicit-trailing-pattern EXPLICIT_TRAILING_PATTERN
    If a comment line matches starts with this pattern
    then it is explicitly a trailing comment for the
    preceeding argument. Default is '#<'
--hashruler-min-length HASHRULER_MIN_LENGTH
    If a comment line starts with at least this many
    consecutive hash characters, then don't lstrip() them
    off. This allows for lazy hash rulers where the first
    hash char is not separated by space
--canonicalize-hashrulers [CANONICALIZE_HASHRULERS]
    If true, then insert a space between the first hash
    char and remaining hash chars in a hash ruler, and
    normalize its length to fill the column
--enable-markup [ENABLE_MARKUP]
    enable comment markup parsing and reflow

Options affecting the linter:
--disabled-codes [DISABLED_CODES [DISABLED_CODES ...]]
    a list of lint codes to disable
--function-pattern FUNCTION_PATTERN
    regular expression pattern describing valid function
    names
--macro-pattern MACRO_PATTERN
    regular expression pattern describing valid macro
    names
--global-var-pattern GLOBAL_VAR_PATTERN
    regular expression pattern describing valid names for
    variables with global (cache) scope
--internal-var-pattern INTERNAL_VAR_PATTERN
    regular expression pattern describing valid names for
    variables with global scope (but internal semantic)
--local-var-pattern LOCAL_VAR_PATTERN
    regular expression pattern describing valid names for
    variables with local scope
--private-var-pattern PRIVATE_VAR_PATTERN
    regular expression pattern describing valid names for
    privatedirectory variables
--public-var-pattern PUBLIC_VAR_PATTERN
    regular expression pattern describing valid names for
    public directory variables
--argument-var-pattern ARGUMENT_VAR_PATTERN
    regular expression pattern describing valid names for
    function/macro arguments and loop variables.
--keyword-pattern KEYWORD_PATTERN
    regular expression pattern describing valid names for
    keywords used in functions or macros
--max-conditionals-custom-parser MAX_CONDITIONALS_CUSTOM_PARSER
    In the heuristic for C0201, how many conditionals to
    match within a loop in before considering the loop a
    parser.
--min-statement-spacing MIN_STATEMENT_SPACING
    Require at least this many newlines between statements
--max-statement-spacing MAX_STATEMENT_SPACING
    Require no more than this many newlines between
    statements
--max-returns MAX_RETURNS

```

(continues on next page)

(continued from previous page)

```
--max-branches MAX_BRANCHES
--max-arguments MAX_ARGUMENTS
--max-localvars MAX_LOCALVARS
--max-statements MAX_STATEMENTS
```

Options affecting file encoding:

```
--emit-byteorder-mark [EMIT_BYTEORDER_MARK]
    If true, emit the unicode byte-order mark (BOM) at the
    start of the file
--input-encoding INPUT_ENCODING
    Specify the encoding of the input file. Defaults to
    utf-8
--output-encoding OUTPUT_ENCODING
    Specify the encoding of the output file. Defaults to
    utf-8. Note that cmake only claims to support utf-8 so
    be careful when using anything else
```

5.2 Inline Directives

cmake-lint supports inline directives to help control local behavior. The format of these directives is a cmake line comment with the following format:

```
# cmake-lint: <body>
```

5.2.1 Pragmas

disable

You may specify a list of error codes to locally disable. You may specify a comma separate list of codes to disable:

```
# cmake-lint: disable=<code1>,<code2>,<code3>,...
```

Example:

```
# cmake-lint: disable=C0103
foreach(LOOPVAR2 a b c d)
    # pass
endforeach()
```

Warning: Currently this pragma must be specified at body scope (e.g. it cannot be a comment within a statement) and it applies for the duration of the scope. This behavior will likely change in the future.

5.3 Example

Given the following linty file:

```
# The line is too long and exceeds the default 80 character column limit enforced_
↪cmake-lint

# This line has trailing whitespace

# This line has the wrong line endings

function(BAD_FUNCTION_NAME badArgName good_arg_name)
    # Function names should be lower case
endfunction()

#
macro(bad_macro_name badArgName good_arg_name)
    # Macro names should be upper case
endmacro()

if(FOOBAR)
    foreach(loopvar a b c d)
        # cmake-lint: disable=C0103
        foreach(LOOPVAR2 a b c d)
            # pass
        endforeach()
    endforeach()
    foreach(LOOPVAR3 a b c d)
        # pass
    endforeach()
endif()

if(TRUE)
    message("Hello world")
endif()

if(TRUE)
    message("Hello world")
endif()

if(TRUE)
    message("Hello world")
endif()

# expect:
set(gtest_force_shared_crt ON # cmake-lint: disable=C0103
    CACHE BOOL "See googletest/googletest/CMakeLists.txt")

set(VARNAME varvalue CACHE STRING)

cmake_minimum_required_version(VERSION 2.8.11 VERSION 3.16)

# expect:
install(
    DIRECTORY foo bar/
    DESTINATION some/path
    PATTERN "CVS" EXCLUDE
    PATTERN "scripts/*" PERMISSIONS OWNER_EXECUTE OWNER_WRITE OWNER_READ
                                GROUP_EXECUTE GROUP_READ)
```

(continues on next page)

(continued from previous page)

```

add_custom_command()

set(_form TARGET PRE_BUILD)
add_custom_command(
    ${form}
    COMMAND echo "hello"
    COMMENT "echo hello")

add_custom_command(
    TARGET PRE_BUILD
    COMMAND echo "hello"
    COMMENT "echo hello")

add_custom_command(OUTPUT foo)

file()

set(_form TOUCH)
file(${form} foo.py)

file(TOUCHE foo.py)

break()

continue()

# foo: docstring
function(foo)
    foreach(arg ${ARGN})
        if(arg STREQUAL "FOO")
            # parse FOO
        elseif(arg STREQUAL "BAR")
            # parse BAR
        elseif(arg MATCHES "BAZ.*")
            # parse BAZ
        endif()
    endforeach()
endfunction()

set(_foo "hello") set(_bar "goodbye")

set(_foo "hello")

set(_bar "goodbye")

# foo: docstring
function(foo "arg-name")
    # pass
endfunction()

# foo: docstring
function(foo arg arg)
    # pass
endfunction()

```

(continues on next page)

(continued from previous page)

```

# foo: docstring
function(foo arg ARG)
    # pass
endfunction()

return()
message("This code is unreachable")

# cmake-lint: disable=E0109,C0321
# foo:docstring, too many arguments
function(foo a0 a1 a2 a3 a4 a5)

    # Too many branches, too many returns
    if(blah) return()
    elseif(blah) return()
    elseif(blah) return()
    elseif(blah) return()
    elseif(blah) return()
    elseif(blah) return()
    elseif(blah) return()
    elseif(blah) return()
    elseif(blah) return()
    elseif(blah) return()
    elseif(blah) return()
    elseif(blah) return()
    elseif(blah) return()
    elseif(blah) return()
    elseif(blah) return()
    else() return()
endif()

# too many statements
message(foo) message(foo) message(foo) message(foo) message(foo) message(foo)
message(foo) message(foo) message(foo) message(foo) message(foo) message(foo)
message(foo) message(foo) message(foo) message(foo) message(foo) message(foo)
message(foo) message(foo) message(foo) message(foo) message(foo) message(foo)
message(foo) message(foo) message(foo) message(foo) message(foo) message(foo)
endfunction()

# cmake-lint: disable=C0111
# cache (global) variables should be upper snake
set(MyGlobalVar CACHE STRING "my var")
# internal variables are treated as private and should be upper snake with an
# underscore prefix
set(MY_INTERNAL_VAR CACHE INTERNAL "my var")
# directory-scope variables should be upper-snake (public) or lower-snake with
# underscore prefix
set(_INVALID_PRIVATE_NAME "foo")
set(invalid_public_name "foo")
function(foo)
    set(INVALID_LOCAL_NAME "foo")
endfunction()

set(CMAKE_Cxx_STANDARD "11")

```

(continues on next page)

(continued from previous page)

```
list(APPEND CMAKE_Cxx_STANDARD "11")

message("Using C++ standard ${CMAKE_Cxx_STANDARD}")

message("${CMAKE_INSTALL_PREFIX}")
message("${CMAKE_INSTALL_PREFIX}")
message("${CMAKE_INSTALL_PREFIX}")

# This file is missing a final newline
```

The output is:

```
cmakelang/lint/test/expect_lint.cmake
=====
cmakelang/lint/test/expect_lint.cmake:01: [C0301] Line too long (92/80)
cmakelang/lint/test/expect_lint.cmake:03: [C0303] Trailing whitespace
cmakelang/lint/test/expect_lint.cmake:05: [C0327] Wrong line ending (windows)
cmakelang/lint/test/expect_lint.cmake:08,00: [C0111] Missing docstring on function or_
↳macro declaration
cmakelang/lint/test/expect_lint.cmake:08,00: [C0305] too many newlines between
↳statements
cmakelang/lint/test/expect_lint.cmake:08,09: [C0103] Invalid function name "BAD_
↳FUNCTION_NAME" doesn't match `[0-9a-z_]+`
cmakelang/lint/test/expect_lint.cmake:13,00: [C0112] Empty docstring on function or_
↳macro declaration
cmakelang/lint/test/expect_lint.cmake:13,06: [C0103] Invalid macro name "bad_macro_
↳name" doesn't match `[0-9A-Z_]+`
cmakelang/lint/test/expect_lint.cmake:20,12: [C0103] Invalid argument name "LOOPVAR2"
↳doesn't match `[a-z][a-z0-9_]+`
cmakelang/lint/test/expect_lint.cmake:24,10: [C0103] Invalid argument name "LOOPVAR3"
↳doesn't match `[a-z][a-z0-9_]+`
cmakelang/lint/test/expect_lint.cmake:30,00: [C0306] Tab-policy violation. Found tab
↳but should be space
cmakelang/lint/test/expect_lint.cmake:34,01: [C0307] Bad indentation:
message
^----BodyNode: 1:0->IfBlockNode: 33:0->BodyNode: 33:8->StatementNode: 34:1->
↳FunctionNameNode: 34:1
cmakelang/lint/test/expect_lint.cmake:38,03: [C0307] Bad indentation:
message
^----BodyNode: 1:0->IfBlockNode: 37:0->BodyNode: 37:8->StatementNode: 38:3->
↳FunctionNameNode: 38:3
cmakelang/lint/test/expect_lint.cmake:43,04: [C0103] Invalid CACHE variable name
↳"gtest_force_shared_crt" doesn't match `[A-Z][0-9A-Z_]+`
cmakelang/lint/test/expect_lint.cmake:46,27: [E1120] Missing required positional
↳argument
cmakelang/lint/test/expect_lint.cmake:46,33: [E1120] Missing required positional
↳argument
cmakelang/lint/test/expect_lint.cmake:48,46: [E1122] Duplicate keyword argument
↳VERSION
cmakelang/lint/test/expect_lint.cmake:59,00: [C0305] too many newlines between
↳statements
cmakelang/lint/test/expect_lint.cmake:59,19: [E1120] Missing required positional
↳argument
cmakelang/lint/test/expect_lint.cmake:63,02: [C0114] Form discriminator hidden behind
↳variable dereference
```

(continues on next page)

(continued from previous page)

```

cmakelang/lint/test/expect_lint.cmake:68,02: [E1126] Invalid form discriminator
cmakelang/lint/test/expect_lint.cmake:72,19: [E1125] Missing required keyword_
↳argument COMMAND
cmakelang/lint/test/expect_lint.cmake:74,05: [E1120] Missing required positional_
↳argument
cmakelang/lint/test/expect_lint.cmake:77,05: [C0114] Form discriminator hidden behind_
↳variable dereference
cmakelang/lint/test/expect_lint.cmake:79,05: [E1126] Invalid form discriminator
cmakelang/lint/test/expect_lint.cmake:81,00: [E0103] break outside of loop
cmakelang/lint/test/expect_lint.cmake:81,00: [W0101] Unreachable code
cmakelang/lint/test/expect_lint.cmake:83,00: [E0103] continue outside of loop
cmakelang/lint/test/expect_lint.cmake:83,00: [W0101] Unreachable code
cmakelang/lint/test/expect_lint.cmake:87,02: [C0201] Consider replacing custom parser_
↳logic with cmake_parse_arguments
cmakelang/lint/test/expect_lint.cmake:98,18: [C0321] Multiple statements on a single_
↳line
cmakelang/lint/test/expect_lint.cmake:103,00: [C0305] too many newlines between_
↳statements
cmakelang/lint/test/expect_lint.cmake:106,13: [E0109] Invalid argument name "arg-name"
↳" in function/macro definition
cmakelang/lint/test/expect_lint.cmake:111,17: [E0108] Duplicate argument name arg in_
↳function/macro definition
cmakelang/lint/test/expect_lint.cmake:116,17: [C0202] Argument name ARG differs from_
↳existing argument only in case
cmakelang/lint/test/expect_lint.cmake:120,00: [W0101] Unreachable code
cmakelang/lint/test/expect_lint.cmake:125,00: [R0913] Too many named arguments 6/5
cmakelang/lint/test/expect_lint.cmake:126: [R0911] Too many return statements 17/6
cmakelang/lint/test/expect_lint.cmake:126: [R0912] Too many branches 17/12
cmakelang/lint/test/expect_lint.cmake:126: [R0915] Too many statements 65/50
cmakelang/lint/test/expect_lint.cmake:157,04: [C0103] Invalid CACHE variable name
↳"MyGlobalVar" doesn't match `[A-Z][0-9A-Z_]+`
cmakelang/lint/test/expect_lint.cmake:160,04: [C0103] Invalid INTERNAL variable name
↳"MY_INTERNAL_VAR" doesn't match `[A-Z][0-9A-Z_]+`
cmakelang/lint/test/expect_lint.cmake:163,04: [C0103] Invalid directory variable name
↳"_INVALID_PRIVATE_NAME" doesn't match `[A-Z][0-9A-Z_]+|[0-9a-z_]+`
cmakelang/lint/test/expect_lint.cmake:164,04: [C0103] Invalid directory variable name
↳"invalid_public_name" doesn't match `[A-Z][0-9A-Z_]+|[0-9a-z_]+`
cmakelang/lint/test/expect_lint.cmake:166,06: [C0103] Invalid local variable name
↳"INVALID_LOCAL_NAME" doesn't match `[a-z][a-z0-9_]+`
cmakelang/lint/test/expect_lint.cmake:169,04: [W0105] Assignment to variable 'CMAKE_
↳Cxx_STANDARD' which matches a built-in except for case
cmakelang/lint/test/expect_lint.cmake:171,12: [W0105] Assignment to variable 'CMAKE_
↳Cxx_STANDARD' which matches a built-in except for case
cmakelang/lint/test/expect_lint.cmake:173,08: [W0105] Reference to variable 'CMAKE_
↳Cxx_STANDARD' which matches a built-in except for case
cmakelang/lint/test/expect_lint.cmake:175,08: [W0106] String looks like a variable_
↳reference missing an open tag '$CMAKE_INSTALL_PREFIX'
cmakelang/lint/test/expect_lint.cmake:176,08: [W0106] String looks like a variable_
↳reference missing an open tag '{CMAKE_INSTALL_PREFIX'
cmakelang/lint/test/expect_lint.cmake:177,08: [W0106] String looks like a variable_
↳reference missing an open tag '{CMAKE_INSTALL_PREFIX'
cmakelang/lint/test/expect_lint.cmake:179: [C0304] Final newline missing

```

Summary

=====

files scanned: 1

found lint:

(continues on next page)

(continued from previous page)

```

Convention: 27
  Error: 12
  Refactor: 4
  Warning: 9

```

5.4 Linter Checks List

Below is a running list of planned and implemented lint checks.

5.4.1 Implemented

Here is a list of implemented lint checks. More detailed information about each check is available in [Lint Code Reference](#).

<i>C0102</i>	Black listed name "{:s}"
<i>C0103</i>	Invalid {:s} name "{:s}" doesn't match {:s}
<i>C0111</i>	Missing docstring on function or macro declaration
<i>C0112</i>	Empty docstring on function or macro declaration
<i>C0113</i>	Missing {:s} in statement which allows it
<i>C0114</i>	Form discriminator hidden behind variable dereference
<i>C0201</i>	Consider replacing custom parser logic with <code>cmake_parse_arguments</code>
<i>C0202</i>	Argument name {:s} differs from existing argument only in case
<i>C0301</i>	Line too long (:{:d}/{:d})
<i>C0303</i>	Trailing whitespace
<i>C0304</i>	Final newline missing
<i>C0305</i>	{:s} newlines between statements
<i>C0306</i>	Tab-policy violation. Found {:s} but should be {:s}
<i>C0307</i>	Bad indentation: {:s}{:s} {:s}^—{ }
<i>C0321</i>	Multiple statements on a single line
<i>C0327</i>	Wrong line ending (:{:s})
<i>E0011</i>	Unrecognized file option {:s}
<i>E0012</i>	Bad option value {:s}
<i>E0103</i>	{:s} outside of loop
<i>E0108</i>	Duplicate argument name {:s} in function/macro definition
<i>E0109</i>	Invalid argument name {:s} in function/macro definition
<i>E1120</i>	Missing required positional argument
<i>E1121</i>	Too many positional arguments
<i>E1122</i>	Duplicate keyword argument {:s}
<i>E1125</i>	Missing required keyword argument {:s}
<i>E1126</i>	Invalid form discriminator
<i>R0911</i>	Too many return statements {:d}/{:d}
<i>R0912</i>	Too many branches {:d}/{:d}
<i>R0913</i>	Too many named arguments {:d}/{:d}
<i>R0914</i>	Too many local variables {:d}/{:d}
<i>R0915</i>	Too many statements {:d}/{:d}
<i>W0101</i>	Unreachable code
<i>W0104</i>	Use of deprecated command {:s}

Continued on next page

Table 5.1 – continued from previous page

W0105	{:s} variable '{:s}' which matches a built-in except for case
W0106	String looks like a variable reference missing an {:s} tag '{:s}'

5.4.2 Planned

Here are some planned lint checks based on the kinds of things that `pylint` looks for. If there's a particular check you'd like to see added, please open an issue on [github](#).

C0203	uncanonical spelling of {:s}
C0204	uncanonical keyword order
C0205	use of bad-idea command {:s}
C0302	Too many lines in listfile
C0303	Wrong hanging indentation
C0304	raw assignment to property
E0001	(syntax error raised for a listfile; message varies)
E0011	Unrecognized file option %r
E0102	%s already defined line %s
E1123	Passing unexpected keyword argument %r in function call
F0001	(error prevented analysis; message varies)
F0002	%s: %s (message varies)
F0010	error while code parsing: %s
I0010	Unable to consider inline option %r
I0011	Locally disabling %s
I0012	Locally enabling %s
I0013	Ignoring entire file
I0020	Suppressed %s (from line %d)
I0021	Useless suppression of %s
R0201	Macro could be a function
R0401	Cyclic import (%s)
R0801	Similar lines in %s files
W0102	Using local variable %r before assignment
W0103	Undefined local variable %r
W0104	Use of deprecated command
W0105	Use of deprecated kwarg
W0106	Use of deprecated command form {:s}
W0212	Access to a private variable %s of a find module
W0402	Uses of a deprecated find module %r
W0622	Redefining built-in %r
W1401	Anomalous backslash in string: '%s'.

5.5 Lint Code Reference

5.5.1 C0102

message

```
Black listed name "{:s}"
```

description

Used when the name is listed in the “bad-names” black list.

This message belongs to the basic checker.

explanation

cmake-lint can be customized to help enforce coding guidelines that discourage or forbid use of certain names for variables, functions, etc.. These names are specified with the bad-names option. This message is raised whenever a name is in the list of names defined with the bad-names option.

5.5.2 C0103**message**

```
Invalid {s} name "{s}" doesn't match `{s}`
```

description

Used when a name doesn’t doesn’t fit the naming convention associated to its type (function, macro, variable, ...).

This message belongs to the basic checker.

explanation

The naming convention is defined with a regular expression, and the naming convention is satisfied if the name matches the regular expression.

5.5.3 C0111**message**

```
Missing docstring on function or macro declaration
```

description

Used when a function or macro is defined without a documentation comment immediately preceeding it.

This message belongs to the basic checker.

explanation

So, you’ve written a some fancy function that makes it “easier” to declare build steps. Congratulations. You probably shouldn’t have, but thats OK. Now that you did, how should people use it? What arguments does it take? What are the semantics of those arguments? You should include documentation in a comment block prior to the function declaration with this information.

5.5.4 C0112

message

```
Empty docstring on function or macro declaration
```

description

Used when a function or macro is preceeded by an empty comment string, rather than one with useful documentation. This message belongs to the basic checker.

explanation

Ok so you saw C0111 and figured you'd be clever right? Sorry, no dice. Please include some useful documentation so that code readers know what your function/macro does and how to use it.

5.5.5 C0113

message

```
Missing {:s} in statement which allows it
```

5.5.6 C0114

message

```
Form discriminator hidden behind variable dereference
```

description

Used when a keyword used to discriminate between different forms of a command is hidden behind a variable dereference.

This message is implemented by individual command checkers.

explanation

Some cmake commands have very different behavior depending on the presence of a particular keyword (see e.g. the *file* command). And because cmake is a macro language that keyword can actually be held inside a variable. Thus the keyword might not actually be visible to cmake-lint (or humans). In general there is no reason to do this and it really hurts readability since different discriminator keywords yield essentially different commands.

5.5.7 C0201

message

```
Consider replacing custom parser logic with cmake_parse_arguments
```

description

Used when custom parse logic is detected.

5.5.8 C0202

message

```
Argument name {:s} differs from existing argument only in case
```

5.5.9 C0301

message

```
Line too long ({:d}/{:d})
```

description

Used when a line is longer than the limit specified in the line-length option.

explanation

It is a good idea to keep each line within a maximum length to keep it from wrapping past the edge of an editing window. This improves readability and tempers other developers' irritability!

The default value of the line-length option is 80, the customary width of a terminal window.

Note that the line length and the limit are counted in characters, not in Bytes needed to represent these characters.

5.5.10 C0303

message

```
Trailing whitespace
```

description

Used when a line has one or more whitespace characters directly before the line end character(s).

This message belongs to the basic checker.

explanation

Such trailing whitespace is visually indistinguishable and some editors will trim them.

5.5.11 C0304

message

```
Final newline missing
```

description

Used when a listfile has no line end character(s) on its last line.

This message belongs to the basic checker.

explanation

While cmake itself does not require line end character(s) on the last line, is simply good practice to have it.

5.5.12 C0305

message

```
{:s} newlines between statements
```

5.5.13 C0306

message

```
Tab-policy violation. Found {:s} but should be {:s}
```

5.5.14 C0307

message

```
Bad indentation:
{:s}{:s}
{:s}^----{ }
```

5.5.15 C0321

message

```
Multiple statements on a single line
```

5.5.16 C0327

message

```
Wrong line ending ({:s})
```

description

Used when a line ends with the wrong line ending character. e.g. A line ends with “rn” when configured for “n”.

This message belongs to the basic checker.

explanation

While cmake itself does not enforce a particular line ending, it is good practice for a project to be consist with their line endings.

5.5.17 E0011

message

```
Unrecognized file option {:s}
```

description

Used when an unrecognized pragma is encountered.

explanation

cmake-lint allows for some inline comments to supress warnings (among other things). This lint is emitted if a bad option key is provided in such a pragma

5.5.18 E0012

message

```
Bad option value {:s}
```

description

Used when a cmake-lint pragma is encountered which attempts to alter some option in an invalid way.

This message belongs to the basic checker.

explanation

cmake-lint allows for some inline comments to suppress warnings (among other things). This lint is emitted if a bad option is provided to one of these pragmas.

5.5.19 E0103

message

```
{:s} outside of loop
```

description

Used when a `break()` or `continue()` statement is used outside a loop.

This message belongs to the basic checker.

5.5.20 E0108

message

```
Duplicate argument name {:s} in function/macro definition
```

5.5.21 E0109

message

```
Invalid argument name {:s} in function/macro definition
```

5.5.22 E1120

message

```
Missing required positional argument
```

description

Used when a positional argument group expecting an exact number of arguments is closed (by a parenthesis) before that number of arguments is found.

This message belongs to the basic checker.

5.5.23 E1121

message

```
Too many positional arguments
```

description

Used when a positional argument is found when no argument group is expected.

This message is implemented by individual command checkers

5.5.24 E1122

message

```
Duplicate keyword argument {:s}
```

description

Used when a keyword shows up more than once within an argument group. In general, only COMMAND is allowed more than once.

5.5.25 E1125

message

```
Missing required keyword argument {:s}
```

5.5.26 E1126

message

```
Invalid form discriminator
```

description

Used when a keyword used to discriminate between different command forms is omitted.

5.5.27 R0911

message

```
Too many return statements {:d}/{:d}
```

5.5.28 R0912

message

```
Too many branches {:d}/{:d}
```

5.5.29 R0913

message

```
Too many named arguments {:d}/{:d}
```

5.5.30 R0914

message

```
Too many local variables {:d}/{:d}
```

5.5.31 R0915

message

```
Too many statements {:d}/{:d}
```

5.5.32 W0101

message

```
Unreachable code
```

5.5.33 W0104

message

```
Use of deprecated command {:s}
```

5.5.34 W0105

message

```
{:s} variable '{:s}' which matches a built-in except for case
```

description

This warning means that you are using a variable such as, for example, `cmake_cxx_standard` which matches a builtin variable (`CMAKE_CXX_STANDARD`) except for the case. If this was intentional, then it's bad practice as it causes confusion (there are two variables in the namespace with identical name except for case), though it was probably not intentional and you probably aren't assigning to the correct variable.

This warning may be emitted for assignment (e.g. `set()` or `list()`) as well as for variable expansion in an argument (e.g. `"${CMAKE_Cxx_STANDARD}"`).

5.5.35 W0106

message

String looks like a variable reference missing an `{:s}` tag `'{:s}'`

5.6 Linter notes

5.6.1 Variable naming conventions

The default patterns used for variable naming convention is chosen to match the dominant convention of the listfiles distributed with cmake itself. The tool `analyze_naming.py` was used to classify each variable assignment in all modules from cmake 3.10 yielding the following counts:

```
PARENT
=====
other: 237
'[A-Z][A-Z0-9_]+' 335
'[a-z][a-z0-9_]+' 146
'_[A-Z0-9_]+' 62
'_[a-z0-9_]+' 236

LOCAL
=====
other: 375
'[A-Z][A-Z0-9_]+' 646
'[a-z][a-z0-9_]+' 1220
'_[A-Z0-9_]+' 375
'_[a-z0-9_]+' 450

DIRECTORY
=====
other: 235
'[A-Z][A-Z0-9_]+' 2140
'[a-z][a-z0-9_]+' 111
'_[A-Z0-9_]+' 515
'_[a-z0-9_]+' 182

LOOP
=====
other: 72
'[A-Z][A-Z0-9_]+' 98
```

(continues on next page)

(continued from previous page)

```
'[a-z][a-z0-9_]+' 288
'_[A-Z0-9_]+' 79
'_[a-z0-9_]+' 114
```

ARGUMENT

=====

```
other: 17
'[A-Z][A-Z0-9_]+' 159
'[a-z][a-z0-9_]+' 512
'_[A-Z0-9_]+' 60
'_[a-z0-9_]+' 184
```

The `ctest-to` program can parse listfiles from a ctest output tree and generate a more structured representation of the test spec.

6.1 Usage

```
usage: ctest-to [-h] [--log-level {debug,info,warning,error}] [--json | --xml]
               [directory]

Parse ctest testfiles and re-emit the test specification in a more structured
format.

positional arguments:
  directory

optional arguments:
  -h, --help            show this help message and exit
  --log-level {debug,info,warning,error}
  --json
  --xml
```

6.2 Example

Here are some examples generated by the ctest file for this repository:

```
[
  {
    "name": "cmakelang-TestAddCustomCommand",
    "argv": [
      "python",
```

(continues on next page)

(continued from previous page)

```

        "-Bm",
        "cmakelang.command_tests",
        "TestAddCustomCommand"
    ],
    "cwd": "/code/cmakelang/.build/nd.x86/cmakelang/command_tests",
    "props": {
        "working_directory": "/code/cmakelang"
    }
},
{
    "name": "cmakelang-TestAddCustomCommand_py3",
    "argv": [
        "python3",
        "-Bm",
        "cmakelang.command_tests",
        "TestAddCustomCommand"
    ],
    "cwd": "/code/cmakelang/.build/nd.x86/cmakelang/command_tests",
    "props": {
        "working_directory": "/code/cmakelang"
    }
},
...
]

```

```

<ctest>
  <test cwd="/code/cmakelang/.build/nd.x86/cmakelang/command_tests" name="cmakelang-
  ↪TestAddCustomCommand" working_directory="/code/cmakelang">
    <argv>
      <arg value="python"/>
      <arg value="-Bm"/>
      <arg value="cmakelang.command_tests"/>
      <arg value="TestAddCustomCommand"/>
    </argv>
  </test>
  <test cwd="/code/cmakelang/.build/nd.x86/cmakelang/command_tests" name="cmakelang-
  ↪TestAddCustomCommand_py3" working_directory="/code/cmakelang">
    <argv>
      <arg value="python3"/>
      <arg value="-Bm"/>
      <arg value="cmakelang.command_tests"/>
      <arg value="TestAddCustomCommand"/>
    </argv>
  </test>
  ...
</ctest>

```

Various configuration options and parameters

7.1 Options affecting listfile parsing

7.1.1 additional_commands

Specify structure for custom cmake functions

default value:

```
{ 'foo': { 'flags': ['BAR', 'BAZ'],  
          'kwargs': {'DEPENDS': '*', 'HEADERS': '*', 'SOURCES': '*'}}}
```

detailed description:

Use this variable to specify how to parse custom cmake functions. See *Implementing Custom Parsers*.

config-file entry:

```
# -----  
# Options affecting listfile parsing  
# -----  
with section("parse"):  
  
    # Specify structure for custom cmake functions  
    additional_commands = { 'foo': { 'flags': ['BAR', 'BAZ'],  
                                     'kwargs': {'DEPENDS': '*', 'HEADERS': '*', 'SOURCES': '*'}}}
```

7.1.2 override_spec

Override configurations per-command where available

default value:

```
{ }
```

config-file entry:

```
# -----  
# Options affecting listfile parsing  
# -----  
with section("parse") :  
  
    # Override configurations per-command where available  
    override_spec = { }
```

7.1.3 vartags

Specify variable tags.

default value:

```
[ ]
```

detailed description:

Specify a mapping of variable patterns (python regular expression) to a list of tags. Any time a variable matching this pattern is encountered the tags can be used to affect the parsing/formatting. For example:

```
vartags = [  
    (".*_COMMAND", [ "cmdline" ])  
]
```

Specifies that any variable ending in `_COMMAND` be tagged as `cmdline`. This will affect the formatting by preventing the arguments from being vertically wrapped.

Note: this particular rule is builtin so you do not need to include this in your configuration. Use the configuration variable to add new rules.

command-line option:

```
--vartags [VARTAGS [VARTAGS ...]]  
        Specify variable tags.
```

config-file entry:

```
# -----
# Options affecting listfile parsing
# -----
with section("parse"):

    # Specify variable tags.
    vartags = []
```

7.1.4 proptags

Specify property tags.

default value:

```
[]
```

detailed description:

Specify a mapping of property patterns (python regular expression) to a list of tags. Any time a a property matching this pattern is encountered the tags can be used to affect the parsing/formatting. For example:

```
proptags = [
    (".*_DIRECTORIES", ["file-list"])
]
```

Specifies that any property ending in `_DIRECTORIES` be tagged as `file-list`. In the future this may affect formatting by allowing arguments to be sorted (but currently has no effect).

Note: this particular rule is builtin so you do not need to include this in your configuration. Use the configuration variable to add new rules.

command-line option:

```
--proptags [PROPTAGS [PROPTAGS ...]]
           Specify property tags.
```

config-file entry:

```
# -----
# Options affecting listfile parsing
# -----
with section("parse"):

    # Specify property tags.
    proptags = []
```

7.2 Options affecting formatting.

7.2.1 disable

Disable formatting entirely, making cmake-format a no-op

default value:

```
False
```

command-line option:

```
--disable [DISABLE]  Disable formatting entirely, making cmake-format a no-  
                        op
```

config-file entry:

```
# -----  
# Options affecting formatting.  
# -----  
with section("format"):  
  
    # Disable formatting entirely, making cmake-format a no-op  
    disable = False
```

7.2.2 line_width

How wide to allow formatted cmake files

default value:

```
80
```

detailed description:

line_width specifies the number of columns that cmake-format should fit commands into. This is the number of columns at which arguments will be wrapped.

```
# line_width = 80 (default)  
add_library(libname STATIC sourcefile_one.cc sourcefile_two.cc  
                           sourcefile_three.cc sourcefile_four.cc)  
  
# line_width = 100  
add_library(libname STATIC sourcefile_one.cc sourcefile_two.cc sourcefile_three.cc  
                           sourcefile_four.cc)
```

command-line option:

```
--line-width LINE_WIDTH
           How wide to allow formatted cmake files
```

config-file entry:

```
# -----
# Options affecting formatting.
# -----
with section("format"):

    # How wide to allow formatted cmake files
    line_width = 80
```

7.2.3 tab_size

How many spaces to tab for indent

default value:

```
2
```

detailed description:

tab_size indicates how many spaces should be used to indent nested “scopes”. For example:

```
# tab_size = 2 (default)
if(this_condition_is_true)
    message("Hello World")
endif()

# tab_size = 4
if(this_condition_is_true)
    message("Hello World")
endif()
```

command-line option:

```
--tab-size TAB_SIZE  How many spaces to tab for indent
```

config-file entry:

```
# -----
# Options affecting formatting.
# -----
with section("format"):
```

(continues on next page)

(continued from previous page)

```
# How many spaces to tab for indent
tab_size = 2
```

7.2.4 use_tabchars

If true, lines are indented using tab characters (utf-8 0x09) instead of <tab_size> space characters (utf-8 0x20). In cases where the layout would require a fractional tab character, the behavior of the fractional indentation is governed by <fractional_tab_policy>

default value:

```
False
```

command-line option:

```
--use-tabchars [USE_TABCHARS]
    If true, lines are indented using tab characters
    (utf-8 0x09) instead of <tab_size> space characters
    (utf-8 0x20). In cases where the layout would require
    a fractional tab character, the behavior of the
    fractional indentation is governed by
    <fractional_tab_policy>
```

config-file entry:

```
# -----
# Options affecting formatting.
# -----
with section("format"):

    # If true, lines are indented using tab characters (utf-8 0x09) instead of
    # <tab_size> space characters (utf-8 0x20). In cases where the layout would
    # require a fractional tab character, the behavior of the fractional
    # indentation is governed by <fractional_tab_policy>
    use_tabchars = False
```

7.2.5 fractional_tab_policy

If <use_tabchars> is True, then the value of this variable indicates how fractional indentions are handled during whitespace replacement. If set to 'use-space', fractional indentation is left as spaces (utf-8 0x20). If set to *round-up* fractional indentation is replaced with a single tab character (utf-8 0x09) effectively shifting the column to the next tabstop

default value:

```
'use-space'
```

command-line option:

```
--fractional-tab-policy {use-space,round-up}
    If <use_tabchars> is True, then the value of this
    variable indicates how fractional indentions are
    handled during whitespace replacement. If set to 'use-
    space', fractional indentation is left as spaces
    (utf-8 0x20). If set to `round-up` fractional
    indentation is replaced with a single tab character
    (utf-8 0x09) effectively shifting the column to the
    next tabstop
```

config-file entry:

```
# -----
# Options affecting formatting.
# -----
with section("format"):

    # If <use_tabchars> is True, then the value of this variable indicates how
    # fractional indentions are handled during whitespace replacement. If set to
    # 'use-space', fractional indentation is left as spaces (utf-8 0x20). If set
    # to `round-up` fractional indentation is replaced with a single tab character
    # (utf-8 0x09) effectively shifting the column to the next tabstop
    fractional_tab_policy = 'use-space'
```

7.2.6 max_subgroups_hwrap

If an argument group contains more than this many sub-groups (parg or kwarg groups) then force it to a vertical layout.

default value:

```
2
```

detailed description:

A “subgroup” in this context is either a positional or keyword argument group within the current depth of the statement parse tree. If the number of “subgroups” at this depth is greater than `max_subgroups_hwrap` then hwrap-formatting is inadmissible and a vertical layout will be selected.

The default value for this parameter is 2.

Consider the following two examples:

```
# This statement has two argument groups, so hwrap is admissible
add_custom_target(target1 ALL COMMAND echo "hello world")

# This statement has three argument groups, so the statement will format
# vertically
add_custom_target(
    target2 ALL
    COMMAND echo "hello world"
    COMMAND echo "hello again")
```

In the first statement, there are two argument groups. We can see them with `--dump parse`

```
└─ BODY: 1:0
  └─ STATEMENT: 1:0
    └─ FUNNAME: 1:0
    └─ LPAREN: 1:17
    └─ ARGGROUP: 1:18
      └─ PARGGROUP: 1:18 <-- group 1
        └─ ARGUMENT: 1:18
          └─ FLAG: 1:26
      └─ KWARGGROUP: 1:30 <-- group 2
        └─ KEYWORD: 1:30
        └─ ARGGROUP: 1:38
          └─ PARGGROUP: 1:38
            └─ ARGUMENT: 1:38
            └─ ARGUMENT: 1:43
    └─ RPAREN: 1:56
```

The second statement has three argument groups:

```
└─ BODY: 1:0
  └─ STATEMENT: 1:0
    └─ FUNNAME: 1:0
    └─ LPAREN: 1:17
    └─ ARGGROUP: 2:5
      └─ PARGGROUP: 2:5 <-- group 1
        └─ ARGUMENT: 2:5
          └─ FLAG: 2:13
      └─ KWARGGROUP: 3:5 <-- group 2
        └─ KEYWORD: 3:5
        └─ ARGGROUP: 3:13
          └─ PARGGROUP: 3:13
            └─ ARGUMENT: 3:13
            └─ ARGUMENT: 3:18
      └─ KWARGGROUP: 4:5 <-- group 3
        └─ KEYWORD: 4:5
        └─ ARGGROUP: 4:13
          └─ PARGGROUP: 4:13
            └─ ARGUMENT: 4:13
            └─ ARGUMENT: 4:18
    └─ RPAREN: 4:31
```

command-line option:

```
--max-subgroups-hwrap MAX_SUBGROUPS_HWRAP
    If an argument group contains more than this many sub-
    (continues on next page)
```

(continued from previous page)

```
groups (parg or kwarg groups) then force it to a
vertical layout.
```

config-file entry:

```
# -----
# Options affecting formatting.
# -----
with section("format") :

    # If an argument group contains more than this many sub-groups (parg or kwarg
    # groups) then force it to a vertical layout.
    max_subgroups_hwrap = 2
```

7.2.7 max_pargs_hwrap

If a positional argument group contains more than this many arguments, then force it to a vertical layout.

default value:

```
6
```

detailed description:

This configuration parameter is relevant only to positional argument groups. A positional argument group is a list of “plain” arguments. If the number of arguments in the group is greater than this number, then then hwrap-formatting is inadmissible and a vertical layout will be selected.

The default value for this parameter is 6

Consider the following two examples:

```
# This statement has six arguments in the second group and so hwrap is
# admissible
set(sources filename_one.cc filename_two.cc filename_three.cc
      filename_four.cc filename_five.cc filename_six.cc)

# This statement has seven arguments in the second group and so hwrap is
# inadmissible
set(sources
    filename_one.cc
    filename_two.cc
    filename_three.cc
    filename_four.cc
    filename_five.cc
    filename_six.cc
    filename_seven.cc)
```

command-line option:

```
--max-pargs-hwrap MAX_PARGS_HWRAP
    If a positional argument group contains more than this
    many arguments, then force it to a vertical layout.
```

config-file entry:

```
# -----
# Options affecting formatting.
# -----
with section("format") :

    # If a positional argument group contains more than this many arguments, then
    # force it to a vertical layout.
    max_pargs_hwrap = 6
```

7.2.8 max_rows_cmdline

If a cmdline positional group consumes more than this many lines without nesting, then invalidate the layout (and nest)

default value:

```
2
```

detailed description:

max_pargs_hwrap does not apply to positional argument groups for shell commands. These are never columnized and always hwrapped. However, if the wrapped format exceeds this many lines, then the group will also be nested.

command-line option:

```
--max-rows-cmdline MAX_ROWS_CMDLINE
    If a cmdline positional group consumes more than this
    many lines without nesting, then invalidate the layout
    (and nest)
```

config-file entry:

```
# -----
# Options affecting formatting.
# -----
with section("format") :

    # If a cmdline positional group consumes more than this many lines without
    # nesting, then invalidate the layout (and nest)
    max_rows_cmdline = 2
```

7.2.9 separate_ctrl_name_with_space

If true, separate flow control names from their parentheses with a space

default value:

```
False
```

command-line option:

```
--separate-ctrl-name-with-space [SEPARATE_CTRL_NAME_WITH_SPACE]
    If true, separate flow control names from their
    parentheses with a space
```

config-file entry:

```
# -----
# Options affecting formatting.
# -----
with section("format"):

    # If true, separate flow control names from their parentheses with a space
    separate_ctrl_name_with_space = False
```

7.2.10 separate_fn_name_with_space

If true, separate function names from parentheses with a space

default value:

```
False
```

command-line option:

```
--separate-fn-name-with-space [SEPARATE_FN_NAME_WITH_SPACE]
    If true, separate function names from parentheses with
    a space
```

config-file entry:

```
# -----
# Options affecting formatting.
# -----
with section("format"):
```

(continues on next page)

(continued from previous page)

```
# If true, separate function names from parentheses with a space
separate_fn_name_with_space = False
```

7.2.11 dangle_parens

If a statement is wrapped to more than one line, than dangle the closing parenthesis on its own line.

default value:

```
False
```

detailed description:

If a statement is wrapped to more than one line, than dangle the closing parenthesis on its own line. For example:

```
# dangle_parens = False (default)
set(sources filename_one.cc filename_two.cc filename_three.cc
    filename_four.cc filename_five.cc filename_six.cc)

# dangle_parens = True
set(sources filename_one.cc filename_two.cc filename_three.cc
    filename_four.cc filename_five.cc filename_six.cc
) # <-- this is a dangling parenthesis
```

The default is false.

command-line option:

```
--dangle-parens [DANGLE_PARENS]
    If a statement is wrapped to more than one line, than
    dangle the closing parenthesis on its own line.
```

config-file entry:

```
# -----
# Options affecting formatting.
# -----
with section("format"):

    # If a statement is wrapped to more than one line, than dangle the closing
    # parenthesis on its own line.
    dangle_parens = False
```

7.2.12 dangle_align

If the trailing parenthesis must be ‘dangled’ on its own line, then align it to this reference: *prefix*: the start of the statement, *prefix-indent*: the start of the statement, plus one indentation level, *child*: align to the column of the arguments

default value:

```
'prefix'
```

detailed description:

If the trailing parenthesis must be ‘dangled’ on it’s on line, then align it to this reference. Options are:

- `prefix`: the start of the statement,
- `prefix-indent`: the start of the statement, plus one indentation level
- `child`: align to the column of the arguments

For example:

```
# dangle_align = "prefix"
set(sources filename_one.cc filename_two.cc filename_three.cc
    filename_four.cc filename_five.cc filename_six.cc
) # <-- aligned to the statement

# dangle_align = "prefix-indent"
set(sources filename_one.cc filename_two.cc filename_three.cc
    filename_four.cc filename_five.cc filename_six.cc
) # <-- plus one indentation level

# dangle_align = "child"
set(sources filename_one.cc filename_two.cc filename_three.cc
    filename_four.cc filename_five.cc filename_six.cc
) # <-- aligned to "sources"
```

command-line option:

```
--dangle-align {prefix,prefix-indent,child,off}
    If the trailing parenthesis must be 'dangled' on its
    on line, then align it to this reference: `prefix`:
    the start of the statement, `prefix-indent`: the start
    of the statement, plus one indentation level, `child`:
    align to the column of the arguments
```

config-file entry:

```
# -----
# Options affecting formatting.
# -----
with section("format"):

    # If the trailing parenthesis must be 'dangled' on its on line, then align it
    # to this reference: `prefix`: the start of the statement, `prefix-indent`:
    # the start of the statement, plus one indentation level, `child`: align to
    # the column of the arguments
    dangle_align = 'prefix'
```

7.2.13 min_prefix_chars

If the statement spelling length (including space and parenthesis) is smaller than this amount, then force reject nested layouts.

default value:

```
4
```

detailed description:

This value only comes into play when considering whether or not to nest arguments below their parent. If the number of characters in the parent is less than this value, we will not nest. In the example below, we'll set `line_width=40` for illustration:

```
# min_prefix_chars = 4 (default)
message(
  "With the default value, this "
  "string is allowed to nest beneath "
  "the statement")

# min_prefix_chars = 8
message("With the default value, this "
        "string is allowed to nest beneath "
        "the statement")
```

command-line option:

```
--min-prefix-chars MIN_PREFIX_CHARS
    If the statement spelling length (including space and
    parenthesis) is smaller than this amount, then force
    reject nested layouts.
```

config-file entry:

```
# -----
# Options affecting formatting.
# -----
with section("format"):

    # If the statement spelling length (including space and parenthesis) is
    # smaller than this amount, then force reject nested layouts.
    min_prefix_chars = 4
```

7.2.14 max_prefix_chars

If the statement spelling length (including space and parenthesis) is larger than the tab width by more than this amount, then force reject un-nested layouts.

default value:

```
10
```

command-line option:

```
--max-prefix-chars MAX_PREFIX_CHARS
    If the statement spelling length (including space and
    parenthesis) is larger than the tab width by more than
    this amount, then force reject un-nested layouts.
```

config-file entry:

```
# -----
# Options affecting formatting.
# -----
with section("format"):

    # If the statement spelling length (including space and parenthesis) is larger
    # than the tab width by more than this amount, then force reject un-nested
    # layouts.
    max_prefix_chars = 10
```

7.2.15 max_lines_hwrap

If a candidate layout is wrapped horizontally but it exceeds this many lines, then reject the layout.

default value:

```
2
```

detailed description:

Usually the layout algorithm will prefer to do a simple “word-wrap” of positional arguments, if it can. However if such a simple word-wrap would exceed this many lines, then that layout is rejected, and further passes are tried. The default value is `max_lines_hwrap=2` so, for example:

```
message("This message can easily be wrapped" "to two lines so there is no"
        "problem with using" "horizontal wrapping")
message(
    "However this message cannot be wrapped to two lines because the "
    "arguments are too long. It would require at least three lines."
    "As a result, a simple word-wrap is rejected"
    "And each argument"
    "gets its own line")
```

command-line option:

```
--max-lines-hwrap MAX_LINES_HWRAP
    If a candidate layout is wrapped horizontally but it
    exceeds this many lines, then reject the layout.
```

config-file entry:

```
# -----
# Options affecting formatting.
# -----
with section("format") :

    # If a candidate layout is wrapped horizontally but it exceeds this many
    # lines, then reject the layout.
    max_lines_hwrap = 2
```

7.2.16 line_ending

What style line endings to use in the output.

default value:

```
'unix'
```

detailed description:

This is a string indicating which style of line ending `cmake-format` should use when writing out the formatted file. If `line_ending="unix"` (default) then the output will contain a single newline character (`\n`) at the end of each line. If `line_ending="windows"` then the output will contain a carriage-return and newline pair (`\r\n`). If `line_ending="auto"` then `cmake-format` will observe the first line-ending of the input file and will use style that all lines in the output.

command-line option:

```
--line-ending {windows,unix,auto}
    What style line endings to use in the output.
```

config-file entry:

```
# -----
# Options affecting formatting.
# -----
with section("format") :

    # What style line endings to use in the output.
    line_ending = 'unix'
```

7.2.17 `command_case`

Format command names consistently as ‘lower’ or ‘upper’ case

default value:

```
'canonical'
```

detailed description:

`cmake` ignores case in command names. Very old projects tend to use uppercase for command names, while modern projects tend to use lowercase. There are three options for this variable:

- `upper`: format commands as uppercase
- `lower`: format commands as lowercase
- `canonical`: format standard commands as they are formatted in the `cmake` documentation.

`canonical` is generally the same as `lower` except that some third-party find modules that have moved into the distribution (e.g. `ExternalProject_Add`).

command-line option:

```
--command-case {lower,upper,canonical,unchanged}
                Format command names consistently as 'lower' or
                'upper' case
```

config-file entry:

```
# -----
# Options affecting formatting.
# -----
with section("format"):

    # Format command names consistently as 'lower' or 'upper' case
    command_case = 'canonical'
```

7.2.18 `keyword_case`

Format keywords consistently as ‘lower’ or ‘upper’ case

default value:

```
'unchanged'
```

detailed description:

cmake ignores the case of sentinel words (keywords) in argument lists. Generally projects tend to prefer uppercase (keyword_case="upper") which is the default. Alternatively, this may also be set to lower to format keywords as lowercase.

command-line option:

```
--keyword-case {lower,upper,unchanged}
                Format keywords consistently as 'lower' or 'upper'
                case
```

config-file entry:

```
# -----
# Options affecting formatting.
# -----
with section("format"):

    # Format keywords consistently as 'lower' or 'upper' case
    keyword_case = 'unchanged'
```

7.2.19 always_wrap

A list of command names which should always be wrapped

default value:

```
[]
```

command-line option:

```
--always-wrap [ALWAYS_WRAP [ALWAYS_WRAP ...]]
                A list of command names which should always be wrapped
```

config-file entry:

```
# -----
# Options affecting formatting.
# -----
with section("format"):

    # A list of command names which should always be wrapped
    always_wrap = []
```

7.2.20 enable_sort

If true, the argument lists which are known to be sortable will be sorted lexicographically

default value:

```
True
```

command-line option:

```
--enable-sort [ENABLE_SORT]
           If true, the argument lists which are known to be
           sortable will be sorted lexicographically
```

config-file entry:

```
# -----
# Options affecting formatting.
# -----
with section("format"):

    # If true, the argument lists which are known to be sortable will be sorted
    # lexicographically
    enable_sort = True
```

7.2.21 autosort

If true, the parsers may infer whether or not an argument list is sortable (without annotation).

default value:

```
False
```

command-line option:

```
--autosort [AUTOSORT]
           If true, the parsers may infer whether or not an
           argument list is sortable (without annotation).
```

config-file entry:

```
# -----
# Options affecting formatting.
# -----
with section("format"):
```

(continues on next page)

(continued from previous page)

```
# If true, the parsers may infer whether or not an argument list is sortable
# (without annotation).
autosort = False
```

7.2.22 require_valid_layout

By default, if cmake-format cannot successfully fit everything into the desired linewidth it will apply the last, most aggressive attempt that it made. If this flag is True, however, cmake-format will print error, exit with non-zero status code, and write-out nothing

default value:

```
False
```

detailed description:

By default, if cmake-format cannot successfully fit everything into the desired linewidth it will apply the last, most aggressive attempt that it made. If this flag is True, however, cmake-format will print error, exit with non-zero status code, and write-out nothing

command-line option:

```
--require-valid-layout [REQUIRE_VALID_LAYOUT]
    By default, if cmake-format cannot successfully fit
    everything into the desired linewidth it will apply
    the last, most aggressive attempt that it made. If this
    flag is True, however, cmake-format will print error,
    exit with non-zero status code, and write-out nothing
```

config-file entry:

```
# -----
# Options affecting formatting.
# -----
with section("format"):

    # By default, if cmake-format cannot successfully fit everything into the
    # desired linewidth it will apply the last, most aggressive attempt that it
    # made. If this flag is True, however, cmake-format will print error, exit
    # with non-zero status code, and write-out nothing
    require_valid_layout = False
```

7.2.23 layout_passes

A dictionary mapping layout nodes to a list of wrap decisions. See the documentation for more information.

default value:

```
{ }
```

detailed description:

See the *Formatting Algorithm* section for more information on how *cmake-format* uses multiple passes to converge on the final layout of the listfile source code. This option can be used to override the default behavior. The format of this option is a dictionary, where the keys are the names of the different layout node classes:

- StatementNode
- ArgGroupNode
- KWargGroupNode
- PargGroupNode
- ParenGroupNode

The dictionary values are a list of pairs (2-tuples) in the form of (passno, wrap-decision). Where passno is the pass number at which the wrap-decision becomes active, and wrap-decision is a boolean (true/false). For each layout pass, the decision of whether or not the node should wrap (either nested, or vertical) is looked-up from this map.

config-file entry:

```
# -----
# Options affecting formatting.
# -----
with section("format"):

    # A dictionary mapping layout nodes to a list of wrap decisions. See the
    # documentation for more information.
    layout_passes = { }
```

7.3 Options affecting comment reflow and formatting.

7.3.1 bullet_char

What character to use for bulleted lists

default value:

```
' * '
```

command-line option:

```
--bullet-char BULLET_CHAR
           What character to use for bulleted lists
```

config-file entry:

```
# -----  
# Options affecting comment reflow and formatting.  
# -----  
with section("markup"):  
  
    # What character to use for bulleted lists  
    bullet_char = '*'
```

7.3.2 enum_char

What character to use as punctuation after numerals in an enumerated list

default value:

```
'.'
```

command-line option:

```
--enum-char ENUM_CHAR  
        What character to use as punctuation after numerals in  
        an enumerated list
```

config-file entry:

```
# -----  
# Options affecting comment reflow and formatting.  
# -----  
with section("markup"):  
  
    # What character to use as punctuation after numerals in an enumerated list  
    enum_char = '.'
```

7.3.3 first_comment_is_literal

If comment markup is enabled, don't reflow the first comment block in each listfile. Use this to preserve formatting of your copyright/license statements.

default value:

```
False
```

command-line option:

```
--first-comment-is-literal [FIRST_COMMENT_IS_LITERAL]
    If comment markup is enabled, don't reflow the first
    comment block in each listfile. Use this to preserve
    formatting of your copyright/license statements.
```

config-file entry:

```
# -----
# Options affecting comment reflow and formatting.
# -----
with section("markup") :

    # If comment markup is enabled, don't reflow the first comment block in each
    # listfile. Use this to preserve formatting of your copyright/license
    # statements.
    first_comment_is_literal = False
```

7.3.4 literal_comment_pattern

If comment markup is enabled, don't reflow any comment block which matches this (regex) pattern. Default is *None* (disabled).

default value:

```
None
```

command-line option:

```
--literal-comment-pattern LITERAL_COMMENT_PATTERN
    If comment markup is enabled, don't reflow any comment
    block which matches this (regex) pattern. Default is
    `None` (disabled).
```

config-file entry:

```
# -----
# Options affecting comment reflow and formatting.
# -----
with section("markup") :

    # If comment markup is enabled, don't reflow any comment block which matches
    # this (regex) pattern. Default is `None` (disabled).
    literal_comment_pattern = None
```

7.3.5 fence_pattern

Regular expression to match preformat fences in comments default= `r'^\s*([\~]{3}[\~]*) (.*)$'`

default value:

```
'^\s*([\~]{3}[\~]*) (.*)$'
```

command-line option:

```
--fence-pattern FENCE_PATTERN
        Regular expression to match preformat fences in
        comments default= ``r'^\s*([\~]{3}[\~]*) (.*)$'``
```

config-file entry:

```
# -----
# Options affecting comment reflow and formatting.
# -----
with section("markup"):

    # Regular expression to match preformat fences in comments default=
    # ``r'^\s*([\~]{3}[\~]*) (.*)$'``
    fence_pattern = '^\s*([\~]{3}[\~]*) (.*)$'
```

7.3.6 ruler_pattern

Regular expression to match rulers in comments default= `r'^\s*[^\\w\\s]{3}.*[^\\w\\s]{3}$'`

default value:

```
'^\s*[^\\w\\s]{3}.*[^\\w\\s]{3}$'
```

command-line option:

```
--ruler-pattern RULER_PATTERN
        Regular expression to match rulers in comments
        default= ``r'^\s*[^\\w\\s]{3}.*[^\\w\\s]{3}$'``
```

config-file entry:

```
# -----
# Options affecting comment reflow and formatting.
# -----
with section("markup"):
```

(continues on next page)

(continued from previous page)

```
# Regular expression to match rulers in comments default=
# ``r'^\s*[\w\s]{3}.*[\w\s]{3}$'``
ruler_pattern = '^\\s*[^\\w\\s]{3}.*[^\\w\\s]{3}$'
```

7.3.7 explicit_trailing_pattern

If a comment line matches starts with this pattern then it is explicitly a trailing comment for the preceeding argument. Default is '#<'

default value:

```
'#<'
```

command-line option:

```
--explicit-trailing-pattern EXPLICIT_TRAILING_PATTERN
    If a comment line matches starts with this pattern
    then it is explicitly a trailing comment for the
    preceeding argument. Default is '#<'
```

config-file entry:

```
# -----
# Options affecting comment reflow and formatting.
# -----
with section("markup"):

    # If a comment line matches starts with this pattern then it is explicitly a
    # trailing comment for the preceeding argument. Default is '#<'
    explicit_trailing_pattern = '#<'
```

7.3.8 hashruler_min_length

If a comment line starts with at least this many consecutive hash characters, then don't lstrip() them off. This allows for lazy hash rulers where the first hash char is not separated by space

default value:

```
10
```

command-line option:

```
--hashruler-min-length HASHRULER_MIN_LENGTH
    If a comment line starts with at least this many
    consecutive hash characters, then don't rstrip() them
    off. This allows for lazy hash rulers where the first
    hash char is not separated by space
```

config-file entry:

```
# -----
# Options affecting comment reflow and formatting.
# -----
with section("markup") :

    # If a comment line starts with at least this many consecutive hash
    # characters, then don't lstrip() them off. This allows for lazy hash rulers
    # where the first hash char is not separated by space
    hashruler_min_length = 10
```

7.3.9 canonicalize_hashrulers

If true, then insert a space between the first hash char and remaining hash chars in a hash ruler, and normalize its length to fill the column

default value:

```
True
```

command-line option:

```
--canonicalize-hashrulers [CANONICALIZE_HASHRULERS]
    If true, then insert a space between the first hash
    char and remaining hash chars in a hash ruler, and
    normalize its length to fill the column
```

config-file entry:

```
# -----
# Options affecting comment reflow and formatting.
# -----
with section("markup") :

    # If true, then insert a space between the first hash char and remaining hash
    # chars in a hash ruler, and normalize its length to fill the column
    canonicalize_hashrulers = True
```

7.3.10 enable_markup

enable comment markup parsing and reflow

default value:`True`**command-line option:**

```
--enable-markup [ENABLE_MARKUP]
           enable comment markup parsing and reflow
```

config-file entry:

```
# -----
# Options affecting comment reflow and formatting.
# -----
with section("markup"):

    # enable comment markup parsing and reflow
    enable_markup = True
```

7.4 Options affecting the linter

7.4.1 disabled_codes

a list of lint codes to disable

default value:`[]`**command-line option:**

```
--disabled-codes [DISABLED_CODES [DISABLED_CODES ...]]
           a list of lint codes to disable
```

config-file entry:

```
# -----
# Options affecting the linter
# -----
with section("lint"):

    # a list of lint codes to disable
    disabled_codes = []
```

7.4.2 function_pattern

regular expression pattern describing valid function names

default value:

```
'[0-9a-z_]+'
```

command-line option:

```
--function-pattern FUNCTION_PATTERN
                        regular expression pattern describing valid function
                        names
```

config-file entry:

```
# -----
# Options affecting the linter
# -----
with section("lint"):

    # regular expression pattern describing valid function names
    function_pattern = '[0-9a-z_]+'
```

7.4.3 macro_pattern

regular expression pattern describing valid macro names

default value:

```
'[0-9A-Z_]+'
```

command-line option:

```
--macro-pattern MACRO_PATTERN
                  regular expression pattern describing valid macro
                  names
```

config-file entry:

```
# -----
# Options affecting the linter
# -----
with section("lint"):
```

(continues on next page)

(continued from previous page)

```
# regular expression pattern describing valid macro names
macro_pattern = '[0-9A-Z_]+'
```

7.4.4 global_var_pattern

regular expression pattern describing valid names for variables with global (cache) scope

default value:

```
'[A-Z][0-9A-Z_]+'
```

command-line option:

```
--global-var-pattern GLOBAL_VAR_PATTERN
    regular expression pattern describing valid names for
    variables with global (cache) scope
```

config-file entry:

```
# -----
# Options affecting the linter
# -----
with section("lint"):

    # regular expression pattern describing valid names for variables with global
    # (cache) scope
    global_var_pattern = '[A-Z][0-9A-Z_]+'
```

7.4.5 internal_var_pattern

regular expression pattern describing valid names for variables with global scope (but internal semantic)

default value:

```
'_[A-Z][0-9A-Z_]+'
```

command-line option:

```
--internal-var-pattern INTERNAL_VAR_PATTERN
    regular expression pattern describing valid names for
    variables with global scope (but internal semantic)
```

config-file entry:

```
# -----  
# Options affecting the linter  
# -----  
with section("lint"):  
  
    # regular expression pattern describing valid names for variables with global  
    # scope (but internal semantic)  
    internal_var_pattern = '_[A-Z][0-9A-Z_]+'
```

7.4.6 local_var_pattern

regular expression pattern describing valid names for variables with local scope

default value:

```
'[a-z][a-z0-9_]+'
```

command-line option:

```
--local-var-pattern LOCAL_VAR_PATTERN  
    regular expression pattern describing valid names for  
    variables with local scope
```

config-file entry:

```
# -----  
# Options affecting the linter  
# -----  
with section("lint"):  
  
    # regular expression pattern describing valid names for variables with local  
    # scope  
    local_var_pattern = '[a-z][a-z0-9_]+'
```

7.4.7 private_var_pattern

regular expression pattern describing valid names for private directory variables

default value:

```
'_[0-9a-z_]+'
```

command-line option:

```
--private-var-pattern PRIVATE_VAR_PATTERN
                        regular expression pattern describing valid names for
                        privatedirectory variables
```

config-file entry:

```
# -----
# Options affecting the linter
# -----
with section("lint"):

    # regular expression pattern describing valid names for privatedirectory
    # variables
    private_var_pattern = '_[0-9a-z]+'
```

7.4.8 public_var_pattern

regular expression pattern describing valid names for public directory variables

default value:

```
'[A-Z][0-9A-Z]+'
```

command-line option:

```
--public-var-pattern PUBLIC_VAR_PATTERN
                        regular expression pattern describing valid names for
                        public directory variables
```

config-file entry:

```
# -----
# Options affecting the linter
# -----
with section("lint"):

    # regular expression pattern describing valid names for public directory
    # variables
    public_var_pattern = '[A-Z][0-9A-Z]+'
```

7.4.9 argument_var_pattern

regular expression pattern describing valid names for function/macro arguments and loop variables.

default value:

```
'[a-z][a-z0-9_]+'
```

command-line option:

```
--argument-var-pattern ARGUMENT_VAR_PATTERN
                        regular expression pattern describing valid names for
                        function/macro arguments and loop variables.
```

config-file entry:

```
# -----
# Options affecting the linter
# -----
with section("lint"):

    # regular expression pattern describing valid names for function/macro
    # arguments and loop variables.
    argument_var_pattern = '[a-z][a-z0-9_]+'
```

7.4.10 keyword_pattern

regular expression pattern describing valid names for keywords used in functions or macros

default value:

```
'[A-Z][0-9A-Z_]+'
```

command-line option:

```
--keyword-pattern KEYWORD_PATTERN
                        regular expression pattern describing valid names for
                        keywords used in functions or macros
```

config-file entry:

```
# -----
# Options affecting the linter
# -----
with section("lint"):

    # regular expression pattern describing valid names for keywords used in
    # functions or macros
    keyword_pattern = '[A-Z][0-9A-Z_]+'
```

7.4.11 max_conditionals_custom_parser

In the heuristic for C0201, how many conditionals to match within a loop in before considering the loop a parser.

default value:

```
2
```

command-line option:

```
--max-conditionals-custom-parser MAX_CONDITIONALS_CUSTOM_PARSER
    In the heuristic for C0201, how many conditionals to
    match within a loop in before considering the loop a
    parser.
```

config-file entry:

```
# -----
# Options affecting the linter
# -----
with section("lint"):

    # In the heuristic for C0201, how many conditionals to match within a loop in
    # before considering the loop a parser.
    max_conditionals_custom_parser = 2
```

7.4.12 min_statement_spacing

Require at least this many newlines between statements

default value:

```
1
```

command-line option:

```
--min-statement-spacing MIN_STATEMENT_SPACING
    Require at least this many newlines between statements
```

config-file entry:

```
# -----
# Options affecting the linter
# -----
with section("lint"):
```

(continues on next page)

(continued from previous page)

```
# Require at least this many newlines between statements
min_statement_spacing = 1
```

7.4.13 max_statement_spacing

Require no more than this many newlines between statements

default value:

```
2
```

command-line option:

```
--max-statement-spacing MAX_STATEMENT_SPACING
                        Require no more than this many newlines between
                        statements
```

config-file entry:

```
# -----
# Options affecting the linter
# -----
with section("lint"):

    # Require no more than this many newlines between statements
    max_statement_spacing = 2
```

7.4.14 max_returns

default value:

```
6
```

command-line option:

```
--max-returns MAX_RETURNS
```

config-file entry:

```
# -----  
# Options affecting the linter  
# -----  
with section("lint"):  
    max_returns = 6
```

7.4.15 max_branches

default value:

```
12
```

command-line option:

```
--max-branches MAX_BRANCHES
```

config-file entry:

```
# -----  
# Options affecting the linter  
# -----  
with section("lint"):  
    max_branches = 12
```

7.4.16 max_arguments

default value:

```
5
```

command-line option:

```
--max-arguments MAX_ARGUMENTS
```

config-file entry:

```
# -----  
# Options affecting the linter  
# -----  
with section("lint"):  
    max_arguments = 5
```

7.4.17 max_localvars

default value:

```
15
```

command-line option:

```
--max-localvars MAX_LOCALVARS
```

config-file entry:

```
# -----  
# Options affecting the linter  
# -----  
with section("lint"):  
    max_localvars = 15
```

7.4.18 max_statements

default value:

```
50
```

command-line option:

```
--max-statements MAX_STATEMENTS
```

config-file entry:

```
# -----  
# Options affecting the linter  
# -----  
with section("lint"):  
    max_statements = 50
```

7.5 Options affecting file encoding

7.5.1 emit_byteorder_mark

If true, emit the unicode byte-order mark (BOM) at the start of the file

default value:`False`**detailed description:**

If `true` (the default is `false`) then output the unicode byte-order at the start of the document.

command-line option:

```
--emit-byteorder-mark [EMIT_BYTEORDER_MARK]
                        If true, emit the unicode byte-order mark (BOM) at the
                        start of the file
```

config-file entry:

```
# -----
# Options affecting file encoding
# -----
with section("encode"):

    # If true, emit the unicode byte-order mark (BOM) at the start of the file
    emit_byteorder_mark = False
```

7.5.2 input_encoding

Specify the encoding of the input file. Defaults to `utf-8`

default value:`'utf-8'`**detailed description:**

Specify the input encoding of the file. The format of this string is *anything understood* by the `encoding=` keyword of the python `open()` function. The default is `utf-8`.

command-line option:

```
--input-encoding INPUT_ENCODING
                        Specify the encoding of the input file. Defaults to
                        utf-8
```

config-file entry:

```
# -----  
# Options affecting file encoding  
# -----  
with section("encode") :  
  
    # Specify the encoding of the input file. Defaults to utf-8  
    input_encoding = 'utf-8'
```

7.5.3 output_encoding

Specify the encoding of the output file. Defaults to utf-8. Note that cmake only claims to support utf-8 so be careful when using anything else

default value:

```
'utf-8'
```

detailed description:

Specify the output encoding of the file. The format of this string is *anything understood* by the `encoding=` keyword of the python `open()` function. The default is utf-8.

command-line option:

```
--output-encoding OUTPUT_ENCODING  
                        Specify the encoding of the output file. Defaults to  
                        utf-8. Note that cmake only claims to support utf-8 so  
                        be careful when using anything else
```

config-file entry:

```
# -----  
# Options affecting file encoding  
# -----  
with section("encode") :  
  
    # Specify the encoding of the output file. Defaults to utf-8. Note that cmake  
    # only claims to support utf-8 so be careful when using anything else  
    output_encoding = 'utf-8'
```

7.6 Miscellaneous configurations options.

7.6.1 per_command

A dictionary containing any per-command configuration overrides. Currently only *command_case* is supported.

default value:

```
{ }
```

config-file entry:

```
# -----  
# Miscellaneous configurations options.  
# -----  
with section("misc"):  
  
    # A dictionary containing any per-command configuration overrides. Currently  
    # only `command_case` is supported.  
    per_command = { }
```

Implementing Custom Parsers

8.1 Using the simple specification

You can tell the parser how to interpret your custom commands by specifying the format of their call signature using the `additional_commands` configuration variable. The format of the variable is a dictionary (a mapping in JSON/YAML) where the keys should be the name of the command and the values satisfy the following (recursive) schema:

```
POSITIONAL_SPEC = {
    # Number of positional arguments. Can be an integer indicating an exact
    # number of arguments, or a string satisfying the regex:
    # "(\d*)\+?/\*/\?". The semantics of the string:
    #
    # * "?": zero or one
    # * "*": zero or more
    # * "+": one or more
    # * (\d+): exactly `n` positional arguments (e.g. "3")
    # * (\d+)\+ : as many positional arguments as available, but at least
    #   `n` (e.g. "3+")
    #
    "nargs": <string,int>,

    # Stores a list of keywords that are treated as positional arguments and
    # included in the positional group, but annotated as keywords for special
    # processing (e.g. case canonicalization).
    "flags": [<string>, ...],

    # Stores a list of tags to apply to this positional argument group. See
    # below for more information on tags.
    "tags": [<string>]

    # If true, then this specification will be repeated indefinitely
    "legacy": <bool>,
}
```

(continues on next page)

(continued from previous page)

```
KEYWORD_SPEC = {
    "pargs": [POSITIONAL_SPEC, ...],
    "kwargs": {<string>: KEYWORD_SPEC}
}
```

As a shorthand:

- If a keyword specification contains no nested *kwargs* and only one positional argument group, you may omit the *KEYWORD_SPEC* overhead and write the *POSITIONAL_SPEC* directly (including shorthands below)
- There is only one positional group, you may omit the list
- The a positional contains now flags, and is not tagged, you may omit the outer dictionary and write only the *nargs* value.

8.1.1 Tags

Positional argument groups support the following tags:

- *cmdline*: The positional arguments of this group are command line arguments in a shell command. In particular this means that they will not be wrapped vertically
- *file-list*: The positional arguments of this group are names/paths of files. In the future this tag will enable certain filters for formatting or linting, such as automatic sorting.

8.2 Generating simple specifications

There is an experimental utility called `cmake-genparsers` which can generate simple specifications for `cmake` functions and macros that use `cmake_parse_arguments`. The tool has very limited ability to process `cmake` arguments. There is a frontend included in the `python` distribution. Usage is

```
usage:
cmake-genparsers [-h] [-o OUTFILE_PATH] infilepath [infilepath ...]

Parse cmake listfiles, find function and macro declarations, and generate
parsers for them.

positional arguments:
  infilepaths

optional arguments:
  -h, --help            show this help message and exit
  -v, --version         show program's version number and exit
  -l {error,warning,info,debug}, --log-level {error,warning,info,debug}
  -o OUTFILE_PATH, --outfile-path OUTFILE_PATH
                        Write results to this file. Default is stdout.
  -f {json,yaml,python}, --output-format {json,yaml,python}
```

For example:

```
:~$ cmake-genparsers /usr/share/cmake-3.10/Modules/*.cmake
{ 'add_command': {'pargs': {'nargs': 1}},
  'add_compiler_export_flags': {'pargs': {'nargs': 0}},
```

(continues on next page)

(continued from previous page)

```
'add_feature_info': {'pargs': {'nargs': 3}},
'add_file_dependencies': {'pargs': {'nargs': 1}},
'add_flex_bison_dependency': {'pargs': {'nargs': 2}},
'add_jar': { 'kwargs': { 'ENTRY_POINT': 1,
                        'INCLUDE_JARS': '+',
                        'MANIFEST': 1,
                        'OUTPUT_DIR': 1,
                        'OUTPUT_NAME': 1,
...

```

or

```
:~$ cmake-genparsers -f yaml /usr/share/cmake-3.10/Modules/*.cmake
add_file_dependencies:
  pargs:
    nargs: 1
android_add_test_data:
  pargs:
    nargs: 1+
    flags: []
  kwargs: {}
get_bundle_main_executable:
  pargs:
...

```

This tool is still in the early stages of development so don't be surprised if it chokes on some of your input files, or if it does not properly generate specifications for your commands.

CMake Parse Tree

This document is intended to describe the high level organization of how cmake listfiles are parsed and organized into an abstract syntax tree.

Digestion and formatting of a listfile is done in four phases:

- tokenization
- parsing
- layout tree construction
- layout / reflow

9.1 Tokenizer

Listfiles are first digested into a sequence of tokens. The tokenizer is implemented in *lex.py* and defines the following types of tokens:

Token Type	Description	Example
QUOTED_LITERAL	A single or double quoted string, from the first quote to the first subsequent un-escaped quote	"foo" 'bar'
BRACKET_ARGUMENT	A bracket-quoted argument of a cmake-statement	[=[hello foo]=]
NUMBER	Unquoted numeric literal	1234
LEFT_PAREN	A left parenthesis	(
RIGHT_PAREN	A right parenthesis	)
WORD	An unquoted literal string which matches lexical rules such that it could be a cmake entity name, such as the name of a function or variable	foo foo_bar
DEREF	A variable dereference expression, from the dollar sign up to the outer most right curly brace	\${foo} \${foo_\${bar}}
NEWLINE	A single carriage return, newline or (carriage-return, newline) pair	
WHITESPACE	A continuous sequence of space, tab or other ascii whitespace	
BRACKET_COMMENT	A bracket-quoted comment string	#=[hello]=]
COMMENT	A single line starting with a hash	# hello world
UN-QUOTED_LITERAL	A sequence of non-whitespace characters used as a cmake argument but not satisfying the requirements of a cmake name	--verbose
FOR-MAT_OFF	A special comment disabling cmake-format temporarily	cmake-format: " off"
FOR-MAT_OFF	A special comment re-enabling	cmake-format: " on"

Each token covers a continuous sequence of characters of the input file. Furthermore, the sequence of tokens digest from the file covers the entire range of infile offsets. The `Token` object stores information about the input file byte offset, line number, and column number of it's start location. Note that for `utf-8` input where a character may be composed of more than one byte, the `(row, col)` location is the location of the character while the `offset` is the index of the first byte of the character.

You can inspect the tokenization of a listfile by executing `cmake-format` with `--dump lex`. For example:

```
Token(type=NEWLINE, content='\n', line=1, col=0)
Token(type=WORD, content='cmake_minimum_required', line=2, col=0)
Token(type=LEFT_PAREN, content='(', line=2, col=22)
Token(type=WORD, content='VERSION', line=2, col=23)
Token(type=WHITESPACE, content=' ', line=2, col=30)
Token(type=UNQUOTED_LITERAL, content='3.5', line=2, col=31)
Token(type=RIGHT_PAREN, content=')', line=2, col=34)
Token(type=NEWLINE, content='\n', line=2, col=35)
Token(type=WORD, content='project', line=3, col=0)
Token(type=LEFT_PAREN, content='(', line=3, col=7)
Token(type=WORD, content='demo', line=3, col=8)
Token(type=RIGHT_PAREN, content=')', line=3, col=12)
Token(type=NEWLINE, content='\n', line=3, col=13)
Token(type=WORD, content='if', line=4, col=0)
Token(type=LEFT_PAREN, content='(', line=4, col=2)
Token(type=WORD, content='FOO', line=4, col=3)
Token(type=WHITESPACE, content=' ', line=4, col=6)
Token(type=WORD, content='AND', line=4, col=7)
Token(type=WHITESPACE, content=' ', line=4, col=10)
Token(type=LEFT_PAREN, content='(', line=4, col=11)
Token(type=WORD, content='BAR', line=4, col=12)
```

(continues on next page)

(continued from previous page)

```
Token(type=WHITESPACE, content=' ', line=4, col=15)
Token(type=WORD, content='OR', line=4, col=16)
Token(type=WHITESPACE, content=' ', line=4, col=18)
Token(type=WORD, content='BAZ', line=4, col=19)
Token(type=RIGHT_PAREN, content=')', line=4, col=22)
Token(type=RIGHT_PAREN, content=')', line=4, col=23)
Token(type=NEWLINE, content='\n', line=4, col=24)
Token(type=WHITESPACE, content=' ', line=5, col=0)
Token(type=WORD, content='add_library', line=5, col=2)
Token(type=LEFT_PAREN, content='(', line=5, col=13)
Token(type=WORD, content='hello', line=5, col=14)
Token(type=WHITESPACE, content=' ', line=5, col=19)
Token(type=UNQUOTED_LITERAL, content='hello.cc', line=5, col=20)
Token(type=RIGHT_PAREN, content=')', line=5, col=28)
Token(type=NEWLINE, content='\n', line=5, col=29)
Token(type=WORD, content='endif', line=6, col=0)
Token(type=LEFT_PAREN, content='(', line=6, col=5)
Token(type=RIGHT_PAREN, content=')', line=6, col=6)
Token(type=NEWLINE, content='\n', line=6, col=7)
```

9.2 Parser: Syntax Tree

`cmake-format` parses the token stream in a single pass. The state machine of the parser is maintained by the program stack (i.e. the parse functions are called recursively) and each node type in the tree has it's own parse function.

There are fourteen types of nodes in the parse tree. They are described below along with the list of possible child node types.

9.2.1 Node Types

Node Type	Description	Allowed Children
BODY	A generic section of a cmake document. This node type is found at the root of the parse tree and within conditional/flow control statements	COMMENT STATEMENT WHITESPACE
WHITESPACE	A consecutive sequence of whitespace tokens between any two other types of nodes.	(none)
COMMENT	A sequence of one or more comment lines. The node consists of all consecutive comment lines unbroken by additional newlines or a single BRACKET_COMMENT token.	(token)
STATEMENT	A cmake statement (i.e. function call)	ARGGROUP COMMENT FUNNAME
FLOW_CONTROL	One or more cmake statements and their nested bodies representing a flow control construct (i.e. if or foreach).	STATEMENT BODY
ARGGROUP	Top-level collection of one or more positional, kwarg, or flag groups	PARGGROUP KWARGGROUP PARGROUP FLAGGROUP COMMENT
PARGROUP	Grouping of one or more positional arguments.	ARGUMENT COMMENT
FLAGGROUP	A grouping of one or more positional arguments, each of which is a flag	FLAG COMMENT
KWARGGROUP	A KEYWORD group, starting with the keyword and ending with the last argument associated with that keyword	KEYWORD ARGGROUP
PARGROUP	A parenthetical group, starting with a left parenthesis and ending with the matching right parenthesis	ARGGROUP
FUNNAME	Consists of a single token containing the name of the function/command in a statement with that keyword	(token)
ARGUMENT	Consists of a single token, containing the literal argument of a statement, and optionally a comment associated with it	(token) COMMENT
KEYWORD	Consists of a single token, containing the literal keyword of a keyword group, and optionally a comment associated with it	(token) COMMENT
FLAG	Consists of a single token, containing the literal keyword of a statment flag, and optionally a comment associated with it	(token) COMMENT
ONOFFSWITCH	Consists of a single token, containing the sentinal comment line # cmake-format: on or # cmake-format: off.	(token)

You can inspect the parse tree of a listfile by `cmake-format` with `--dump parse`. For example:

```

└─ BODY: 1:0
    └─ WHITESPACE: 1:0
        └─ Token(type=NEWLINE, content='\n', line=1, col=0)
    └─ STATEMENT: 2:0
        └─ FUNNAME: 2:0
            └─ Token(type=WORD, content='cmake_minimum_required', line=2, col=0)
        └─ LPAREN: 2:22
            └─ Token(type=LEFT_PAREN, content='(', line=2, col=22)
        └─ ARGGROUP: 2:23
            └─ KWARGGROUP: 2:23
                └─ KEYWORD: 2:23
                    └─ Token(type=WORD, content='VERSION', line=2, col=23)
                └─ Token(type=WHITESPACE, content=' ', line=2, col=30)
                └─ ARGGROUP: 2:31

```

(continues on next page)

(continued from previous page)

```

└─ PARGGROUP: 2:31
  └─ ARGUMENT: 2:31
    └─ Token(type=UNQUOTED_LITERAL, content='3.5', line=2,
↪col=31)
  └─ RPAREN: 2:34
    └─ Token(type=RIGHT_PAREN, content=')', line=2, col=34)
  └─ WHITESPACE: 2:35
    └─ Token(type=NEWLINE, content='\n', line=2, col=35)
  └─ STATEMENT: 3:0
    └─ FUNNAME: 3:0
      └─ Token(type=WORD, content='project', line=3, col=0)
    └─ LPAREN: 3:7
      └─ Token(type=LEFT_PAREN, content='(', line=3, col=7)
    └─ ARGGROUP: 3:8
      └─ PARGGROUP: 3:8
        └─ ARGUMENT: 3:8
          └─ Token(type=WORD, content='demo', line=3, col=8)
      └─ RPAREN: 3:12
        └─ Token(type=RIGHT_PAREN, content=')', line=3, col=12)
    └─ WHITESPACE: 3:13
      └─ Token(type=NEWLINE, content='\n', line=3, col=13)
    └─ FLOW_CONTROL: 4:0
      └─ STATEMENT: 4:0
        └─ FUNNAME: 4:0
          └─ Token(type=WORD, content='if', line=4, col=0)
        └─ LPAREN: 4:2
          └─ Token(type=LEFT_PAREN, content='(', line=4, col=2)
        └─ ARGGROUP: 4:3
          └─ PARGGROUP: 4:3
            └─ ARGUMENT: 4:3
              └─ Token(type=WORD, content='FOO', line=4, col=3)
              └─ Token(type=WHITESPACE, content=' ', line=4, col=6)
            └─ KWARGGROUP: 4:7
              └─ KEYWORD: 4:7
                └─ Token(type=WORD, content='AND', line=4, col=7)
              └─ Token(type=WHITESPACE, content=' ', line=4, col=10)
              └─ ARGGROUP: 4:11
                └─ PARENGROUP: 4:11
                  └─ LPAREN: 4:11
                    └─ Token(type=LEFT_PAREN, content='(', line=4, col=11)
                  └─ ARGGROUP: 4:12
                    └─ PARGGROUP: 4:12
                      └─ ARGUMENT: 4:12
                        └─ Token(type=WORD, content='BAR', line=4,
↪col=12)
                        └─ Token(type=WHITESPACE, content=' ', line=4,
↪col=15)
                      └─ KWARGGROUP: 4:16
                        └─ KEYWORD: 4:16
                          └─ Token(type=WORD, content='OR', line=4,
↪col=16)
                        └─ Token(type=WHITESPACE, content=' ', line=4,
↪col=18)
                      └─ ARGGROUP: 4:19
                        └─ PARGGROUP: 4:19
                          └─ ARGUMENT: 4:19
                            └─ Token(type=WORD, content='BAZ',
↪line=4, col=19)

```

(continues on next page)

(continued from previous page)




9.3 Formatter: Layout Tree

As of version 0.4.0, `cmake-format` will create a tree structure parallel to the parse tree and called the “layout tree”. Each node in the layout tree points to at most one node in the parse tree. The structure of the layout tree is essentially the same as the parse tree with the following exceptions:

1. The primary argument group of a statement is expanded, so that the possible children of a STATEMENT layout node are: ARGGROUP, ARGUMENT, COMMENT, FLAG, FUNNAME, KWARGROUP.
2. WHITESPACE nodes containing less than two newlines are dropped, and not represented in the layout tree.

You can inspect the layout tree of a listfile by `cmake-format` with `--dump layout`. For example:



(continues on next page)

(continued from previous page)



(continues on next page)

(continued from previous page)

```
└─ RPAREN, (passno=0,wrap=F,ok=T) pos:(4,6) coextent:7
```

9.4 Example file

The example file used to create the tree dumps above is::

```
cmake_minimum_required(VERSION 3.5)
project(demo)
if(FOO AND (BAR OR BAZ))
  add_library(hello hello.cc)
endif()
```

CHAPTER 10

Parser Algorithm

TODO(josh): add notes regarding the standard parse function and what it does with regard to positionals and kwargs. Then add notes about the new style parser which uses nested function calls. Note that the motivation for this is commands that take multiple forms. We need computational logic to look at the first argument to determine how to parse the rest of it.

CHAPTER 11

Automatic Parsers

cmake provides help commands which can print out the usage information for all of the builtin statements that it supports. You can get a list of commands with

```
cmake --help-command-list
```

And you can get the help text for a command with (for example):

```
cmake --help-command add_custom_command
```

In general (but not always) the usage string is given in a restructured-text block that looks like this:

```
::

add_custom_command(TARGET <target>
                   PRE_BUILD | PRE_LINK | POST_BUILD
                   COMMAND command1 [ARGS] [args1...]
                   [COMMAND command2 [ARGS] [args2...] ...]
                   [BYPRODUCTS [files...]]
                   [WORKING_DIRECTORY dir]
                   [COMMENT comment]
                   [VERBATIM] [USES_TERMINAL])
```

The syntax of these usage strings isn't 100% consistent but if we could generate a parser that even understands *most* of these strings then that would greatly reduce the maintenance load.

11.1 Expect Objects

The output of the specification parser is an “Expect Tree”. A tree of objects representing what is expected from a statement. If a sequence of tokens satisfies an expected subtree then the a corresponding parse tree is generated. If a mandatory expected subtree is not satisfied then an error is generated. If an optional expected subtree is not satisfied then the next sibling is tried.

11.2 Case studies

11.2.1 Inconsistent usage of angle brackets

Sometimes mandatory arguments are shown in angle brackets, sometimes not. I can't really figure a pattern for when they are used and when they are not.

11.2.2 Ellipses

Whether or not there is a space between an elipsis and the preceeding token seems to imply something about what is repeated.

```
add_custom_command(TARGET <target>
                   PRE_BUILD | PRE_LINK | POST_BUILD
                   COMMAND command1 [ARGS] [args1...]
                   [COMMAND command2 [ARGS] [args2...] ...]
                   [BYPRODUCTS [files...]]
                   [WORKING_DIRECTORY dir]
                   [COMMENT comment]
                   [VERBATIM] [USES_TERMINAL])
```

Note that the elipsis for “COMMAND” is inside the bracket above, but is outside the bracket here:

```
add_dependencies(<target> [<target-dependency>]...)
```

11.2.3 Choices

Pipe character is used to separate choices.

```
configure_file(<input> <output>
              [COPYONLY] [ESCAPE_QUOTES] [@ONLY]
              [NEWLINE_STYLE [UNIX|DOS|WIN32|LF|CRLF] ])
```

Sometimes it's a mandatory choice

```
ctest_test([BUILD <build-dir>] [APPEND]
           [START <start-number>]
           [END <end-number>]
           [STRIDE <stride-number>]
           [EXCLUDE <exclude-regex>]
           [INCLUDE <include-regex>]
           [EXCLUDE_LABEL <label-exclude-regex>]
           [INCLUDE_LABEL <label-include-regex>]
           [EXCLUDE_FIXTURE <regex>]
           [EXCLUDE_FIXTURE_SETUP <regex>]
           [EXCLUDE_FIXTURE_CLEANUP <regex>]
           [PARALLEL_LEVEL <level>]
           [TEST_LOAD <threshold>]
           [SCHEDULE_RANDOM <ON|OFF>]
           [STOP_TIME <time-of-day>]
           [RETURN_VALUE <result-var>]
           [CAPTURE_CMAKE_ERROR <result-var>]
           [QUIET]
           )
```

Sometimes the choice is among literals, in which case there are no surrounding brackets.

```
file(GLOB <variable>
      [LIST_DIRECTORIES true|false] [RELATIVE <path>]
      [<globbing-expressions>...])
```

11.2.4 Mandatory Sequence

In this case the literal pattern is listed inside the mandatory group pattern (angle brackets).

```
file(GENERATE OUTPUT output-file
      <INPUT input-file|CONTENT content>
      [CONDITION expression])
```

This one is pretty complex, and also demonstrates the nested bracket usage. I think the indication here is that “you must have one of these choices.

```
get_property(<variable>
             <GLOBAL
             DIRECTORY [dir]
             TARGET    <target>
             SOURCE    <source>
             INSTALL   <file>
             TEST      <test>
             CACHE     <entry>
             VARIABLE>
             PROPERTY <name>
             [SET | DEFINED | BRIEF_DOCS | FULL_DOCS])
```

11.2.5 Nested Optionals

```
install(TARGETS targets... [EXPORT <export-name>]
        [ [ARCHIVE|LIBRARY|RUNTIME|OBJECTS|FRAMEWORK|BUNDLE|
          PRIVATE_HEADER|PUBLIC_HEADER|RESOURCE]
        [DESTINATION <dir>]
        [PERMISSIONS permissions...]
        [CONFIGURATIONS [Debug|Release|...]]
        [COMPONENT <component>]
        [OPTIONAL] [EXCLUDE_FROM_ALL]
        [NAMELINK_ONLY|NAMELINK_SKIP]
        ] [...]
        [INCLUDES DESTINATION [<dir> ...]]
        )
```

11.2.6 Multiple Forms

```
string(SUBSTRING <string> <begin> <length> <output variable>)
string(STRIP <string> <output variable>)
string(GENEX_STRIP <input string> <output variable>)
string(COMPARE LESS <string1> <string2> <output variable>)
```

11.3 Conclusion

After implementing a prototype parser and testing it on some of the above cases it is clear that the help text is not very consistent and is likely to be very challenging to get an implementation that works reliably and knows when it fails. For example:

```
add_custom_command(TARGET <target>
                   PRE_BUILD | PRE_LINK | POST_BUILD
                   COMMAND command1 [ARGS] [args1...]
                   [COMMAND command2 [ARGS] [args2...] ...]
                   [BYPRODUCTS [files...]]
                   [WORKING_DIRECTORY dir]
                   [COMMENT comment]
                   [VERBATIM] [USES_TERMINAL])
```

In this form of the command, the *PRE_BUILD* *PRE_LINK* or *POST_BUILD* argument is required. Normally it seems like they would put this in angle brackets as *<PRE_BUILD|PRE_LINK|POST_BUILD>* but they do not. So it's ambiguous where the pipes are splitting and what the groups are.

12.1 General Rules

1. Please use `pylint` and `flake8` to check your code for lint. There are config files in the repo.
2. There is a `python unittest` suite in `cmakelangtests.py`. Run with `python -Bm cmakelangtests` (ensure modified code is on the `python` path). Alternatively you can use `cmake` (`make test`, `ninja test`, etc) or `bazel` (`bazel test ...`).
3. There's an `autopep8` config file in the repo as well. Feel free to use that to format the code. Note that `autopep8` and `pylint` disagree in a few places so using `autopep8` may require some manual edits afterward.

12.2 Build Systems

You don't need to "build" `cmake-format`, but there are `cmake` and `bazel` build rules that you can use if you find it convenient. For the most part your contribution is in good shape if the `test` and `lint` (`cmake`) build targets pass or, equivalently, if `bazel test ...` passes. If you add new files to the repository, please update the corresponding `CMakeLists.txt` and `BUILD` files to keep the lint and test configurations up to date.

12.3 Sidecar Tests

Whether or not to write your tests in `cmake` or in `python` will depend largely on the test. If you simply want to assert that a particular snippet of code is formatted in a specific way, writing the test in `cmake` is most natural. If any logic is needed, then writing in the body of a `python` function makes the most sense.

Test written in `cmake` are stored in `.cmake` sidecar files associated with `python unittest` cases (see `command_tests/*`).

The format of these tests are very simple. The test begins with a line comment in the form of:

```
# test: <test-name>
```

And ends with the start of the next test, the end of the file, or a line comment in the form of:

```
# end-test
```

If non-default configuration options are required, or if you would like to assert a lex, parse, or layout result, then you can specify that in an optional bracket comment immediately following the `# test: sentinel`. The bracket comment must begin and end on it's own line, such as:

```
# [= [  
    line_width = 10  
]=]
```

The content of the comment is parsed as python and variables are interpreted as configuration variables, except for the following:

- `expect_lex` - a list of lexer tokens indicated the expected lex result
- `expect_parse` - a tree of parse node names indicated the expected parse tree structure
- `expect_layout` - a tree of layout node names and geometries indicated the expected layout result.

A test called `test_<test-name>` will be generated at runtime. The test will involve `cmake-format` formatting the code snippet using the default configuration, and asserting that the output matches the input.

12.4 Debugging

12.4.1 Formatting

For the most part, `cmake-format` ignores white-space when it parses the list file into the parse tree so most of the formatting tests can be restricted to “idempotency” tests. In other words, you write down the listfile code in the format you expect and if `cmake-format` doesn't change it, the test passes.

12.4.2 Lexing, Parsing, Layout

If you suspect a problem with the lexing, parsing, or layout algorithms, try to create a minimal working example of the problem, and use the `--dump [lex|parse|layout]` command line option to inspect the output of the different phases.

Once you've identified the problem, the best thing to do is create a test asserting an expected output at the problematic phase. You can start by asserting an empty output. For example, something like:

```
# test: debug_my_case  
# [= [  
    expect_lex = []  
]=]  
if(something)  
    your_cmake_code_here(foo bar baz)  
else()
```

The test will fail, but the error message will print out the actual result. In the example above:

```
Second list contains 19 additional elements.
First extra element 0:
TokenType.WORD
```

```
- []
+ [TokenType.WORD,
+   TokenType.LEFT_PAREN,
+   TokenType.WORD,
+   TokenType.RIGHT_PAREN,
+   TokenType.NEWLINE,
+   TokenType.WHITESPACE,
+   TokenType.WORD,
+   TokenType.LEFT_PAREN,
+   TokenType.WORD,
+   TokenType.WHITESPACE,
+   TokenType.WORD,
+   TokenType.WHITESPACE,
+   TokenType.WORD,
+   TokenType.RIGHT_PAREN,
+   TokenType.NEWLINE,
+   TokenType.WORD,
+   TokenType.LEFT_PAREN,
+   TokenType.RIGHT_PAREN,
+   TokenType.NEWLINE]
```

You can copy-paste the actual output as the expected output as a starting point for your test. You can modify the “expected” specification to match what the output *should* be. Then, as you iterate, you can use the test to know when you’ve fixed the problem.

12.5 Pull Requests

Feel free to make a pull request on github, though please take note of the following rules and guidelines. These rules are enforced through the travis CI builds so if travis passes your submission is probably in good shape.

12.5.1 Squash your feature

Please squash your changes when issuing a pull request so that the request is for a single commit. This helps us move the patch from the public github mirror into the upstream respository. When updating your request, please squash additional commits (you will likely need to force-push to your feature branch).

12.5.2 Rebase before submit

Please rebase your patch on the current HEAD before submitting the pull request. This helps us to keep a tidy history. When we merge your commit we don’t want to create graph connections across long regions of the git history. Travis will fail any pull request which is more than 10 commits behind the HEAD.

12.5.3 Sign your commit

When making a pull request, please sign the commit (use `git commit -S`).

12.5.4 Sign the copyright assignment

Please sign the copyright assignment agreement (details below) using the same PGP key you use to sign the commit, and please ensure that the key is available on the popular keyservers. Travis will fetch it from <https://keyserver.ubuntu.com>

12.6 Copyright Assignment

To sign the copyright assignment agreement the quick way, run:

```
python -Bm cmakelang.contrib.sign_ca
```

from the root of the repository.

For the long way, please follow this process:

1. Copy the file `cmakelang/contrib/individual_ca.txt` to some working directory as, e.g., `cmake-format-ca.txt.in`.
2. Replace the template strings at the bottom with your actual name and email address.
3. Sign the document with e.g.:

```
gpg --output cmake-format-ca.txt --clearsign cmake-format-ca.txt.in``
```

Please be sure to use the same pgp key that you'll be using to sign your commits.

4. Copy the ascii-armored signature packet at the bottom of the signed document and paste it into `cmakelang/contrib/signature_db.json`. Include this change in your first pull request.

12.7 Un-Assigned contributions

In general, copyright for contributions should be assigned to the project. This should keep everything on the level should we find the need to offer `cmake-format` though additional licenses in the future.

If you'd like to make a significant contribution to `cmake-format` but don't agree to the terms of the copyright assignment please contact us to set up an alternate agreement. Otherwise, please consider filing a feature-request for changes you would like to see implemented.

This page documents details of the `cmake-format` release process.

13.1 Update master

1. Push release candidate to the staging branch
2. travis will build and test the commit and then push the `pseudo-staging` tag
3. travis will build and test the commit, and will also create a new `psuedo-staging` release ([see here](#)), pushing the binary artifacts (wheel, vsix, etc). Travis will also push a new commit to the `cmake-format-rtd` repository ([link](#)) under the `staging` branch.
4. read-the-docs will build the documentation under the `staging` version, with [status here](#) and [result here](#)
5. Download and install the python wheel and vsix packages. Test them manually to make sure everything looks good.
6. Push the same commit with that modification to the `master` branch. The same pipeline as above will execute. Double check there are no errors

13.2 Cut a Release

7. Add one commit on top of the `HEAD` of master, removing the `dev#` version suffix. Push to a tag.
8. The same pipeline above will execute, but this time the artifacts will belong to the real realease number. The release message text will be taken from the release notes document.
9. Download the python source and wheel distributions and vsix packages.
10. Push the python packages to test.pypi.org with:

```
twine upload -r test cmake-format.*
```

11. Push the python packages to `pypi.org` with `twine upload cmake-format.*`

12. Push the vscode package with:

```
vsce publish --baseImagesUrl \  
https://raw.githubusercontent.com/cheshirekow/cmakelang/master/cmakelang/vscode_  
↪extension
```

Details of changes can be found in the changelog, but this file will contain some high level notes and highlights from each release.

14.1 v0.6 series

14.1.1 v0.6.13

This is a hotfix on v0.6.12. The python distribution package was missing some modules.

14.1.2 v0.6.12

This release includes mostly internal housekeeping. The code organization was overhauled to better represent the division between different components. The `cmake_format` package has been replaced by `cmakelang`, with `format` now a subpackage. All the first class tools are now subpackages of `cmakelang`. For now, I'll leave the github repository at `cmake_format` but there's a good chance I'll move it to `cmakelang` in the future. Big refactors like this have a tendency to expose gaps in coverage so please report any breakages you observe.

In addition, the configuration now includes options for using tab characters in listfiles (though, I'm not sure who in the right mind would choose to do so). If enabled, the formatter will translate indentations from spaces to tabs, and the linter will enforce a consistent tab policy.

This release also includes a couple of minor bug fixes. See the release notes for more details.

14.1.3 v0.6.11

This release adds `argcomplete` handling to enable automatic shell completion to `cmake-format` and `cmake-lint`. `argcomplete` is not an installation dependency so if you wish to enable completion please install `argcomplete` (e.g. via `pip`) and then activate it (see the documentation for `argcomplete`).

The visual studio code extension now supports variable substitution for things like `${workspaceRoot}` and `${workspaceFolder}` in the `args` and `cwd` configuration options.

There is a new configuration option to `disable` formatting. This can be specified in a config file to conveniently no-op formatting within a subdirectory (such as third-party source code) of a project.

14.1.4 v0.6.10

This release fixes a number of issues with `cmake-lint` and activates `cmake-lint` as part of the lint build step in CI for this project and the upstream repository. There is still a lot of work to do on `cmake-lint` but at this point it is in a less experimental state and I am sufficiently confident in it enough to suggest that you start using it. Feel free to report any issues you encounter with it.

This release also includes some cleanup work under the hood of `cmake-format` and the parsing code. Most notably, the command specifications for all of the `cmake` functions and macros defined in standard modules have been generated using `genparsers` and are now included by default. I have not audited all of them so the detected specifications are probably not all correct. Please let me know if you observe any problems with them.

14.1.5 v0.6.9

The parser now performs token look-ahead when parsing a comment within a statement. This allows it to determine whether a comment belongs to the current semantic node or one higher up in the tree (previously it would assign all comments to the most recent semantic node). This should prevent some unusual indentation of comments within deep statements.

Some `cmake-lint` crashes have been fixed and the test coverage has increased significantly. There are still some outstanding issues but it should crash less frequently and with more helpful information.

Detailed documentation for configuration options is now generated automatically, including default value, command line syntax, and example configuration file entry.

14.1.6 v0.6.8

There is now an embedded database of known variables and properties. `cmake-lint` uses this database to implement checks on assignment/use of variables that are likely to be typos of a builtin variable name. There are also two new configuration options `vartags` and `proptags` that can be used to affect how the parser and formatter treat certain variables and properties.

Line comments within a statement are now consumed the same as line comments at block-scope. This means that your multiline mid-statement comments will be reflowed whereas they would previously have been left alone.

The CI Build has gotten a little more complicated. Generated documentation sources are no longer committed to the repository. Instead, they are pushed to a separate staging repository from which the read-the-docs pages are built.

14.1.7 v0.6.7

With this release, the `specification` format for custom commands has been updated to enable a number of new features. Positional argument groups now support “tags” which can be used to influence the formatting for some special cases. The format now also supports multiple positional argument groups. Lastly, there is a new **experimental** tool `cmake-genparsers` which can automatically generate parser specifications from your custom commands that use the standard `cmake_parse_arguments`.

There is a new configuration option `max_rows_cmdline` which applies only to shell commands and determines when a shell command should nest under its keyword argument.

14.1.8 v0.6.6

The configuration datastructures have been overhauled and configuration options are now separated into different groupings based on which part of the processing pipeline they are relevant to. Legacy configuration files (without sections) are still supported, though they may be deprecated in the future. `cmake-format` can update your configuration file for you with the following command:

There is a new configuration option `explicit_trailing_pattern` which can be used to define a particular character sequence used by comments that are explicitly matched as trailing comments of an argument or statement. See [the docs](#) for more information.

Configuration files can now include additional configuration files. This might help keep configurations organized if you are maintaining a database of custom command definitions.

14.1.9 v0.6.5

This is largely a maintenance release, implementing explicit parse logic for all `cmake` commands that don't already have parsers. One additional configuration option is added allowing `cmake-lint` to globally ignore specific lint ids.

14.1.10 v0.6.4

This release includes implementations for many more lint checkers. Under the hood there was a pretty significant refactor of the parser, though none of the parse logic has changed. The refactor was primarily to split up the very large `parser` module, and to make it easier to access qualifiers of the parse tree during lint checks.

You can see a running list of all the implemented checkers at [the docs](#).

14.1.11 v0.6.3

This release finally includes some progress on a long-standing goal: a `cmake-linter` built on the same foundation as the formatter. As of this release The `cmake-format` python package now comes with both the `cmake-format` and `cmake-lint` programs. The linter is still in a relatively early state and lacks many features, but should continue to grow with the formatter in future releases.

Along with the new linter, this release also includes some reorganization of the documentation in order to more clearly separate information about the different programs that are distributed from this repository.

14.1.12 v0.6.2

This is a maintenance release. Some additional command parsers have moved out of the standard parse model improving the parse of these commands. This release also includes some groundwork scripts to parse the usage strings in the `cmake` help text. Additionally:

- `--in-place` will preserve file mode
- The new `--check` command line option will not format the file, but exit with non-zero status if any changes would be made
- The new `--require-valid-layout` option will exit with non-zero status if an admissible layout is not found.

14.1.13 v0.6.1

This is primarily a documentation update. Some of the testing infrastructure has changed but no user-facing code has been modified.

14.1.14 v0.6.0

This release includes a significant refactor of the formatting logic. Details of the new algorithm are described in the [documentation](#). As a result of the algorithm changes, some config options have changed too. The following config options are removed:

- `max_subargs_per_line` (see `max_pargs_hwrap`)
- `nest_threshold` (see `min_prefix_chars`)
- `algorithm_order` (see `layout_passes`)

And the following config options have been added:

- `max_subgroups_hwrap`
- `max_pargs_hwrap`
- `dangle_align`
- `min_prefix_chars`
- `max_prefix_chars`
- `max_lines_hwrap`
- `layout_passes`
- `enable_sort`

Also as a result of the algorithm changes, the default layout has changed. By default, `cmake-format` will now prefer to nest long lists rather than aligning them to the opening parenthesis of a statement. Also, due to the new configuration options, the output of `cmake-format` is likely to be different with your current configs.

Additionally, `cmake-format` will now tend to prefer a normal “horizontal” wrap for relatively long lists of positional arguments (e.g. source files in `add_library`) whereas it would previously prefer a vertical layout (one-entry per line). This is a consequence of an ambiguity between which positional arguments should be vertical versus which should be wrapped. Two planned features (layout tags and positional semantics) should help to provide enough control to get the layout you want in these lists.

I acknowledge that it is not ideal for formatting to change between releases but this is an unfortunate inevitability at this stage of development. The changes in this release eliminate a number of inconsistencies and also adds the groundwork for future planned features and options. Hopefully we are getting close to a stable state and a 1.0 release.

14.2 v0.5 series

14.2.1 v0.5.5

This is a maintenance release fixing a few minor bugs and enhancements. One new feature is that the `--config` command line option now accepts a list of config files, which should allow for including multiple databases of command specifications — v0.5.4 —

This is a maintenance release fixing a couple of bugs and adding some missing documentation. One notable feature added is that, during in-place formatting, if the file content is unchanged `cmake-format` will no-longer write the file.

14.2.2 v0.5.3

This hotfix release fixes a bug that would crash `cmake-format` if no configuration file was present. It also includes some small under-the-hood changes in preparation for an overhaul of the formatting logic.

14.2.3 v0.5.2

This release fixes a few bugs and does some internal prep work for upcoming format algorithm changes. The documentation on the format algorithm is a little ahead of the code state in this release. Also, the documentation theme has changed to something based on read-the-docs (I hope you like it).

- Add missing forms of `add_library()` and `add_executable()`
- `--autosort` now defaults to `False` (it can be somewhat suprising) and it doesn't always get it right.
- Configuration options in `--help` and in the example configurations from `--dump-config` are now split into hopefully meaningful sections.
- `cmake-format` no longer tries to infer “keywords” or “flags” from `COMMAND` strings. This matching wasn't good enough as there is way too much variance in how programs design their command line options.

14.2.4 v0.5.1

The 0.5.0 release involved some pretty big changes to the parsing engine and introduced a new format algorithm. These two things combined unfortunately lead to a lot of new bugs. The full battery of pre-release tests wasn't run and so a lot of those issues popped up after release. Hopefully most of those are squashed in this release.

- Fixed lots of bugs introduced in 0.5.0
- `cmake-format` has a channel on discord now. Come chat about it at <https://discord.gg/NgjwyPy>

14.2.5 v0.5.0

- Overhauled the parser logic enabling arbitrary implementations of statement parsers. The generic statement parser is now implemented by the `standard_parse` function (or the `StandardParser` functor, which is used to load legacy `additional_commands`).
- New custom parser logic for deep `cmake` statements such as:
 - `install`
 - `file`
 - `ExternalProject_XXX`
 - `FetchContent_XXX`
- `cmake-format` can now sort your argument lists for you (such as lists of files). This enabled with the `autosort` config option. Some argument lists are inherently sortable (e.g. the list of sources supplied to `add_library` or `add_executable`). Other commands (e.g. `set()` which cannot be inferred sortable can be explicitly tagged using a comment at the beginning of the list. See the README for more information.

- A consequence of the above is that the parse tree for `set()` has changed, and so its default formatting in many cases has also changed. You can restore the old behavior by adding the following to your config:

```
additional_commands = {  
    "set": {  
        "flags": ["FORCE", "PARENT_SCOPE"],  
        "kwargs": {  
            "CACHE": "*"   
        }  
    }  
}
```

- The default command case has changed from `lower` to `canonical` (which is a new option). In most cases this is the same as `lower` but for some standard, non-builtin commands the canonical spelling is CamelCase (i.e. `ExternalProject_Add`).
- There is a new `cmake-annotate` program distributed with the package. It can generate semantic HTML renderings of your listfiles (see the documentation for details).

14.3 v0.4 series

14.3.1 v0.4.5

- Add travis CI configuration for public github repo

14.3.2 v0.4.4

- Add the ability to dump out markup parse lists for debugging.
- Add the ability to dump out a semantic HTML markup of a listfile, allowing for easy server-side semantic highlighting of documentation pages. See [cmake-annotate](#).

14.3.3 v0.4.2

- Added the brand new Visual Studio Code extension, which can be found in the `vscode` marketplace! You can now use `cmake-format` to “Format Document” in `vscode`.
- Some new configuration options to allow user-specified literal fences and rulers in comment markup.
- New configuration options to preserve literal comment blocks at the start of your listfiles (intended for copyright statements), as well as to disable comment reflow altogether.
- Fixed some bugs and improved some error messages

Enjoy!

15.1 v0.6 series

15.1.1 v0.6.13

- Fix subpackages missing from python distribution

15.1.2 v0.6.12

- Fix `--check` missing early return.
- Fix wrong base class for `TupleParser`
- Add `PATTERN` as allowed duplicate keyword
- Enable `cmake-lint: disable=` within a statement
- Add `cmake` lint checks on tab policy and indentation size
- Closes: [#31](#): Allow use of tabs instead of spaces
- Closes: [#197](#): [\[C0103\]](#) Invalid `CACHE` variable
- Closes: [#205](#): Multiple config files aren't merged...
- Closes: [#208](#): Duplicate `PATTERN` in `install(...`
- Closes: [#210](#): Usage: banning tabs and enforcing the spaces per tab
- Closes: [#216](#): `--check` mode dumps entire file since 0.6.11
- Closes: [#217](#): strange formatting for `set_target_properties`

15.1.3 v0.6.11

- Fix tag handling in release pipeline
- Fix positional specification removed from global configuration on first parse of legacy commands
- Add argcomplete to frontend commands enabling bash completion
- Parse template listfiles that contain `@atword@` tokens at the statement level (e.g. `@PACKAGE_INIT@`).
- Simplify path specification for `always_wrap` to omit `BodyNode`, and number `PargGroupNode[ # ]`.
- Fix spelling configuration option not plumbed through to the formatter
- Add a config option to disable formatting (e.g. in a subdirectory)
- Add documentation for `cmake-lint` disable
- Closes: [#109](#): Formatting of files containing `@VARIABLE@` fails
- Closes: [#177](#): vscode extension: add support for variable substitution ...
- Closes: [#179](#): Official docker image
- Closes: [#180](#): ... regarding `always_wrap`
- Closes: [#191](#): Inconsistent formatting for ...
- Closes: [#202](#): Spelling not accounted for
- Closes: [#207](#): Add `DisableFormat` option
- Closes: [#211](#): Add documentation for “`cmake-lint:disable`”
- Closes: [f0fcbce](#)

15.1.4 v0.6.10

- Fix some bugs in genparsers
- Fix some typos in environment handling in extension
- Fix `cmake-lint` can't `-dump-config`
- Fix default max statement spacing was 1 instead of 2
- Cleanup legacy command specifications
- Autogenerate command specifications for standard modules
- Don't mark lint for `add_custom_target()` missing `COMMAND`
- Add missing annotate resources to distribution package
- Don't break long words when reflowing comment text
- Print violated regex for C0103 lint
- Make line number consistently start from “1” between tokenizer and checker
- Fix `Scope.PARENT` is same enum value as `scope.INTERNAL`
- Skip travis deploy stage on pull request
- Move `commands.py` into `parse_funs/standard_funs.py`
- replace duplicates of `parse_db` update from `standard_funs`

- get rid of root makefile
- document the release process
- refactor basic_checker module into a class where common function parameters are now member state.
- analyze and document variable naming conventions
- add a pattern for function/macro argument names
- implement W0106 looks like a variable reference missing a brace
- fix name checks shouldn't be applied to variable references
- enable cmake-lint during build/CI
- Closes: #170: Comment is wrong
- Closes: #171: Crash when running `cmake-lint --dump-config`
- Closes: #172: Possibly false positives for too many newlines
- Closes: #173: `find_package_handle_standard_args()`
- Closes: #176: `cmake-lint: [C0113]` is issued for `COMMAND` in `add_custom_target()`
- Closes: #181: `cmake-annotate` is missing `css` file
- Closes: #182: line break in url
- Closes: #183: `cmake-lint: add exact configuration item/value to output`
- Closes: #184: Trailing whitespace reported on wrong line
- Closes: #185: `cmake-lint: set with PARENT_SCOPE is not INTERNAL`
- Closes: #187: Fixed typos and bugs in `vscode` extension
- Closes: 358e95c, 376422c, 5258b1b, 97f7956, d85b7c7, e03ec57, f0fcbce,

15.1.5 v0.6.9

- fix RTD push on Travis if the pseudo-release is already up-to-date
- added pattern for at-words to the lexer and new token type
- fix custom parsers didn't set lint spec for `PositionalGroupNode`
- don't pedantically error out on empty JSON config file
- parser can comprehend comments belonging to higher than the current depth in the semantic tree.
- cleanup README, move some stuff to documentation pointers
- generate the config options details page rather than hand writing it
- Closes: #109: Formatting of files containing `@VARIABLE@` fails
- Closes: #122: `parse_positionals` consumes non-related comments after code
- Closes: #168: `cmake-lint` crashes on `add_library` function
- Closes: 031922e, 5bcc447, c07a668, efba824, 7eb2cb6

15.1.6 v0.6.8

- Reduce packaging dependency version numbers
- Add build rules to generate variable and property pattern lists
- Implement lint checks on assignment/use of variables that are “close” to builtins except for case.
- Move first_token from configuration object into format context
- Add line, col info to lex error message
- Fix wrong root parser for FetchContent_MakeAvailable
- Fix missing support for string integer npargs
- Fix missing spec for derived classes of PositionalGroupNode
- Fix on/off switch doesn’t work inside a statement
- Fix extraneous whitespace inserted before line comment in some statements
- Add more helpful error message on failed configfile parse
- Move documentation build to build time and push documentation artifacts to an artifact repository
- Closes #162: cmake-lint crashes when evaluating math
- Closes #163: cmake-lint crashes when using VERBATIM in add_custom_target
- Closes #164: Internal error FetchContent_MakeAvailable
- Closes: 000bf9a, 6e4ef70, 85a3985, 9a3afa6, c297b3d, cf4570e

15.1.7 v0.6.7

- Add missing dependency on six
- Update pylint, flake8 used in CI
- Remove spurious config warning for some unfiltered command line options
- Add tags field to positional argument groups. Assign “file-list” tag to file lists from add_library and add_executable
- Remove “sortable” flag from root TreeNode class
- Custom commands can specify if a positional group is a command line
- Custom commands can specify multiple positional groups
- max_pargs_hwrap does not apply to cmdline groups
- Remove stale members from TreeNode
- Format extension.ts with two spaces
- Create a tool to generate parsers from cmake_parse_args
- Closes #139: Disable wrap for custom functions
- Closes #159: Missing dependency on six
- Closes: 6ef7d0d, 9669d02, cc60267, cf7ac49, cfa3c02, eefbde3, e75513a,
- Closes: f704714

15.1.8 v0.6.6

- Fix greedy match for bracket comments
- Implement some more readable error messages
- Add source support for sidecar tests
- Overhaul the configuration data structures, dividing configuration up among different classes.
- Remove configuration fields from config object `__init__`
- Add dump-config options to exclude helptext or defaults
- Implement explicit trailing comments
- Implement “include” from config files
- Move logging init into main() functions
- Closes [#156](#): Linter exception when parsing certain multiline comments
- Closes: [19baaf5](#), [200a6ed](#), [3435d8a](#), [4e6ca84](#), [6397d42](#), [9fbeebee](#), [b7fb891](#), [f097478](#)

15.1.9 v0.6.5

- Fix bullet formatting in README
- Capture some input exceptions and print a more friendly error message
- Fix partialmethod docstrings in command tests
- Add a more detailed configuration description and samples
- Get rid of “extra” dictionary hack to get valid reflow bit out of `process_file` in `__main__.py`.
- Implement disabled lint codes config option
- Add preamble and summary to cmake-lint output
- Add test to ensure all cmake commands are in the database
- Implement all commands available in cmake 3.10.2
- Closes [#154](#): cmake-lint: Human readable errors
- Closes: [06918d6](#), [0b6db3a](#), [26582bc](#), [7039c5c](#), [c8d18f1](#), [ea5583e](#), [eb4fb01](#),
- Closes: [5abae5c](#)

15.1.10 v0.6.4

- Split `parser.py` module into `parse/` sub package.
- Implement derived classes of `TreeNode` for for many parsers
- Refactor parse functions into class members of the appropriate `TreeNode` derived class
- Add lint checkers for: C0103, C0113, C0202, C0305, E0103, E0104, E0108, E0109, E1120, E1122, W0101
- Fix wrong token pattern for unquoted literal was including literal tabs and newlines (not literal “t” and “n”).
- Closes [#153](#): Spaces added to generator expressions

15.1.11 v0.6.3

- Add `ctest-to` program
- Add `cmake-lint` program
- Separate documentation by program
- Add some more detailed configuration documentation
- Make some of the config logic generic and push into a base class
- Some groundwork for cleaning up the config into different sections
- Fix `externalproject_add_stepdependencies`
- Closes [#152](#): AssertionError on `externalproject_add_stepdependencies`

15.1.12 v0.6.2

- some initial work on `cmake helptext/usage` parser
- fix `set_target_properties`
- fix `TOUCH_NOCREATE`
- `copymode` during `-in-place`
- add `-check` command
- suppress spurious warnings in tests
- create `add_custom_target` parser
- update `add_custom_command` parser with different forms
- fix target form of `install` command
- implement `require-valid-layout` and add tests
- `sidecar` tests don't need a companion `pyfile`
- fix some typos in documentation
- Closes [#133](#): Better handling of un-wrappable, too-long lines
- Closes [#134](#): Wrong formatting of `install(TARGETS)`
- Closes [#140](#): add `USES_TERMINAL` to `kwargs`
- Closes [#142](#): Add a `-check` option that doesn't write the files
- Closes [#143](#): Broken file attributes after formatting
- Closes [#144](#): Wrong warning about "`file(TOUCH_NOCREATE ...)`"
- Closes [#145](#): Bad formatting for `set_target_properties`
- Closes [#147](#): `foreach` format
- Closes [#150](#): Contributing documentation
- Closes [#151](#): `README.rst`: fix two typos

15.1.13 v0.6.1

- consolidate `--config-file` command line flag variants
- add documentation on integration with `pre-commit`
- add documentation on sidecar tests
- simplify the tag format for sidecar tests
- add support of config options and lex/parse/layout assertions in sidecar tests
- add documentation on debugging with tests
- add tests to validate pull requests
- move most tests into sidecar files

15.1.14 v0.6.0

Significant refactor of the formatting logic.

- Move `format_tests` into `command_tests.misc_tests`
- Prototype sidecar tests for easier readability/maintainability
- `ArgGroupNodes` gain representation in the layout tree
- Get rid of `WrapAlgo`
- Eliminate vertical/nest as separate decisions. Nesting is just the wrap decision for `StatementNode` and `KwargNode` whereas vertical is the wrap decision for `PargGroupNode` and `ArgGroupNode`.
- Replace `algorithm_order` with `_layout_passes`
- Get rid of `default_accept_layout` and move logic into a member function
- Move configuration and `node_path` into new `StackContext`
- Stricter valid-child-set for most layout nodes

15.2 v0.5 series

15.2.1 v0.5.5

- Python config files now have `__file__` set in the global namespace
- Add parse support for BYPRODUCTS in `add_custom_command`
- Modify vscode extension cwd to better support subtree configuration files
- Fix vscode extension args type configuration
- Support multiple config files
- Closes #121: Support BYPRODUCTS
- Closes #123: Allow multiple config files
- Closes #125: Swap ordering of cwd location in vscode extension
- Closes #128: Include LICENSE.txt in sdist and wheel
- Closes #129: `cmakeFormat.args` in `settings.json` yields Incorrect type

- Closes #131: cmakeFormat.args is an array of items of type string

15.2.2 v0.5.4

- Don't write un-changed file content when doing in-place formatting
- Fix windows line-endings dropped during read
- Add documentation on how to add custom commands
- Fix yaml-loader returns None instead of empty dictionary for an empty yaml config file.
- Closes #114: Example of adding custom cmake functions/macros
- Closes #117: Fix handling of -dump-config with empty existing yaml config
- Closes #118: Avoid writing outfile unnecessarily
- Closes #119: Fix missing newline argument
- Closes #120: auto-line ending option not working correctly under Windows

15.2.3 v0.5.3

- add some configuration options for next format Refactor
- update documentation source generator scripts and run to get updated dynamic doc texts
- add a couple more case studies
- split reflow methods into smaller methods per case
- fix os.expanduser on None
- Closes #115: crash when no config file

15.2.4 v0.5.2

- add parsers for different forms of `add_library()` and `add_executable()`
- move `add_library`, `add_executable()` and `install()` parsers to their own modules
- don't infer sortability in `add_library` or `add_executable()` if the discriminator token might be a cmake variable hiding the discriminator spelling
- Split configuration options into different groups during dump and -help
- Refactor long `_reflow()` implementations, splitting into methods for the different wrap cases. This is in preparation for the next rev of the format algorithm.
- Add documentation on the format algorithm and some case studies.
- Autosort defaults to `False`
- Changed documentation theme to something based on rtd
- Get rid of `COMMAND` kwarg specialization
- Closes #111: Formatting breaks `add_library`
- Closes #112: `expanduser` on `configfile_path`

15.2.5 v0.5.1

- Fix empty kwarg can yield a parg group node with only whitespace children
- Fix `file(READ ...)` and `file(STRINGS ...)` parser kwargs using set syntax instead of dict syntax
- Fix aggressive positional parser within conditional parser
- Fix missing `endif`, `endwhile` in `parsemap`
- Split parse functions out into separate modules for better organization
- Add more sanity tests for `file(...)`.
- Remove README from online docs, replace with expanded documentation for each README section
- Restore ability to accept paren-group in arbitrary parg-group
- Fix missing tests on travis
- Fix new tests using unicode literals (affects python2)
- Fix command parser after `-`
- Closes #104: Extra space for export targets
- Closes #106: Formatting of `file(READ)` fails
- Closes #107: multiline `cmake` commands
- Closes #108: Formatting of `file(String)` fails
- Closes #110: Formatting of Nested Expressions Fails

15.2.6 v0.5.0

- Implement canonical command case
- Canonicalize capitalization of keys in `cmdspec`
- Add README documentation regarding fences and enable/disable
- Statement parsers are now generic functions. Old standard parser remains for most statements, but some statements now have custom parsers.
- Implement deeper parse logic for `install()` and `file()` commands, improving the formatting of these statements.
- Implement input/output encoding configuration parameters
- Implement hashruler markup logic and preserve hashrulers if markup is disable or if configured to do so.
- Implement autosort and sortable tagging
- Separate `cmake-annotate` frontend
- Provider a `Loader=` to `yaml load()`
- Fix python3 lint
- Fix bad lexing of make-style variables
- Fix multiple hash chars `rstrip()`ed from comments
- Closes #62: Possible improvement on formatting “file”
- Closes #75: configurable positioning of flags

- Closes #87: Hash-rulers are stripped when markup disabled
- Closes #91: Add missing keyword arguments to project command
- Closes #95: added argument `--encoding` to allow for non-utf8
- Closes #98: Fix kwargs/flag index for non-lowercase functions
- Closes #100: Extra linebreak inserted when `'$'` encountered
- Closes #101: Provide a Loader to `yaml.load`
- Closes #102: fences does not work as expected

15.3 v0.4 series

15.3.1 v0.4.5

- Fix testing instructions in README
- Fix dump-config instructions in README
- Remove numpy dependency
- Add travis CI configuration
- Fix some issues with lint under python3
- Closes #40
- Closes #76
- Closes #77
- Closes #80
- Fixes #82: Keyword + long coment + long argument asserts

15.3.2 v0.4.4

- Fix bug where rulers wouldn't break bulleted lists in comment markup
- Add missing flags COMPONENT and CONFIGURATIONS to command spec
- add `--dump markup` to dump the markup parse tree for debugging comment formatting behavior
- fix invalid `NoneType` value for `--literal-comment-pattern`
- shebang is preserved if present (without additional options)
- fix trailing comment of kwarg group consumes rparen
- add test to verify correct consumption of args matching outer kwargs
- add new quoted assignment pattern to lexer for cases like quoted compile definitions
- add `--dump html-stub` and `--dump html-page` listfile renderers
- Fixes #56: ignores boolean configuration values
- Closes #66: Positional argument of keyword incorrectly matched as keyword of containing command
- Resolves #73: Control of macro/function renaming
- Fixes #74: shebang in cmake scripts

- Fixes #79: BOM (Byte-order-mark) crashes parser
- Closes #81: Fix comment handling in kwarg group
- Fixes #85: commands: find_package broken
- Fixes #86: Breaking in Quotes

15.3.3 v0.4.3

- dump_config now dumps the active config, including loaded from file or modified by command line
- use cmake macros for cleaner listfiles
- fix argparse defaults override config file settings for boolean args

Closed issues:

- Fixes #70: ignores boolean configuration values

15.3.4 v0.4.2

- Add visual studio code extension
- Add algorithm order config option
- Add user specified fence regex config option
- Add user specified ruler regex config option
- Add config option to disable comment formatting altogether
- Fix get_config bug in __main__
- Fix missing elseif command specification
- Fix missing elseif/else paren spacing when specified
- Add enable_markup config option
- Fix kwargstack early breaking in conditionals
- Add some notes for developers.
- Add warning if formatter is inactive at the end of a print
- Add config options to preserve first comment or any matching a regex

Closed issues:

- Fixes #34: if conditions with many elements
- Closes #35: break_before_args
- Implements #42: user specified string for fencing
- Implements #43: allow custom string for rulers
- Fixes #45: config file not loaded properly
- Fixes #51: competing heuristics for 2+ argument statements
- Implements #60: option to not reflow initial comment block
- Implements #61: add non-builtin commands
- Fixes #63: elseif like if

- Implements #65: warn if off doesn't have corresponding on
- Closes #67: global option to not format comments
- Fixes #68: seperate-ctrl-name-with-space

15.3.5 v0.4.1

- Add missing numpy dependency to setup.py
- Fix arg comments dont force vpack
- Fix arg comments dont force dangle parenthesis
- Add some missing function specifications

Closed issues:

- Fixes #53: add numpy as required
- Closes #54: more cmake commands
- Fixes #55: function with interior comment
- Fixes #56: function with trailing comment
- Fixes #59: improve export

15.3.6 v0.4.0

- Overhaul parser into a cleaner single-pass implementation that generates a more complete representation of the syntax tree.
- Parser now recognizes arbitrary nested command specifications. Keyword argument groups are formatted like statements.
- Complete rewrite of formatter (see docs for design)
- Support line comments inside statements and argument groups
- Add some additional command specifications
- Add `--dump [lex|parse|layout] debug` commands
- `--dump-config` dumps the active configuration (after loading)
- Add keyword case correction
- Improve layout of complicated boolean expressions

Closed issues:

- Implements #10: treat COMPONENT keyword different
- Implements #37: `--dump-config` dumps current config
- Implements #39: always wrap for certain functions
- Fixes #46: leading comment in function body
- Fixes #47: function argument incorrectly appended
- Implements #48: improve install `target_*`
- Fixes #49: removes entire while() sections

- Fixes #50: indented comments appended to preceding line

15.4 v0.3 series

15.4.1 v0.3.6

- Implement “auto” line ending option #27
- Implement command casing #29
- Implement stdin as an input file #30

Closed issues:

15.4.2 v0.3.5

- Fix #28: lexing pattern for quoted strings with escaped quotes
- Add lex tests for quoted strings with escaped quotes
- Fix windows format test

Closed issues:

15.4.3 v0.3.4

- Don't use `tempfile.NamedTemporaryFile` because it has different (and, honestly, buggy behavior) compared to `codecs.open()` or `io.open()`
- Use `io.open()` instead of `codecs.open()`. I'm not sure why to prefer one over the other but since `io.open` is more or less required for printing to stdout I'll use `io.open` for everything
- Lexer consumes windows line endings as line endings
- Add inplace invocation test
- Add line ending configuration parameter
- Add configuration parameter command line documentation
- Add documentation to python config file dump output
- Strip trailing whitespace and normalize line endings in bracket comments

15.4.4 v0.3.3

- Convert all string literals in `format.py` to unicode literals
- Added python3 tests
- Attempt to deal with python2/python3 string differences by using `codecs` and `io` modules where appropriate. I probably got this wrong somewhere.
- Fix missing comma in config file matching

Closed issues:

- Implement #13: option to dangle parenthesis

- Fix #17: trailing comment stripped from commands with no arguments
- Fix #21: corruption upon trailing whitespace
- Fix #23: wrapping long arguments has some weird extra newline or missing indentation space.
- Fix #25: cannot invoke cmake-format with python3

15.4.5 v0.3.2

- Move configuration to it's own module
- Add lexer/parser support for bracket arguments and bracket comments
- Make `stable_wrap` work for any `prefix / subsequent_prefix`.
- Preserve scope-level bracket comments verbatim
- Add markup module with parse/format support for rudimentary markup in comments including nested bulleted and enumerated lists, and fenced blocks.
- Add pyyaml as an extra dependency in pip configuration

Closed issues:

- Fix #16: argparse defaults always override config

15.4.6 v0.3.1

- use `exec` instead of `execfile` for python3 compatibility

15.4.7 v0.3.0

- fix #2 : parser matching builtin logical expression names should not be case sensitive
- fix #3 : default code used to read `long_description` can't decode utf8
- implement #7 : add configuration option to separate control statement or function name from parenthesis
- implement #9 : allow configuration options specified from command line
- Add support for python as the configfile format
- Add `--dump-config` option
- Add support for "separator" lines in comments. Any line consisting of only five or more non-alphanum characters will be preserved verbatim.
- Improve python3 support by using `print_function`

Closed issues:

15.5 v0.2 series

15.5.1 v0.2.1

- fix bug in reflow if text goes to exactly the end of the line
- add python module documentation to sphinx autodoc

- make formatting of COMMANDs a bit more compact

15.5.2 v0.2.0

- add unit tests using python unit test framework
- accept configuration as yaml or json
- Implemented custom cmake AST parser, getting rid of dependency on cmlp
- Removed static global command configuration
- If no configuration file specified, search for a file based on the input file path.
- Moved code out of `__main__.py` and into modules
- More documentation and general cleanup
- Add `setup.py`
- Tested on a production codebase with 350+ listfiles and a manual scan of changes looked good, and the build seems to be healthy.

16.1 Module contents

Language tools for cmake

16.2 Submodules

16.3 `cmake_format.configuration` module

```
class cmakelang.configuration.Configuration (**kwargs)
    Bases: cmakelang.config_util.ConfigObject
    Various configuration options and parameters

encode
    Implements the descriptor interface for nested configuration objects.

format
    Implements the descriptor interface for nested configuration objects.

lint
    Implements the descriptor interface for nested configuration objects.

markup
    Implements the descriptor interface for nested configuration objects.

misc
    Implements the descriptor interface for nested configuration objects.

parse
    Implements the descriptor interface for nested configuration objects.
```

resolve_for_command(*command_name*, *config_key*, *default_value=None*)

Check for a per-command value or override of the given configuration key and return it if it exists. Otherwise return the global configuration value for that key.

class cmakelang.configuration.**EncodingConfig**(***kwargs*)

Bases: cmakelang.config_util.ConfigObject

Options affecting file encoding

emit_byteorder_mark = False

input_encoding = 'utf-8'

output_encoding = 'utf-8'

class cmakelang.configuration.**FormattingConfig**(***kwargs*)

Bases: cmakelang.config_util.ConfigObject

Options affecting formatting.

always_wrap = []

autosort = False

command_case = 'canonical'

dangle_align = 'prefix'

dangle_parens = False

disable = False

enable_sort = True

fractional_tab_policy = 'use-space'

keyword_case = 'unchanged'

layout_passes = {}

line_ending = 'unix'

line_width = 80

linewidth

max_lines_hwrap = 2

max_pargs_hwrap = 6

max_prefix_chars = 10

max_rows_cmdline = 2

max_subgroups_hwrap = 2

min_prefix_chars = 4

require_valid_layout = False

separate_ctrl_name_with_space = False

separate_fn_name_with_space = False

set_line_ending(*detected*)

tab_size = 2

use_tabchars = False

```

class cmakelang.configuration.LinterConfig(**kwargs)
    Bases: cmakelang.config_util.ConfigObject

    Options affecting the linter

    argument_var_pattern = '[a-z][a-z0-9_]+'
    disabled_codes = []
    function_pattern = '[0-9a-z_]+'
    global_var_pattern = '[A-Z][0-9A-Z_]+'
    internal_var_pattern = '_[A-Z][0-9A-Z_]+'
    keyword_pattern = '[A-Z][0-9A-Z_]+'
    local_var_pattern = '[a-z][a-z0-9_]+'
    macro_pattern = '[0-9A-Z_]+'
    max_arguments = 5
    max_branches = 12
    max_conditionals_custom_parser = 2
    max_localvars = 15
    max_returns = 6
    max_statement_spacing = 2
    max_statements = 50
    min_statement_spacing = 1
    private_var_pattern = '_[0-9a-z_]+'
    public_var_pattern = '[A-Z][0-9A-Z_]+'

class cmakelang.configuration.MarkupConfig(**kwargs)
    Bases: cmakelang.config_util.ConfigObject

    Options affecting comment reflow and formatting.

    bullet_char = '*'
    canonicalize_hashrulers = True
    enable_markup = True
    enum_char = '.'
    explicit_trailing_pattern = '#<'
    fence_pattern = '^\\s*([`~]{3}[`~]*) (.*)$'
    first_comment_is_literal = False
    hashruler_min_length = 10
    literal_comment_pattern = None
    ruler_pattern = '^\\s*[^\\w\\s]{3}.*[^\\w\\s]{3}$'

class cmakelang.configuration.MiscConfig(**kwargs)
    Bases: cmakelang.config_util.ConfigObject

    Miscellaneous configurations options.

```

```
per_command = {}  
  
class cmakelang.configuration.ParseConfig(**kwargs)  
    Bases: cmakelang.config_util.ConfigObject  
  
    Options affecting listfile parsing  
  
    additional_commands = {'foo': {'flags': ['BAR', 'BAZ'], 'kwargs': {'DEPENDS': '*'},  
                                'override_spec': {}}  
  
    override_spec = {}  
  
    proptags = []  
  
    vartags = []
```

16.4 cmake_format.common module

```
class cmakelang.common.EnumObject(value)  
    Bases: object  
  
    Simple enumeration base. Design inspired by clang python bindings BaseEnumeration. Subclasses must provide  
    class member _id_map.  
  
    as_dict()  
  
    classmethod assign_names()  
  
    classmethod from_id(qid)  
  
    classmethod from_name(name)  
  
    classmethod get(name, default=None)  
  
    name  
        Get the enumeration name of this value.  
  
    classmethod register_value(value, obj)  
  
exception cmakelang.common.FormatError(msg=None)  
    Bases: Exception  
  
    Raised during format or format -check indicating that the program should exit with nonzero status code.  
  
exception cmakelang.common.InternalError(msg=None)  
    Bases: Exception  
  
    Raised when we encounter something we do not expect, indicating a problem with the code itself.  
  
exception cmakelang.common.UserError(msg=None)  
    Bases: Exception  
  
    Raised when we encounter a fatal problem with usage: e.g. parse error, config error, input error, etc.  
  
cmakelang.common.stable_wrap(wrapper, paragraph_text)  
    textwrap doesn't appear to be stable. We run it multiple times until it converges
```

16.5 cmake_format.lexer module

16.6 cmake_format.markup module

Functions for parsing comments in markup

```
class cmakelang.markup.CommentItem(kind)
    Bases: object

class cmakelang.markup.CommentType(value)
    Bases: cmakelang.common.EnumObject

    BULLET_LIST = CommentType.BULLET_LIST
    ENUM_LIST = CommentType.ENUM_LIST
    FENCE = CommentType.FENCE
    NOTE = CommentType.NOTE
    PARAGRAPH = CommentType.PARAGRAPH
    RULER = CommentType.RULER
    SEPARATOR = CommentType.SEPARATOR
    VERBATIM = CommentType.VERBATIM
```

```
cmakelang.markup.format_item(config, line_width, item)
    Return lines of formatted text based on the type of markup
```

```
cmakelang.markup.format_items(config, line_width, items)
    Return lines of formatted text for the sequence of items within a comment block
```

```
cmakelang.markup.is_hashruler(item)
    Return true if the markup item is a hash ruler, i.e.:
```

```
#####
# Like this ^^^ or this vvv
#####
```

```
cmakelang.markup.parse(lines, config=None)
    Parse comment lines. Returns objects of different formatable entities
```

16.7 cmake_format.parse module

```
class cmakelang.parse.MockEverything
    Bases: object
```

Dummy object which implements any interface by mocking all functions with an empty implementation that returns None

```
class cmakelang.parse.ParseContext(parse_db=None, lint_ctx=None, config=None)
    Bases: object
```

Global context passed through every function in the parse stack.

```
pusharg(node)
```

`cmakelang.parse.parse` (*tokens*, *ctx=None*)
digest tokens, then layout the digested blocks.

16.8 `cmake_format.parse.funs` module

Statement parser functions

`cmakelang.parse.funs.get_funtree` (*cmds**spec*)

`cmakelang.parse.funs.get_parse_db` ()

Returns a dictionary mapping statement name to parse functor for that statement.

CHAPTER 17

Indices and tables

- `genindex`
- `modindex`
- `search`

C

- `cmakelang`, [153](#)
- `cmakelang.common`, [156](#)
- `cmakelang.configuration`, [153](#)
- `cmakelang.markup`, [157](#)
- `cmakelang.parse`, [157](#)
- `cmakelang.parse.funs`, [158](#)

A

additional_commands (cmake-
lang.configuration.ParseConfig attribute),
156

always_wrap (cmake-
lang.configuration.FormattingConfig attribute),
154

argument_var_pattern (cmake-
lang.configuration.LinterConfig attribute),
155

as_dict() (cmakelang.common.EnumObject method),
156

assign_names() (cmakelang.common.EnumObject
class method), 156

autosort (cmakelang.configuration.FormattingConfig
attribute), 154

B

bullet_char (cmake-
lang.configuration.MarkupConfig attribute),
155

BULLET_LIST (cmakelang.markup.CommentType at-
tribute), 157

C

canonicalize_hashrulers (cmake-
lang.configuration.MarkupConfig attribute),
155

cmakelang (module), 153

cmakelang.common (module), 156

cmakelang.configuration (module), 153

cmakelang.markup (module), 157

cmakelang.parse (module), 157

cmakelang.parse.funs (module), 158

command_case (cmake-
lang.configuration.FormattingConfig attribute),
154

CommentItem (class in cmakelang.markup), 157

CommentType (class in cmakelang.markup), 157

Configuration (class in cmakelang.configuration),
153

D

dangle_align (cmake-
lang.configuration.FormattingConfig attribute),
154

dangle_parens (cmake-
lang.configuration.FormattingConfig attribute),
154

disable (cmakelang.configuration.FormattingConfig
attribute), 154

disabled_codes (cmake-
lang.configuration.LinterConfig attribute),
155

E

emit_byteorder_mark (cmake-
lang.configuration.EncodingConfig attribute),
154

enable_markup (cmake-
lang.configuration.MarkupConfig attribute),
155

enable_sort (cmake-
lang.configuration.FormattingConfig attribute),
154

encode (cmakelang.configuration.Configuration at-
tribute), 153

EncodingConfig (class in cmakelang.configuration),
154

enum_char (cmakelang.configuration.MarkupConfig
attribute), 155

ENUM_LIST (cmakelang.markup.CommentType at-
tribute), 157

EnumObject (class in cmakelang.common), 156

explicit_trailing_pattern (cmake-
lang.configuration.MarkupConfig attribute),
155

F

FENCE (*cmakelang.markup.CommentType* attribute), 157

fence_pattern (*cmakelang.configuration.MarkupConfig* attribute), 155

first_comment_is_literal (*cmakelang.configuration.MarkupConfig* attribute), 155

format (*cmakelang.configuration.Configuration* attribute), 153

format_item() (in module *cmakelang.markup*), 157

format_items() (in module *cmakelang.markup*), 157

FormatError, 156

FormattingConfig (class in *cmakelang.configuration*), 154

fractional_tab_policy (*cmakelang.configuration.FormattingConfig* attribute), 154

from_id() (*cmakelang.common.EnumObject* class method), 156

from_name() (*cmakelang.common.EnumObject* class method), 156

function_pattern (*cmakelang.configuration.LinterConfig* attribute), 155

G

get() (*cmakelang.common.EnumObject* class method), 156

get_funtree() (in module *cmakelang.parse.funs*), 158

get_parse_db() (in module *cmakelang.parse.funs*), 158

global_var_pattern (*cmakelang.configuration.LinterConfig* attribute), 155

H

hashruler_min_length (*cmakelang.configuration.MarkupConfig* attribute), 155

I

input_encoding (*cmakelang.configuration.EncodingConfig* attribute), 154

internal_var_pattern (*cmakelang.configuration.LinterConfig* attribute), 155

InternalError, 156

is_hashruler() (in module *cmakelang.markup*), 157

K

keyword_case (*cmakelang.configuration.FormattingConfig* attribute), 154

keyword_pattern (*cmakelang.configuration.LinterConfig* attribute), 155

L

layout_passes (*cmakelang.configuration.FormattingConfig* attribute), 154

line_ending (*cmakelang.configuration.FormattingConfig* attribute), 154

line_width (*cmakelang.configuration.FormattingConfig* attribute), 154

linewidth (*cmakelang.configuration.FormattingConfig* attribute), 154

lint (*cmakelang.configuration.Configuration* attribute), 153

LinterConfig (class in *cmakelang.configuration*), 154

literal_comment_pattern (*cmakelang.configuration.MarkupConfig* attribute), 155

local_var_pattern (*cmakelang.configuration.LinterConfig* attribute), 155

M

macro_pattern (*cmakelang.configuration.LinterConfig* attribute), 155

markup (*cmakelang.configuration.Configuration* attribute), 153

MarkupConfig (class in *cmakelang.configuration*), 155

max_arguments (*cmakelang.configuration.LinterConfig* attribute), 155

max_branches (*cmakelang.configuration.LinterConfig* attribute), 155

max_conditionals_custom_parser (*cmakelang.configuration.LinterConfig* attribute), 155

max_lines_hwrap (*cmakelang.configuration.FormattingConfig* attribute), 154

max_localvars (*cmakelang.configuration.LinterConfig* attribute), 155

- max_pargs_hwrap (*cmakelang.configuration.FormattingConfig* attribute), 154
- max_prefix_chars (*cmakelang.configuration.FormattingConfig* attribute), 154
- max_returns (*cmakelang.configuration.LinterConfig* attribute), 155
- max_rows_cmdline (*cmakelang.configuration.FormattingConfig* attribute), 154
- max_statement_spacing (*cmakelang.configuration.LinterConfig* attribute), 155
- max_statements (*cmakelang.configuration.LinterConfig* attribute), 155
- max_subgroups_hwrap (*cmakelang.configuration.FormattingConfig* attribute), 154
- min_prefix_chars (*cmakelang.configuration.FormattingConfig* attribute), 154
- min_statement_spacing (*cmakelang.configuration.LinterConfig* attribute), 155
- misc (*cmakelang.configuration.Configuration* attribute), 153
- MiscConfig (class in *cmakelang.configuration*), 155
- MockEverything (class in *cmakelang.parse*), 157
- ## N
- name (*cmakelang.common.EnumObject* attribute), 156
- NOTE (*cmakelang.markup.CommentType* attribute), 157
- ## O
- output_encoding (*cmakelang.configuration.EncodingConfig* attribute), 154
- override_spec (*cmakelang.configuration.ParseConfig* attribute), 156
- ## P
- PARAGRAPH (*cmakelang.markup.CommentType* attribute), 157
- parse (*cmakelang.configuration.Configuration* attribute), 153
- parse() (in module *cmakelang.markup*), 157
- parse() (in module *cmakelang.parse*), 157
- ParseConfig (class in *cmakelang.configuration*), 156
- ParseContext (class in *cmakelang.parse*), 157
- per_command (*cmakelang.configuration.MiscConfig* attribute), 155
- private_var_pattern (*cmakelang.configuration.LinterConfig* attribute), 155
- proptags (*cmakelang.configuration.ParseConfig* attribute), 156
- public_var_pattern (*cmakelang.configuration.LinterConfig* attribute), 155
- pusharg() (*cmakelang.parse.ParseContext* method), 157
- ## R
- register_value() (*cmakelang.common.EnumObject* class method), 156
- require_valid_layout (*cmakelang.configuration.FormattingConfig* attribute), 154
- resolve_for_command() (*cmakelang.configuration.Configuration* method), 153
- RULER (*cmakelang.markup.CommentType* attribute), 157
- ruler_pattern (*cmakelang.configuration.MarkupConfig* attribute), 155
- ## S
- separate_ctrl_name_with_space (*cmakelang.configuration.FormattingConfig* attribute), 154
- separate_fn_name_with_space (*cmakelang.configuration.FormattingConfig* attribute), 154
- SEPARATOR (*cmakelang.markup.CommentType* attribute), 157
- set_line_ending() (*cmakelang.configuration.FormattingConfig* method), 154
- stable_wrap() (in module *cmakelang.common*), 156
- ## T
- tab_size (*cmakelang.configuration.FormattingConfig* attribute), 154
- ## U
- use_tabchars (*cmakelang.configuration.FormattingConfig* attribute), 154
- UserError, 156
- ## V
- vartags (*cmakelang.configuration.ParseConfig* attribute), 156

VERBATIM (*cmakelang.markup.CommentType* attribute), [157](#)